

STF19NM50N, STP19NM50N, STW19NM50N

Datasheet

N-channel 500 V, 200 mΩ typ., 14 A MDmesh II Power MOSFET in a TO-220FP, TO-220 and TO-247 packages





Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
STF19NM50N	500 V	250 mΩ	14 A
STP19NM50N			
STW19NM50N			

- 100% avalanche tested
- Low input capacitance and gate charge
- Low gate input resistance

Applications

- Switching applications

Description

These devices are N-channel Power MOSFETs developed using the second generation of MDmesh technology. These revolutionary Power MOSFETs associate a vertical structure to the company's strip layout to yield one of the world's lowest on-resistance and gate charge. They are therefore suitable for the most demanding high-efficiency converters.

Product status links
STF19NM50N
STP19NM50N
STW19NM50N

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value		Unit
		TO-220 TO-247	TO-220FP	
V_{DS}	Drain-source voltage	500		V
V_{GS}	Gate-source voltage	±25		V
I_D	Drain current (continuous) at T_C = 25 °C	14		A
	Drain current (continuous) at T_C = 100 °C	10		
I_{DM}(1)	Drain current (pulsed)	56		A
P_{TOT}	Total power dissipation at T_C = 25 °C	110	30	W
V_{ISO}	Insulation withstand voltage (RMS) from all,three leads to external heat sink (t = 1 s; T_C = 25 °C)	-	2.5	kV
dv/dt(2)	Peak diode recovery voltage slope	15		V/ns
°C	Storage temperature range	-55 to 150		°C
T_J	Maximum operating junction temperature	150		°C

1. *Pulse width limited by safe operating area.*
2. *I_{SD} ≤ 14 A, di/dt ≤ 400 A/µs, V_{DS} (peak) ≤ $V_{(BR)DSS}$, V_{DD} = 400 V.*

Table 2. Thermal data

Symbol	Parameter	Value			Unit
		TO-220	TO-247	TO-220FP	
R_{thJC}	Thermal resistance, junction-to-case	1.14		4.17	°C/W
R_{thJA}	Thermal resistance, junction-to-ambient	62.5	50	62.5	°C/W

Table 3. Avalanche characteristics

Symbol	Parameter	Value	Unit
I_{AR}	Avalanche current, repetitive or not-repetitive (pulse width limited by T_J max.)	6	A
E_{AS}	Single pulse avalanche energy (starting T_J = 25 °C, I_D = I_{AR}, V_{DD} = 50 V)	208	mJ

2 Electrical characteristics

(T_C = 25 °C unless otherwise specified)

Table 4. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	I_D = 1 mA, V_{GS} = 0 V	500	-	-	V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 500 V	-	-	1	µA
		V_{GS} = 0 V, V_{DS} = 500 V, T_C = 125 °C(1)	-	-	100	
I_{GSS}	Gate body leakage current	V_{DS} = 0 V, V_{GS} = ±25 V	-	-	±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	2	3	4	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 7 A	-	200	250	mΩ

1. *Specified by design, not tested in production.*

Table 5. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 50 V, f = 1 MHz, V_{GS} = 0 V	-	1000	-	pF
C_{oss}	Output capacitance		-	72	-	pF
C_{rss}	Reverse transfer capacitance		-	3	-	pF
$C_{oss\ eq.}$(1)	Equivalent capacitance time related	V_{DS} = 0 to 400 V, V_{GS} = 0 V	-	202	-	pF
Q_g	Total gate charge	V_{DD} = 400 V, I_D = 14 A, V_{GS} = 0 to 10 V (see the Figure 16. Test circuit for gate charge behavior)	-	34	-	nC
Q_{gs}	Gate-source charge		-	5	-	nC
Q_{gd}	Gate-drain charge		-	18	-	nC
R_g	Intrinsic gate resistance	f = 1 MHz, I_D = 0 A	-	4.4	-	Ω

1. *$C_{oss\ eq.}$ is defined as a constant equivalent capacitance giving the same charging time as C_{oss} when V_{DS} increases from 0 to 80% V_{DSS}.*

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 250 V, I_D = 7 A, R_G = 4.7 Ω, V_{GS} = 10 V (see the Figure 15. Test circuit for resistive load switching times and Figure 20. Switching time waveform)	-	12	-	ns
t_r	Rise time		-	16	-	ns
$t_{d(off)}$	Turn-off delay time		-	61	-	ns
t_f	Fall time		-	17	-	ns

Table 7. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-	-	14	A
I_{SDM}(1)	Source-drain current (pulsed)		-	-	56	A
V_{SD}(2)	Forward on voltage	I_{SD} = 14 A, V_{GS} = 0 V	-	-	1.5	V
t_{rr}	Reverse recovery time	I_{SD} = 14 A, di/dt = 100 A/µs, V_{DD} = 60 V (see the Figure 17. Test circuit for inductive load switching and diode recovery times)	-	296	-	ns
Q_{rr}	Reverse recovery charge		-	3.5	-	µC
I_{RRM}	Reverse recovery current		-	23	-	A
t_{rr}	Reverse recovery time	I_{SD} = 14 A, di/dt = 100 A/µs, V_{DD} = 60 V, T_J = 150 °C (see the Figure 17. Test circuit for inductive load switching and diode recovery times)	-	346	-	ns
Q_{rr}	Reverse recovery charge		-	4	-	µC
I_{RRM}	Reverse recovery current		-	24	-	A

1. *Pulse width limited by safe operating area.*
2. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%.*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area for TO-220FP




Figure 2. Normalized transient thermal impedance for TO-220FP




Figure 3. Safe operating area for TO-220




Figure 4. Normalized transient thermal impedance for TO-220




Figure 5. Safe operating area for TO-247




Figure 6. Normalized transient thermal impedance for TO-247




Figure 7. Typical output characteristics




Figure 8. Typical transfer characteristics




Figure 9. Typical gate charge characteristics




Figure 10. Typical capacitance characteristics




Figure 11. Typical drain-source on-resistance




Figure 12. Normalized breakdown voltage vs temperature




Figure 13. Normalized gate threshold vs temperature






Figure 14. Normalized on-resistance vs temperature




3 Test circuits

Figure 15. Test circuit for resistive load switching times




AM01468v1

Figure 16. Test circuit for gate charge behavior




AM01469v1

Figure 17. Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 18. Unclamped inductive load test circuit




AM01471v1

Figure 19. Unclamped inductive waveform



AM01472v1

Figure 20. Switching time waveform




AM01473v1

4 Package information

To meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 TO-220FP type B package information

Figure 21. TO-220FP type B package outline



7012510_B_rev.14

Table 8. **TO-220FP type B package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
B	2.50		2.70
D	2.50		2.75
E	0.45		0.70
F	0.75		1.00
F1	1.15		1.70
F2	1.15		1.70
G	4.95		5.20
G1	2.40		2.70
H	10.00		10.40
L2		16.00	
L3	28.60		30.60
L4	9.80		10.60
L5	2.90		3.60
L6	15.90		16.40
L7	9.00		9.30
Dia	3.00		3.20

4.2 TO-220 type A package information

Figure 22. **TO-220 type A package outline**





Table 9. **TO-220 type A package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
b	0.61		0.88
b1	1.14		1.55
c	0.48		0.70
D	15.25		15.75
D1		1.27	
E	10.00		10.40
e	2.40		2.70
e1	4.95		5.15
F	1.23		1.32
H1	6.20		6.60
J1	2.40		2.72
L	13.00		14.00
L1	3.50		3.93
L20		16.40	
L30		28.90	
øP	3.75		3.85
Q	2.65		2.95
Slug flatness		0.03	0.10

4.3 TO-247 package information

Figure 23. **TO-247 package outline**



0075325_11

Table 10. **TO-247 package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
A2		1.27	
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70

5 Ordering information

Table 11. **Order codes**

Order codes	Marking	Package	Packing
STF19NM50N	19NM50N	TO-220FP	Tube
STP19NM50N		TO-220	
STW19NM50N		TO-247	

Revision history

Table 12. **Document revision history**

Date	Revision	Changes
09-Feb-2010	1	First release.
03-Sep-2013	2	Updated: *Section 2.1: Electrical characteristics (curves)*. Updated: *Section 4: Package mechanical data*. Minor text changes.
29-Jan-2026	3	Updated Section 4: Package information. Minor text changes.

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Test circuits** 8
4 **Package information** 9
4.1 TO-220FP type B package information 9
4.2 TO-220 type A package information 11
4.3 TO-247 package information 13
5 **Ordering information** 15
Revision history 16

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2026 STMicroelectronics – All rights reserved