
# STD65N3LLH5
# STU65N3LLH5

## N-channel 30 V, 0.0061 Ω, 65 A, DPAK, IPAK STripFET™ V Power MOSFET

## Features

| Type | $V_{DSS}$ | $R_{DS(on)}$ max | $I_D$ |
|---|---|---|---|
| STD65N3LLH5 | 30 V | 0.0069 Ω | 65 A |
| STU65N3LLH5 | 30 V | 0.0073 Ω | 65 A |

- $R_{DS(on)}$ * $Q_g$ industry benchmark
- Extremely low on-resistance $R_{DS(on)}$
- Very low switching gate charge
- High avalanche ruggedness
- Low gate drive power losses




DPAK IPAK

## Application

Switching applications

## Description

This STripFET™V Power MOSFET technology is among the latest improvements, which have been especially tailored to achieve very low on-state resistance providing also one of the best-in-class figure of merit.

**Figure 1. Internal schematic diagram**





**Table 1. Device summary**

| Order code | Marking | Package | Packaging |
|---|---|---|---|
| STD65N3LLH5 | 65N3LLH5 | DPAK | Tape and reel |
| STU65N3LLH5 | 65N3LLH5 | IPAK | Tube |

# Contents

1 Electrical ratings . . . . . 3

2 Electrical characteristics . . . . . 4

2.1 Electrical characteristics (curves) . . . . . 6

3 Test circuits . . . . . 8

4 Package mechanical data . . . . . 9

5 Packaging mechanical data . . . . . 14

6 Revision history . . . . . 16

# 1 Electrical ratings

**Table 2. Absolute maximum ratings**

| Symbol | Parameter | Value | Unit |
|---|---|---|---|
| $V_{DS}$ | Drain-source voltage ($V_{GS}$=0) | 30 | V |
| $V_{GS}$ | Gate-source voltage | ± 22 | V |
| $I_D$ | Drain current (continuous) at $T_C$ = 25 °C | 65 | A |
| $I_D$ | Drain current (continuous) at $T_C$ = 100 °C | 46 | A |
| $I_{DM}$ (1) | Drain current (pulsed) | 260 | A |
| $P_{TOT}$ | Total dissipation at $T_C$ = 25 °C | 50 | W |
| | Derating factor | 0.3 | W/°C |
| $E_{AS}$ (2) | Single pulse avalanche energy | TBD | mJ |
| $T_j$<br>$T_{stg}$ | Operating junction temperature<br>Storage temperature | -55 to 175 | °C |

1. Pulse width limited by safe operating area.
2. Starting Tj = 25 °C, Id = 32.5 A, Vdd = 12 V.

**Table 3. Thermal resistance**

| Symbol | Parameter | Value | Unit |
|---|---|---|---|
| Rthj-case | Thermal resistance junction-case max | 3 | °C/W |
| Rthj-amb | Thermal resistance junction-case max | 100 | °C/W |
| $T_j$ | Maximum lead temperature for soldering purpose | 275 | °C |

# 2 Electrical characteristics

($T_{CASE}$ = 25 °C unless otherwise specified).

**Table 4. Static**

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $V_{(BR)DSS}$ | Drain-source breakdown Voltage | $I_D$ = 250 µA, $V_{GS}$= 0 | 30 | | | V |
| $I_{DSS}$ | Zero gate voltage drain current ($V_{GS}$ = 0) | $V_{DS}$ = 30 V<br>$V_{DS}$ = 30 V,Tc = 125 °C | | | 1<br>10 | µA<br>µA |
| $I_{GSS}$ | Gate body leakage current ($V_{DS}$ = 0) | $V_{GS}$ = ± 22 V | | | ±100 | nA |
| $V_{GS(th)}$ | Gate threshold voltage | $V_{DS}$= $V_{GS}$, $I_D$ = 250 µA | 1 | 1.8 | 3 | V |
| $R_{DS(on)}$ | Static drain-source on resistance | $V_{GS}$= 10 V, $I_D$= 32.5 A SMD version | | 0.0061 | 0.0069 | Ω |
| | | $V_{GS}$= 10 V, $I_D$= 32.5 A | | 0.0065 | 0.0073 | Ω |
| | | $V_{GS}$= 4.5 V, $I_D$= 32.5 A SMD version | | 0.0084 | 0.0093 | Ω |
| | | $V_{GS}$= 4.5 V, $I_D$= 32.5 A | | 0.0088 | 0.0097 | Ω |

**Table 5. Dynamic**

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $C_{iss}$<br>$C_{oss}$<br>$C_{rss}$ | Input capacitance<br>Output capacitance<br>Reverse transfer capacitance | $V_{DS}$ =25 V, f=1 MHz, $V_{GS}$=0 | - | 1290<br>240<br>32 | - | pF<br>pF<br>pF |
| $Q_g$<br>$Q_{gs}$<br>$Q_{gd}$ | Total gate charge<br>Gate-source charge<br>Gate-drain charge | $V_{DD}$=15 V, $I_D$ = 65 A<br>$V_{GS}$ =4.5 V<br>*(Figure 14)* | - | 8<br>3.6<br>3.4 | - | nC<br>nC<br>nC |
| $R_g$ | Intrinsic gate resistance | f=1 MHz Gate DC Bias=0<br>test signal level = 20 mV<br>open drain | | 1.7 | | Ω |

**Table 6. Switching on/off (resistive load)**

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $t_{d(on)}$<br>$t_r$ | Turn-on delay time<br>Rise time | $V_{DD}$=10 V, $I_D$= 65 A,<br>$R_G$=4.7 Ω, $V_{GS}$= 10 V<br>*(Figure 13 and Figure 18)* | - | 8.6<br>11.2 | - | ns<br>ns |
| $t_{d(off)}$<br>$t_f$ | Turn-off delay time<br>Fall time | $V_{DD}$=10 V, $I_D$= 25 A,<br>$R_G$=4.7 Ω, $V_{GS}$= 10 V<br>*(Figure 13 and Figure 18)* | - | 32.4<br>6 | - | ns<br>ns |

**Table 7. Source drain diode**

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---|---|---|---|---|---|---|
| $I_{SD}$<br>$I_{SDM}$ | Source-drain current<br>Source-drain current (pulsed)(1) | | - | | 65<br>260 | A<br>A |
| $V_{SD}$ | Forward on voltage | $I_{SD}$=32.5 A, $V_{GS}$=0 | - | | 1.1 | V |
| $t_{rr}$<br>$Q_{rr}$<br>$I_{RRM}$ | Reverse recovery time<br>Reverse recovery charge<br>Reverse recovery current | $I_{SD}$=32.5 A,<br>di/dt =100 A/µs,<br>$V_{DD}$=20 V, *(Figure 15)* | - | 22<br>15<br>1.4 | | ns<br>nC<br>A |

1. Pulsed: pulse duration = 300µs, duty cycle 1.5%.

## 2.1 Electrical characteristics (curves)

**Figure 2. Safe operating area**





**Figure 3. Thermal impedance**





**Figure 4. Output characteristics**





**Figure 5. Transfer characteristics**





**Figure 6. Normalized $B_{VDSS}$ vs temperature**





**Figure 7. Static drain-source on resistance**




**Figure 8. Gate charge vs gate-source voltage**





**Figure 9. Capacitance variations**





**Figure 10. Normalized gate threshold voltage vs temperature**





**Figure 11. Normalized on resistance vs temperature**






**Figure 12. Source-drain diode forward characteristics**



# 3 Test circuits

**Figure 13. Switching times test circuit for resistive load**





**Figure 14. Gate charge test circuit**





**Figure 15. Test circuit for inductive load switching and diode recovery times**





**Figure 16. Unclamped inductive load test circuit**





**Figure 17. Unclamped inductive waveform**






**Figure 18. Switching time waveform**




# 4 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

**Table 8. DPAK (TO-252) mechanical data**

| Dim. | mm | | |
|---|---|---|---|
| | Min. | Typ. | Max. |
| A | 2.20 | | 2.40 |
| A1 | 0.90 | | 1.10 |
| A2 | 0.03 | | 0.23 |
| b | 0.64 | | 0.90 |
| b4 | 5.20 | | 5.40 |
| c | 0.45 | | 0.60 |
| c2 | 0.48 | | 0.60 |
| D | 6.00 | | 6.20 |
| D1 | | 5.10 | |
| E | 6.40 | | 6.60 |
| E1 | | 4.70 | |
| e | | 2.28 | |
| e1 | 4.40 | | 4.60 |
| H | 9.35 | | 10.10 |
| L | 1 | | |
| L1 | | 2.80 | |
| L2 | | 0.80 | |
| L4 | 0.60 | | 1 |
| R | | 0.20 | |
| V2 | 0° | | 8° |

**Figure 19. DPAK footprint[a]**




a. All dimension are in millimeters

**Figure 20. DPAK (TO-252) drawing**





Table 9. IPAK (TO-251) mechanical data

| Dim. | mm. | | |
|---|---|---|---|
| | Min. | Typ. | Max. |
| A | 2.20 | | 2.40 |
| A1 | 0.90 | | 1.10 |
| b | 0.64 | | 0.90 |
| b2 | | | 0.95 |
| b4 | 5.20 | | 5.40 |
| B5 | | 0.3 | |
| c | 0.45 | | 0.60 |
| c2 | 0.48 | | 0.60 |
| D | 6.00 | | 6.20 |
| E | 6.40 | | 6.60 |
| e | | 2.28 | |
| e1 | 4.40 | | 4.60 |
| H | | 16.10 | |
| L | 9.00 | | 9.40 |
| L1 | 0.80 | | 1.20 |
| L2 | | 0.80 | 1.00 |
| V1 | | $10^{o}$ | |

**Figure 21. IPAK (TO-251) drawing**



# 5 Packaging mechanical data

**Table 10. DPAK (TO-252) tape and reel mechanical data**

| Tape | | | Reel | | |
|---|---|---|---|---|---|
| Dim. | mm | | Dim. | mm | |
| | Min. | Max. | | Min. | Max. |
| A0 | 6.8 | 7 | A | | 330 |
| B0 | 10.4 | 10.6 | B | 1.5 | |
| B1 | | 12.1 | C | 12.8 | 13.2 |
| D | 1.5 | 1.6 | D | 20.2 | |
| D1 | 1.5 | | G | 16.4 | 18.4 |
| E | 1.65 | 1.85 | N | 50 | |
| F | 7.4 | 7.6 | T | | 22.4 |
| K0 | 2.55 | 2.75 | | | |
| P0 | 3.9 | 4.1 | Base qty. | | 2500 |
| P1 | 7.9 | 8.1 | Bulk qty. | | 2500 |
| P2 | 1.9 | 2.1 | | | |
| R | 40 | | | | |
| T | 0.25 | 0.35 | | | |
| W | 15.7 | 16.3 | | | |

**Figure 22. Tape for DPAK (TO-252)**






**Figure 23. Reel for DPAK (TO-252)**



# 6 Revision history

Table 11. Document revision history

| Date | Revision | Changes |
|---|---|---|
| 19-May-2011 | 1 | First release. |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER’S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2011 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

**www.st.com**