

STL56N3LLH5

Datasheet

N-channel 30 V, 7.6 mΩ typ., 56 A STripFET H5 Power MOSFET in a PowerFLAT 5x6 package



PowerFLAT 5x6



Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
STL56N3LLH5	30 V	9 mΩ	56 A

- Low on-resistance $R_{DS(on)}$
- High avalanche ruggedness
- Low gate drive power loss

Applications

- Switching applications

Description

This device is an N-channel Power MOSFET developed using STMicroelectronics' STripFET H5 technology. The device has been optimized to achieve very low on-state resistance, contributing to a FoM that is among the best in its class.

Product status link
STL56N3LLH5

Product summary	
Order code	STL56N3LLH5
Marking	56N3LLH5
Package	PowerFLAT 5x6
Packing	Tape and reel

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	30	V
V_{GS}	Gate-source voltage	+22 / -20	V
I_D(1)	Drain current (continuous) at T_C = 25 °C	56	A
	Drain current (continuous) at T_C= 100 °C	37	A
I_D(2)	Drain current (continuous) at T_{pcb} = 25 °C	15	A
	Drain current (continuous) at T_{pcb}= 100 °C	10	A
I_{DM}(1)(3)	Drain current (pulsed)	224	A
I_{DM}(2)(3)	Drain current (pulsed)	60	A
P_{TOT}(1)	Total power dissipation at T_C = 25 °C	62.5	W
P_{TOT}(2)	Total power dissipation at T_{pcb} = 25 °C	4	W
E_{AS}(4)	Single pulse avalanche energy	150	mJ
T_{stg}	Storage temperature range	- 55 to 150	°C
T_J	Operating junction temperature range		°C

1. *This value is rated according to $R_{thj\text{-}c}$.*
2. *This value is rated according to $R_{thj\text{-}pcb}$.*
3. *Pulse width is limited by safe operating area.*
4. *Starting T_J = 25 °C, I_D = 56 A, V_{DD} = 50 V.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
$R_{thj\text{-}case}$	Thermal resistance junction-case	2	°C/W
$R_{thj\text{-}pcb}$(1)	Thermal resistance junction-pcb	31.3	

1. *When mounted on a 1-inch² FR-4 board, 2oz Cu, t < 10 s.*

2 Electrical characteristics

(T_C = 25 °C unless otherwise specified)

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 250 µA	30			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 30 V			1	µA
		V_{GS} = 0 V, V_{DS} = 30 V, T_C = 125 °C			10	µA
I_{GSS}	Gate-body leakage current	V_{DS} = 0 V, V_{GS} = +22 / -20 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	1		2.5	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 7.5 A		7.6	9	mΩ
		V_{GS} = 4.5 V, I_D = 7.5 A		9.9	11.2	

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 25 V, f = 1 MHz, V_{GS} = 0 V	-	950		pF
C_{oss}	Output capacitance		-	193		pF
C_{rss}	Reverse transfer capacitance		-	27		pF
Q_g	Total gate charge	V_{DD} = 15 V, I_D = 15 A, V_{GS} = 4.5 V (see Figure 13. Test circuit for gate charge behavior)	-	6.5	10	nC
Q_{gs}	Gate-source charge		-	3.3		nC
Q_{gd}	Gate-drain charge		-	2.4		nC
R_g	Gate input resistance	f = 1 MHz, gate DC Bias = 0 V, test signal level = 20 mV, I_D = 0 A	-	1.7	2.5	Ω

Table 5. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 15 V, I_D = 7.5 A, R_G = 4.7 Ω, V_{GS} = 10 V (see Figure 12. Test circuit for resistive load switching times and Figure 17. Switching time waveform)	-	10.8	-	ns
t_r	Rise time		-	15.6	-	ns
$t_{d(off)}$	Turn-off-delay time		-	14.2	-	ns
t_f	Fall time		-	6	-	ns

Table 6. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		56	A
I_{SDM}(1)	Source-drain current (pulsed)		-		224	A
V_{SD}(2)	Forward on voltage	V_{GS} = 0 V, I_{SD} = 15 A	-		1.1	V
t_{rr}	Reverse recovery time	I_{SD} = 15 A, di/dt = 100 A/µs,	-	20	36	ns
Q_{rr}	Reverse recovery charge	V_{DD} = 25 V, T_J = 150 °C	-	10	18	nC
I_{RRM}	Reverse recovery current	(see Figure 14. Test circuit for inductive load switching and diode recovery times)	-	1		A

1. *Pulse width limited by safe operating area.*
2. *Pulse test: pulse duration = 300 µs, duty cycle 1.5%.*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Thermal impedance




Figure 3. Output characteristics




Figure 4. Transfer characteristics




Figure 5. Gate charge vs gate-source voltage




Figure 6. Static drain-source on-resistance




Figure 7. Capacitance variations




Figure 8. Normalized gate threshold voltage vs temperature




Figure 9. Normalized on-resistance vs temperature




Figure 10. Normalized $V_{(BR)DSS}$ vs temperature





Figure 11. Source-drain diode forward characteristics



3 Test circuits

Figure 12. Test circuit for resistive load switching times




Figure 13. Test circuit for gate charge behavior




Figure 14. Test circuit for inductive load switching and diode recovery times




Figure 15. Unclamped inductive load test circuit




Figure 16. Unclamped inductive waveform





Figure 17. Switching time waveform




4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 PowerFLAT 5x6 type R package information

Figure 18. PowerFLAT 5x6 type R package outline



A0ER_8231817_Rev20

Table 7. **PowerFLAT 5x6 type R mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	0.80		1.00
A1	0.02		0.05
A2		0.25	
b	0.30		0.50
C	5.80	6.00	6.20
D	5.00	5.20	5.40
D2	4.15		4.45
D3	4.05	4.20	4.35
D4	4.80	5.00	5.20
D5	0.25	0.40	0.55
D6	0.15	0.30	0.45
e		1.27	
E	5.95	6.15	6.35
E2	3.50		3.70
E3	2.35		2.55
E4	0.40		0.60
E5	0.08		0.28
E6	0.20	0.325	0.45
E7	0.75	0.90	1.05
K	1.275		1.575
L	0.60		0.80
L1	0.05	0.15	0.25
θ	0°		12°

4.2 PowerFLAT 5x6 type R SUBCON package information

Figure 19. **PowerFLAT 5x6 type R SUBCON package outline**





Table 8. **PowerFLAT 5x6 type R SUBCON package mechanical data**


Dim.	mm		
	Min.	Typ.	Max.
A	0.90	0.95	1.00
A1		0.02	
b	0.35	0.40	0.45
b1		0.30	
c	0.21	0.25	0.34
D			5.10
D1	4.80	4.90	5.00
D2	3.91	4.01	4.11
e	1.17	1.27	1.37
E	5.90	6.00	6.10
E1	5.70	5.75	5.80
E2	3.34	3.44	3.54
E4	0.15	0.25	0.35
E5	0.06	0.16	0.26
H	0.51	0.61	0.71
K	1.10		
L	0.51	0.61	0.71
L1	0.06	0.13	0.20
L2			0.10
P	1.00	1.10	1.20
θ	8°	10°	12°

Figure 20. **PowerFLAT 5x6 recommended footprint (dimensions are in mm)**



4.3 PowerFLAT 5x6 packing information

Figure 21. PowerFLAT 5x6 tape (dimensions are in mm)



Ao	6.30 +/– 0.1
Bo	5.30 +/– 0.1
Ko	1.20 +/– 0.1
F	5.50 +/– 0.1
P1	8.00 +/– 0.1
W	12.00 +/– 0.3

(I) Measured from centreline of sprocket hole to centreline of pocket.

(II) Cumulative tolerance of 10 sprocket holes is ±0.20.

(III) Measured from centreline of sprocket hole to centreline of pocket

Base and bulk quantity 3000 pcs
All dimensions are in millimeters

8234350_Tape_rev_C

Figure 22. PowerFLAT 5x6 package orientation in carrier tape





Figure 23. **PowerFLAT 5x6 reel**



All dimensions are in millimeters

8234350_Reel_rev_C

Revision history

Table 9. **Document revision history**

Date	Revision	Changes
24-Jan-2011	1	First release.
01-Jul-2011	2	Document status promoted from preliminary data to datasheet.
27-Apr-2012	3	Added E_{AS} value in *Table 2: Absolute maximum ratings*. Updated Table *3: Thermal resistance*, *Table 4: On/off states*, *Table 5: Dynamic* and *Table 7: Source drain diode*. Minor text changes.
13-Feb-2013	4	– Added: *Section 5: Packaging mechanical data*. – Updated *Section 4: Package mechanical data*.
25-Jul-2014	5	– Modified: title, features and description in cover page – Modified: I_{SD} and I_{SDM} max values in *Table 7* – Updated: *Figure 2* and *3* – Updated: *Figure 13*, *14*, *15* and *16* – Updated: *Section 4: Package mechanical data* – Minor text changes
19-Feb-2020	6	Updated *Section 4 Package information.*. Minor text changes.
20-May-2021	7	Updated marking in cover page.

Contents

1 **Electrical ratings** 2

2 **Electrical characteristics** 3

2.1 Electrical characteristics (curves) 5

3 **Test circuits** 7

4 **Package information** 8

4.1 PowerFLAT 5x6 type R package information 8

4.2 PowerFLAT 5x6 type R SUBCON package information 10

4.3 PowerFLAT 5x6 packing information 13

Revision history 15

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2021 STMicroelectronics – All rights reserved