

STY139N65M5

Datasheet

N-channel 650 V, 14 mΩ typ., 130 A MDmesh M5 Power MOSFET in a Max247 package



Max247



AM01475v1_noZen

Features

Order code	V_{DS} at T_J max.	$R_{DS(on)}$ max.	I_D
STY139N65M5	710 V	17 mΩ	130 A

- Extremely low $R_{DS(on)}$
- Low gate charge and input capacitance
- Excellent switching performance
- 100% avalanche tested

Applications

- Switching applications

Description

This device is an N-channel Power MOSFET based on the MDmesh M5 innovative vertical process technology combined with the well-known PowerMESH horizontal layout. The resulting product offers extremely low on-resistance, making it particularly suitable for applications requiring high power and superior efficiency.

Product status link
STY139N65M5

Product summary	
Order code	STY139N65M5
Marking	139N65M5
Package	Max247
Packing	Tube

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{GS}	Gate-source voltage	±25	V
I_D	Drain current (continuous) at T_C = 25 °C	130	A
	Drain current (continuous) at T_C = 100 °C	78	
I_{DM}(1)	Drain current (pulsed)	520	A
P_{TOT}	Total power dissipation at T_C = 25 °C	625	W
I_{AR}	Avalanche current, repetitive or not repetitive (pulse width limited by T_J max.)	12	A
E_{AS}	Single pulse avalanche energy (starting T_J = 25 °C, I_D = I_{AR}, V_{DD} = 50 V)	2400	mJ
dv/dt(2)	Peak diode recovery voltage slope	15	V/ns
T_{stg}	Storage temperature range	-55 to 150	°C
T_J	Operating junction temperature range		°C

1. *Pulse width is limited by safe operating area.*
2. *I_{SD} ≤ 130 A, di/dt ≤ 400 A/µs, V_{DS} (peak) < $V_{(BR)DSS}$, V_{DD} = 400 V.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	0.2	°C/W
R_{thJA}	Thermal resistance, junction-to-ambient	30	°C/W

2 Electrical characteristics

T_C = 25 °C unless otherwise specified.

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 1 mA	650			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 650 V			10	µA
		V_{GS} = 0 V, V_{DS} = 650 V, T_C = 125 °C(1)			100	
I_{GSS}	Gate-body leakage current	V_{DS} = 0 V, V_{GS} = ±25 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	3	4	5	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 65 A		14	17	mΩ

1. *Specified by design, not tested in production.*

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 100 V, f = 1 MHz, V_{GS} = 0 V	-	15600	-	pF
C_{oss}	Output capacitance		-	365	-	pF
C_{rss}	Reverse transfer capacitance		-	9	-	pF
$C_{o(tr)}$(1)	Equivalent capacitance time related	V_{DS} = 0 to 520 V, V_{GS} = 0 V	-	1559	-	pF
$C_{o(er)}$(2)	Equivalent capacitance energy related		-	360	-	pF
R_G	Intrinsic gate resistance	f = 1 MHz, I_D = 0 A	-	1.2	-	Ω
Q_g	Total gate charge	V_{DD} = 520 V, I_D = 65 A	-	363	-	nC
Q_{gs}	Gate-source charge	V_{GS} = 0 to 10 V	-	88	-	nC
Q_{gd}	Gate-drain charge	(see Figure 14. Test circuit for gate charge behavior)	-	164	-	nC

1. *$C_{o(tr)}$ is an equivalent capacitance that provides the same charging time as C_{oss} while V_{DS} is rising from 0 V to the stated value.*
2. *$C_{o(er)}$ is an equivalent capacitance that provides the same stored energy as C_{oss} while V_{DS} is rising from 0 V to the stated value.*

Table 5. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(v)}$	Voltage delay time	V_{DD} = 400 V, I_D = 80 A,	-	295	-	ns
$t_{r(v)}$	Voltage rise time	R_G = 4.7 Ω, V_{GS} = 10 V	-	56	-	ns
$t_{f(i)}$	Current fall time	(see Figure 15. Test circuit for inductive load switching and diode recovery times	-	37	-	ns
$t_{c(off)}$	Crossing time	and Figure 18. Switching time waveform)	-	84	-	ns

Table 6. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		130	A
I_{SDM}(1)	Source-drain current (pulsed)		-		520	A
V_{SD}(2)	Forward on voltage	I_{SD} = 130 A, V_{GS} = 0 V	-		1.5	V
t_{rr}	Reverse recovery time	I_{SD} = 130 A, di/dt = 100 A/µs,	-	570		ns
Q_{rr}	Reverse recovery charge	V_{DD} = 100 V	-	15		µC
I_{RRM}	Reverse recovery current	(see Figure 15. Test circuit for inductive load switching and diode recovery times)	-	53		A
t_{rr}	Reverse recovery time	I_{SD} = 130 A, di/dt = 100 A/µs,	-	720		ns
Q_{rr}	Reverse recovery charge	V_{DD} = 100 V, T_J = 150 °C	-	24		µC
I_{RRM}	Reverse recovery current	(see Figure 15. Test circuit for inductive load switching and diode recovery times)	-	68		A

1. *Pulse width is limited by safe operating area.*
2. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%.*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Normalized transient thermal impedance




Figure 3. Typical output characteristics




Figure 4. Typical transfer characteristics




Figure 5. Normalized breakdown voltage vs temperature




Figure 6. Typical drain-source on-resistance




Figure 7. Typical gate charge characteristics




Figure 8. Typical capacitance characteristics




Figure 9. Normalized gate threshold vs temperature




Figure 10. Normalized on-resistance vs temperature




Figure 11. Typical output capacitance stored energy






Figure 12. Typical switching energy vs gate resistance



Note: E_{on} including reverse recovery of a SiC diode.


3 Test circuits

Figure 13. Test circuit for resistive load switching times




AM01468v1

Figure 14. Test circuit for gate charge behavior




AM01469v1

Figure 15. Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 16. Unclamped inductive load test circuit




AM01471v1

Figure 17. Unclamped inductive waveform



AM01472v1

Figure 18. Switching time waveform




AM05540v2

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 Max247 package information

Figure 19. Max247 package outline



0094330_5

Table 7. **Max247 package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.70	-	5.30
A1	2.20	-	2.60
b	1.00	-	1.40
b1	2.00	-	2.40
b2	3.00	-	3.40
c	0.40	-	0.80
D	19.70	-	20.30
e	5.35	-	5.55
E	15.30	-	15.90
L	14.20	-	15.20
L1	3.70	-	4.30

Revision history

Table 8. **Document revision history**

Date	Revision	Changes
09-Mar-2012	1	First release.
04-Apr-2012	2	Inserted new *Section 2.1: Electrical characteristics (curves)*. Updated *Section 4: Package mechanical data*.
19-Apr-2012	3	Document promoted from preliminary data to production data. Updated *Section 4: Package mechanical data*.
24-Jan-2013	4	– Minor text changes – Modified: I_{AR} E_{AS} values on *Table 2*
18-Jul-2022	5	Updated title, Internal schematic, Features and Description on cover page. Updated I_{AR} value in Table 1. Absolute maximum ratings and updated Table 2. Thermal data. Minor text changes.

Contents

1 **Electrical ratings** 2

2 **Electrical characteristics** 3

2.1 Electrical characteristics (curves) 5

3 **Test circuits** 7

4 **Package information** 8

4.1 Max247 package information 8

Revision history 10

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2022 STMicroelectronics – All rights reserved