P-channel 30 V, 24 mΩ typ., 9 A STripFET F6 DeepGATE Power MOSFET in a PowerFLAT 5x6 package



PowerFLAT 5x6



AM01475v4

Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D	P_{TOT}
STL30P3LLH6	30 V	30 mΩ	9 A	4.8 W

- Very low on-resistance
- Very low gate charge
- High avalanche ruggedness
- Low gate drive power loss

Applications

- Switching applications

Description

This device is a P-channel Power MOSFET developed using the STripFET F6 technology, with a new trench gate structure. The resulting Power MOSFET exhibits very low $R_{DS(on)}$ in all packages.

Product status link
STL30P3LLH6

Product summary	
Order code	STL30P3LLH6
Marking	30P3L
Package	PowerFLAT 5x6
Packing	Tape and reel

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	30	V
V_{GS}	Gate-source voltage	±20	V
I_D(1)	Drain current (continuous) at T_C = 25 °C	30	A
	Drain current (continuous) at T_C = 100 °C	18.75	A
I_D(2)	Drain current (continuous) at T_{pcb} = 25 °C	9	A
	Drain current (continuous) at T_{pcb} = 100 °C	6.4	A
I_{DM}(2)(3)	Drain current (pulsed)	36	A
P_{TOT}(1)	Total power dissipation at T_C = 25 °C	75	W
P_{TOT}(2)	Total power dissipation at T_{pcb} = 25 °C	4.8	W
	Derating factor(2)	0.03	W/°C
T_{stg}	Storage temperature range	-55 to 175	°C
T_J	Operating junction temperature range	175	°C

1. *This value is rated according to $R_{thj\text{-}c}$.*
2. *This value is rated according to $R_{thj\text{-}pcb}$.*
3. *Pulse width is limited by safe operating area.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
$R_{thj\text{-}case}$	Thermal resistance junction-case max	2.00	°C/W
$R_{thj\text{-}pcb}$(1)	Thermal resistance junction-pcb, single operation	31.3	°C/W

1. *When mounted on an FR-4 board of 1 inch², 2oz Cu, steady state.*

Note: For the P-channel Power MOSFETs the actual polarity of the voltages and the current must be reversed.

2 Electrical characteristics

T_C = 25 °C unless otherwise specified

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 250 µA	30			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 30 V			1	µA
		V_{GS} = 0 V, V_{DS} = 30 V, T_C = 125 °C			10	µA
I_{GSS}	Gate-body leakage current	V_{DS} = 0 V, V_{GS} = ±20 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	1			V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 4.5 A		24	30	mΩ
		V_{GS} = 4.5 V, I_D = 4.5 A		32	40	mΩ

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{GS} = 0 V, V_{DS} = 25 V, f = 1 MHz	-	1450	-	pF
C_{oss}	Output capacitance		-	178	-	pF
C_{rss}	Reverse transfer capacitance		-	120	-	pF
Q_g	Total gate charge	V_{DD} = 24 V, I_D = 9 A, V_{GS} = 4.5 V (see Figure 13. Gate charge test circuit)	-	12	-	nC
Q_{gs}	Gate-source charge		-	4.4	-	nC
Q_{gd}	Gate-drain charge		-	5	-	nC

Table 5. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 24 V, I_D = 4.5 A, R_G = 4.7 Ω, V_{GS} = 10 V (see Figure 12. Switching times test circuit for resistive load)	-	15	-	ns
t_r	Rise time		-	15	-	ns
$t_{d(off)}$	Turn-off delay time		-	24	-	ns
t_f	Fall time		-	21	-	ns

Note: For the P-channel Power MOSFETs the actual polarity of the voltages and the current must be reversed.

Table 6. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		9	A
I_{SDM}(1)	Source-drain current (pulsed)		-		36	A
V_{SD}(2)	Forward on voltage	V_{GS} = 0 V, I_{SD} = 4.5 A	-		1.1	V
t_{rr}	Reverse recovery time	I_{SD} = 4.5 A, di/dt = 100 A/µs,	-	15		ns
Q_{rr}	Reverse recovery charge	V_{DD} = 16 V, T_J = 150 °C	-	6.5		nC
I_{RRM}	Reverse recovery current	(see Figure 14. Test circuit for inductive load switching and diode recovery times)	-	0.9		A

1. *Pulse width is limited by safe operating area.*
2. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%.*

Note: For the P-channel Power MOSFETs the actual polarity of the voltages and the current must be reversed.

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area



Figure 2. Thermal impedance



Figure 3. Output characteristics



Figure 4. Transfer characteristics



Figure 5. Gate charge vs gate-source voltage



Figure 6. Static drain-source on-resistance



Figure 7. Capacitance variations



Figure 8. Normalized gate threshold voltage vs temperature



Figure 9. Normalized on-resistance vs temperature



Figure 10. Normalized V_{DS} vs temperature



Figure 11. Source-drain diode forward characteristics



3 Test circuits

Figure 12. Switching times test circuit for resistive load



Figure 13. Gate charge test circuit



Figure 14. Test circuit for inductive load switching and diode recovery times



4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 PowerFLAT 5x6 type R package information

Figure 15. PowerFLAT 5x6 type R package outline



A0ER_8231817_Rev20

Table 7. **PowerFLAT 5x6 type R mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	0.80		1.00
A1	0.02		0.05
A2		0.25	
b	0.30		0.50
C	5.80	6.00	6.20
D	5.00	5.20	5.40
D2	4.15		4.45
D3	4.05	4.20	4.35
D4	4.80	5.00	5.20
D5	0.25	0.40	0.55
D6	0.15	0.30	0.45
e		1.27	
E	5.95	6.15	6.35
E2	3.50		3.70
E3	2.35		2.55
E4	0.40		0.60
E5	0.08		0.28
E6	0.20	0.325	0.45
E7	0.75	0.90	1.05
K	1.275		1.575
L	0.60		0.80
L1	0.05	0.15	0.25
θ	0°		12°

4.2 PowerFLAT 5x6 type R SUBCON package information

Figure 16. **PowerFLAT 5x6 type R SUBCON package outline**



8472137_SUBCON_998G_Type_R_REV4

Table 8. PowerFLAT 5x6 type R SUBCON package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	0.90	0.95	1.00
A1		0.02	
b	0.35	0.40	0.45
b1		0.30	
c	0.21	0.25	0.34
D			5.10
D1	4.80	4.90	5.00
D2	3.91	4.01	4.11
e	1.17	1.27	1.37
E	5.90	6.00	6.10
E1	5.70	5.75	5.80
E2	3.34	3.44	3.54
E4	0.15	0.25	0.35
E5	0.06	0.16	0.26
H	0.51	0.61	0.71
K	1.10		
L	0.51	0.61	0.71
L1	0.06	0.13	0.20
L2			0.10
P	1.00	1.10	1.20
θ	8°	10°	12°

Figure 17. **PowerFLAT 5x6 recommended footprint (dimensions are in mm)**



4.3 PowerFLAT 5x6 packing information

Figure 18. PowerFLAT 5x6 tape (dimensions are in mm)



Ao	6.30 +/– 0.1
Bo	5.30 +/– 0.1
Ko	1.20 +/– 0.1
F	5.50 +/– 0.1
P1	8.00 +/– 0.1
W	12.00 +/– 0.3

(I) Measured from centreline of sprocket hole to centreline of pocket.

(II) Cumulative tolerance of 10 sprocket holes is ±0.20.

(III) Measured from centreline of sprocket hole to centreline of pocket

Base and bulk quantity 3000 pcs
All dimensions are in millimeters

8234350_Tape_rev_C

Figure 19. PowerFLAT 5x6 package orientation in carrier tape



Figure 20. **PowerFLAT 5x6 reel**



Revision history

Table 9. Document revision history

Date	Revision	Changes
20-Mar-2013	1	First release
28-Nov-2013	2	– Modified: title – Modified: I_D, P_{TOT} values and *Figure 1* in cover page – Modified: V_{GS}, I_D (at T_{pcb} = 125 °C and T_{pcb} = 100 °C), I_{DM}, P_{TOT} (at T_C = 25 °C and T_{pcb} = 25 °C) and T_{stg} in *Table 2* – Modified: $R_{thj\text{-}pcb}$ value in *Table 3* – Modified: I_{GSS} (V_{GS} - test condition) value and I_D (for $R_{DS(on)}$) in *Table 4* – Modified: Q_g value in *Table 5* – Modified: I_D value in *Table 6* – Modified: I_{SD} and I_{SDM} in *Table 7* – Added: *Section 2.1: Electrical characteristics (curves)* – Minor text changes
08-Jan-2014	3	– Modified: T_J value in *Table 2* – Modified: *Figure 6* – Updated: *Section 4: Package mechanical data* – Minor text changes
03-Feb-2020	4	Updated *Section 4 Package information*. Minor text changes.
18-Feb-2020	5	Updated Internal schematic in cover page.

Contents

1 **Electrical ratings** 2

2 **Electrical characteristics** 3

2.1 Electrical characteristics (curves) 5

3 **Test circuits** 7

4 **Package information** 8

4.1 PowerFLAT 5x6 type R package information 8

4.2 PowerFLAT 5x6 type R SUBCON package information 9

4.3 PowerFLAT 5x6 packing information 12

Revision history 15

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved