

N-channel 80 V, 3.0 mΩ typ., 120 A STripFET F7 Power MOSFET in a PowerFLAT 5x6 package



PowerFLAT 5x6



Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D	P_{TOT}
STL130N8F7	80 V	3.6 mΩ	120 A	135 W

- Among the lowest $R_{DS(on)}$ on the market
- Excellent FoM (figure of merit)
- Low C_{rss}/C_{iss} ratio for EMI immunity
- High avalanche ruggedness

Applications

- Switching applications

Description

This N-channel Power MOSFET utilizes STripFET F7 technology with an enhanced trench gate structure that results in very low on-state resistance, while also reducing internal capacitance and gate charge for faster and more efficient switching.

Product status link
STL130N8F7

Product summary	
Order code	STL130N8F7
Marking	130N8F7
Package	PowerFLAT 5x6
Packing	Tape and reel

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	80	V
V_{GS}	Gate-source voltage	±20	V
I_D (1)	Drain current (continuous) at T_C = 25 °C	120	A
	Drain current (continuous) at T_C = 100 °C	93	
I_D (2)	Drain current (continuous) at T_{pcb} = 25 °C	26	A
	Drain current (continuous) at T_{pcb} = 100 °C	19	
I_{DM} (1)(3)	Drain current (pulsed)	480	A
I_{DM} (2)(3)	Drain current (pulsed)	104	A
P_{TOT} (1)	Total power dissipation at T_C = 25 °C	135	W
P_{TOT} (2)	Total power dissipation at T_{pcb} = 25 °C	4.8	W
E_{AS} (4)	Single pulse avalanche energy	515	mJ
T_{stg}	Storage temperature range	-55 to 175	°C
T_J	Operating junction temperature range		

1. *This value is rated according to $R_{thj\text{-}case}$ and is limited by package.*
2. *This value is rated according to $R_{thj\text{-}pcb}$.*
3. *Pulse width is limited by safe operating area.*
4. *Starting T_J = 25 °C, I_D = 18.5 A, V_{DD} = 50 V.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
$R_{thj\text{-}case}$	Thermal resistance junction-case	1.1	°C/W
$R_{thj\text{-}pcb}$ (1)	Thermal resistance junction-pcb	31.3	°C/W

1. *When mounted on FR-4 board of 1 inch², 2oz Cu, t < 10 s.*

2 Electrical characteristics

T_C = 25 °C unless otherwise specified

Table 3. On/off-state

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 250 µA	80			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 80 V			1	µA
		V_{GS} = 0 V, V_{DS} = 80 V, T_J = 125 °C(1)			10	µA
I_{GSS}	Gate body leakage current	V_{DS} = 0 V, V_{GS} = 20 V			100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	2.5		4.5	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 13 A		3.0	3.6	mΩ

1. *Defined by design, not subject to production test.*

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{GS} = 0 V, V_{DS} = 40 V, f = 1 MHz	-	6340	-	pF
C_{oss}	Output capacitance		-	1195	-	pF
C_{rss}	Reverse transfer capacitance		-	105	-	pF
Q_g	Total gate charge	V_{DD} = 40 V, I_D = 26 A, V_{GS} = 0 to 10 V (see Figure 13. Test circuit for gate charge behavior)	-	96	-	nC
Q_{gs}	Gate-source charge		-	29	-	nC
Q_{gd}	Gate-drain charge		-	26	-	nC

Table 5. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 40 V, I_D = 13 A, R_G = 4.7 Ω, V_{GS} = 10 V (see Figure 12. Test circuit for resistive load switching times and Figure 17. Switching time waveform)	-	26	-	ns
t_r	Rise time		-	51	-	ns
$t_{d(off)}$	Turn-off delay time		-	82	-	ns
t_f	Fall time		-	44	-	ns

Table 6. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{SD}(1)	Forward on voltage	I_{SD} = 26 A, V_{GS} = 0 V	-		1.2	V
t_{rr}	Reverse recovery time	I_{SD} = 26 A, di/dt = 100 A/µs, V_{DD} = 60 V, T_J = 150 °C (see Figure 14. Test circuit for inductive load switching and diode recovery times)	-	58		ns
Q_{rr}	Reverse recovery charge		-	92		nC
I_{RRM}	Reverse recovery current		-	3.2		A

1. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%.*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Normalized thermal impedance




Figure 3. Output characteristics




Figure 4. Transfer characteristics




Figure 5. Gate charge vs gate-source voltage




Figure 6. Static drain-source on-resistance




Figure 7. Capacitance variations




Figure 8. Normalized $V_{(BR)DSS}$ vs temperature




Figure 9. Normalized gate threshold voltage vs temperature




Figure 10. Normalized on-resistance vs temperature





Figure 11. Source-drain diode forward characteristics



3 Test circuits

Figure 12. Test circuit for resistive load switching times




Figure 13. Test circuit for gate charge behavior




Figure 14. Test circuit for inductive load switching and diode recovery times




Figure 15. Unclamped inductive load test circuit




Figure 16. Unclamped inductive waveform





Figure 17. Switching time waveform



4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 PowerFLAT 5x6 type C package information

Figure 18. PowerFLAT 5x6 type C package outline





Table 7. **PowerFLAT 5x6 type C package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	0.80		1.00
A1	0.02		0.05
A2		0.25	
b	0.30		0.50
C	5.80	6.00	6.20
D	5.00	5.20	5.40
D2	4.15		4.45
D3	4.05	4.20	4.35
D4	4.80	5.00	5.20
D5	0.25	0.40	0.55
D6	0.15	0.30	0.45
e		1.27	
E	5.95	6.15	6.35
E2	3.50		3.70
E3	2.35		2.55
E4	0.40		0.60
E5	0.08		0.28
E6	0.20	0.325	0.45
E7	0.75	0.90	1.05
K	1.05		1.35
L	0.725		1.025
L1	0.05	0.15	0.25
θ	0°		12°

4.2 PowerFLAT 5x6 type C SUBCON package information

Figure 19. **PowerFLAT 5x6 type C SUBCON package outline**




8472137_SUBCON_998G_REV4

Table 8. PowerFLAT 5x6 type C SUBCON package mechanical data


Dim.	mm		
	Min.	Typ.	Max.
A	0.90	0.95	1.00
A1		0.02	
b	0.35	0.40	0.45
b1		0.30	
c	0.21	0.25	0.34
D			5.10
D1	4.80	4.90	5.00
D2	4.01	4.21	4.31
e	1.17	1.27	1.37
E	5.90	6.00	6.10
E1	5.70	5.75	5.80
E2	3.54	3.64	3.74
E4	0.15	0.25	0.35
E5	0.26	0.36	0.46
H	0.51	0.61	0.71
K	0.95		
L	0.51	0.61	0.71
L1	0.06	0.13	0.20
L2			0.10
P	1.00	1.10	1.20
θ	8°	10°	12°

Figure 20. **PowerFLAT 5x6 recommended footprint (dimensions are in mm)**



4.3 PowerFLAT 5x6 packing information

Figure 21. PowerFLAT 5x6 tape (dimensions are in mm)



Ao	6.30 +/– 0.1
Bo	5.30 +/– 0.1
Ko	1.20 +/– 0.1
F	5.50 +/– 0.1
P1	8.00 +/– 0.1
W	12.00 +/– 0.3

(I) Measured from centreline of sprocket hole to centreline of pocket.

(II) Cumulative tolerance of 10 sprocket holes is ±0.20.

(III) Measured from centreline of sprocket hole to centreline of pocket

Base and bulk quantity 3000 pcs
All dimensions are in millimeters

8234350_Tape_rev_C

Figure 22. PowerFLAT 5x6 package orientation in carrier tape





Figure 23. **PowerFLAT 5x6 reel**



Revision history

Table 9. **Document revision history**

Date	Revision	Changes
21-May-2013	1	First release
23-Sep-2013	2	Document status promoted form preliminary to production data. Inserted *Section 2.1: Electrical characteristics (curves)*.
25-Jul-2014	3	Modified: title and description Modified: ID and PTOT values in cover page Updated: *Figure 13, 14, 15 and 16* Updated: *Section 4: Package mechanical data* Minor text changes
03-Nov-2017	4	Updated title and features table on cover page. Updated *Table 2: "Absolute maximum ratings"* and *Table 7: "Source-drain diode"*. Updated *Figure 2: "Safe operating area"* and *Figure 3: "Normalized thermal impedance"*. Updated *Section 4.1: "PowerFLAT™ 5x6 type C package information"*. Minor text changes
26-Feb-2020	5	Updated Section 4 Package information. Minor text changes.

Contents

1 **Electrical ratings** 2

2 **Electrical characteristics** 3

2.1 Electrical characteristics (curves) 4

3 **Test circuits** 6

4 **Package information** 7

4.1 PowerFLAT 5x6 type C package information 7

4.2 PowerFLAT 5x6 type C SUBCON package information 9

4.3 PowerFLAT 5x6 packing information 12

Revision history 14

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved