STGFW40V60DF, STGW40V60DF

Datasheet

Trench gate field-stop IGBT, V series 600 V, 40 A very high speed



TO-3PF



TO-247



STPOWER

Product status links
STGFW40V60DF
STGW40V60DF

Features

- Maximum junction temperature: T_J = 175 °C
- Tail-less switching off
- $V_{CE(sat)}$ = 1.8 V (typ.) @ I_C = 40 A
- Tight parameters distribution
- Safe paralleling
- Low thermal resistance
- Very fast soft recovery antiparallel diode

Applications

- Welding
- PFC converters - single phase input
- Solar inverters (string and central)
- Uninterruptable power supplies (UPS)
- EV charging - DC fast charging stations

Description

These devices are IGBTs developed using an advanced proprietary trench gate field-stop structure. The device is part of the V series IGBTs, which represent an optimum compromise between conduction and switching losses to maximize the efficiency of very high frequency converters. Furthermore, the positive $V_{CE(sat)}$ temperature coefficient and very tight parameter distribution result in safer paralleling operation.

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value		Unit
		TO-247	TO-3PF	
V_{CES}	Collector-emitter voltage (V_{GE} = 0 V)	600		V
I_C	Continuous collector current at T_C = 25 °C	80		A
	Continuous collector current at T_C = 100 °C	40		A
I_{CP}(1)	Pulsed collector current	160		A
V_{GE}	Gate-emitter voltage	±20		V
I_F	Continuous forward current at T_C = 25 °C	80		A
	Continuous forward current at T_C = 100 °C	40		A
I_{FP}(1)	Pulsed forward current	160		A
P_{TOT}	Total power dissipation at T_C = 25 °C	283	98.5	W
V_{ISO}	Insulation withstand voltage (RMS) from all three leads to external heat sink (t = 1 s; T_C = 25 °C)		3.5	kV
T_{stg}	Storage temperature range	-55 to 150		°C
T_J	Operating junction temperature range	-55 to 175		°C

1. *Pulse width is limited by maximum junction temperature.*

Table 2. Thermal data

Symbol	Parameter	Value		Unit
		TO-247	TO-3PF	
R_{thJC}	Thermal resistance, junction-to-case IGBT	0.53	1.52	°C/W
R_{thJC}	Thermal resistance, junction-to-case diode	1.14	1.95	°C/W
R_{thJA}	Thermal resistance, junction-to-ambient	50		°C/W

2 Electrical characteristics

T_J = 25 °C unless otherwise specified

Table 3. Static characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)CES}$	Collector-emitter breakdown voltage	V_{GE} = 0 V, I_C = 2 mA	600			V
$V_{CE(sat)}$	Collector-emitter saturation voltage	V_{GE} = 15 V, I_C = 40 A		1.8	2.3	V
		V_{GE} = 15 V, I_C = 40 A, T_J = 125 °C		2.15		
		V_{GE} = 15 V, I_C = 40 A, T_J = 175 °C		2.35		
V_F	Forward on-voltage	I_F = 40 A		1.7	2.45	V
		I_F = 40 A, T_J = 125 °C		1.4		
		I_F = 40 A, T_J = 175 °C		1.3		
$V_{GE(th)}$	Gate threshold voltage	V_{CE} = V_{GE}, I_C = 1 mA	5	6	7	V
I_{CES}	Collector cut-off current	V_{GE} = 0 V, V_{CE} = 600 V			25	µA
I_{GES}	Gate-emitter leakage current	V_{CE} = 0 V, V_{GE} = ±20 V			±250	nA

Table 4. Dynamic characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{ies}	Input capacitance	V_{CE} = 25 V, f = 1 MHz, V_{GE} = 0 V	-	5400	-	pF
C_{oes}	Output capacitance		-	220	-	pF
C_{res}	Reverse transfer capacitance		-	180	-	pF
Q_g	Total gate charge	V_{CC} = 480 V, I_C = 40 A, V_{GE} = 0 to 15 V (see Figure 34. Gate charge test circuit)	-	226	-	nC
Q_{ge}	Gate-emitter charge		-	38	-	nC
Q_{gc}	Gate-collector charge		-	95	-	nC

Table 5. IGBT switching characteristics (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{CE} = 400 V, I_C = 40 A, R_G = 10 Ω, V_{GE} = 15 V (see Figure 33. Test circuit for inductive load switching)	-	52	-	ns
t_r	Current rise time		-	17	-	ns
$(di/dt)_{on}$	Turn-on current slope		-	1850	-	A/µs
$t_{d(off)}$	Turn-off delay time		-	208	-	ns
t_f	Current fall time		-	20	-	ns
E_{on} (1)	Turn-on switching energy		-	456	-	µJ
E_{off} (2)	Turn-off switching energy		-	411	-	µJ
E_{ts}	Total switching energy		-	867	-	µJ
$t_{d(on)}$	Turn-on delay time	V_{CE} = 400 V, I_C = 40 A, R_G = 10 Ω, V_{GE} = 15 V, T_J = 175 °C (see Figure 33. Test circuit for inductive load switching)	-	52	-	ns
t_r	Current rise time		-	21	-	ns
$(di/dt)_{on}$	Turn-on current slope		-	1538	-	A/µs
$t_{d(off)}$	Turn-off-delay time		-	220	-	ns
t_f	Current fall time		-	21	-	ns
E_{on} (1)	Turn-on switching energy		-	1330	-	µJ
E_{off} (2)	Turn-off switching energy		-	560	-	µJ
E_{ts}	Total switching energy		-	1890	-	µJ

1. *Including the reverse recovery of the diode.*
2. *Including the tail of the collector current.*

Table 6. Diode switching characteristics (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
t_{rr}	Reverse recovery time	I_F = 40 A, V_R = 400 V, V_{GE} = 15 V, di/dt = 1000 A/µs (see Figure 33. Test circuit for inductive load switching)	-	41	-	ns
Q_{rr}	Reverse recovery charge		-	440	-	nC
I_{rrm}	Reverse recovery current		-	21.6	-	A
dI_{rr}/dt	Peak rate of fall of reverse recovery current during t_b		-	1363	-	A/µs
E_{rr}	Reverse recovery energy		-	151	-	µJ
t_{rr}	Reverse recovery time	I_F = 40 A, V_R = 400 V, V_{GE} = 15 V, di/dt = 1000 A/µs, T_J = 175 °C (see Figure 33. Test circuit for inductive load switching)	-	109	-	ns
Q_{rr}	Reverse recovery charge		-	2400	-	nC
I_{rrm}	Reverse recovery current		-	44.4	-	A
dI_{rr}/dt	Peak rate of fall of reverse recovery current during t_b		-	670	-	A/µs
E_{rr}	Reverse recovery energy		-	718	-	µJ

2.1 Electrical characteristics (curves)

Figure 1. Power dissipation vs case temperature for TO-247



Figure 2. Collector current vs case temperature for TO-247



Figure 3. Power dissipation vs case temperature for TO-3PF



Figure 4. Collector current vs case temperature for TO-3PF



Figure 5. Output characteristics (T_J = 25 °C)



Figure 6. Output characteristics (T_J = 175 °C)



Figure 7. $V_{CE(sat)}$ vs junction temperature



Figure 8. $V_{CE(sat)}$ vs collector current



Figure 9. Collector current vs switching frequency for TO-247



Figure 10. Collector current vs switching frequency for TO-3PF



Figure 11. Forward bias safe operating area for TO-247



Figure 12. Forward bias safe operating area for TO-3PF



Figure 13. Transfer characteristics



Figure 14. Diode V_F vs forward current



Figure 15. Normalized $V_{GE(th)}$ vs junction temperature



Figure 16. Normalized $V_{(BR)CES}$ vs junction temperature



Figure 17. Capacitance variations



Figure 18. Gate charge vs gate-emitter voltage



Figure 19. Switching energy vs collector current



Figure 20. Switching energy vs gate resistance



Figure 21. Switching energy vs junction temperature



Figure 22. Switching energy vs collector emitter voltage



Figure 23. Switching times vs collector current



Figure 24. Switching times vs gate resistance



Figure 25. Reverse recovery current vs diode current slope



Figure 26. Reverse recovery time vs diode current slope



Figure 27. Reverse recovery charge vs diode current slope



Figure 28. Reverse recovery energy vs diode current slope



Figure 29. Thermal impedance for IGBT in TO-247



Figure 30. Thermal impedance for IGBT in TO-3PF



Figure 31. Thermal impedance for diode in TO-247



Figure 32. Thermal impedance for diode in TO-3PF



3 Test circuits

Figure 33. Test circuit for inductive load switching



Figure 34. Gate charge test circuit



Figure 35. Switching waveform



Figure 36. Diode reverse recovery waveform



4 Package information

To meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 TO-3PF type A package information

Figure 37. TO-3PF type A package outline



Table 7. **TO-3PF type A mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	5.30		5.70
C	2.80		3.20
D	3.10		3.50
D1	1.80		2.20
E	0.80		1.00
F	0.65		0.85
F2	1.80		2.20
G	10.80		11.00
G1	5.35	5.45	5.55
H	15.30		15.70
L	9.80	10.00	10.20
L2	22.80		23.20
L3	26.30		26.70
L4	43.60		44.00
L5	4.30		4.70
L6	24.30		24.70
L7	14.60		15.00
N	1.80		2.20
R	3.80		4.20
Dia	3.40		3.80

4.2 TO-247 package information

Figure 38. **TO-247 package outline**



0075325_11

Table 8. **TO-247 package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
A2		1.27	
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70

5 Ordering information

Table 9. **Order codes**

Order code	Marking	Package	Packing
STGFW40V60DF	G40V60DF	TO-3PF	Tube
STGW40V60DF	GW40V60DF	TO-247	

Revision history

Table 10. **Document revision history**

Date	Revision	Changes
20-Mar-2013	1	Initial release
17-Apr-2013	2	Document status promoted from preliminary data to production data. Added: *Section 2.1: Electrical characteristics (curves)*
04-Jun-2013	3	Added minimum and maximum values for $V_{GE(th)}$ in *Table 4: Static characteristics*.
11-Sep-2013	4	Updated V_F value in *Table 4: Static characteristics*.
08-Oct-2013	5	Updated title, features and description in cover page.
10-Jan-2014	6	Updated *Figure 8: $V_{CE(sat)}$ vs. junction temperature*, *Figure 15: Diode V_F vs. forward current* and *Figure 16: Normalized $V_{GE(th)}$ vs junction temperature*.
03-Mar-2014	7	Updated test conditions in *Table 7: Diode switching characteristics (inductive load)*.
23-Apr-2014	8	Added new device in TO-3PF. Updated *Table 1: Device summary*, *Table 2: Absolute maximum ratings*, *Table 3: Thermal data* and *Section 4: Package mechanical data*. Added *Figure 4: Power dissipation vs. case temperature for TO-3PF*, *Figure 5: Collector current vs. case temperature for TO-3PF*, *Figure 11: Collector current vs. switching frequency for TO-3PF* and *Figure 12: Forward bias safe operating area for TO-247 and TO-3P*. Minor text changes.
27-Oct-2017	9	Updated *Table 3: "Thermal data"*. Added *Figure 33: "Thermal impedance for diode in TO-3PF"*. Updated *Section 4: "Package information"*. Minor text changes
06-Mar-2020	10	Updated *Section 5 Ordering information.* Minor text changes.
17-Feb-2021	11	Modified *Figure 3. Power dissipation vs case temperature for TO-3PF*, *Figure 4. Collector current vs case temperature for TO-3PF, Figure 10. Collector current vs switching frequency for TO-3PF* and *Figure 12. Forward bias safe operating area for TO-3PF*. Minor text changes.
06-Jun-2022	12	The part number STGWT40V60DF has been removed and the document has been updated accordingly. Updated test conditions for the ICES in *Table 3. Static characteristics*. Updated *Section 4.2 TO-247 package information*. Minor text changes.
26-Aug-2026	13	Updated Section 4.1: TO-3PF type A package information.

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Test circuits** 11
4 **Package information** 12
4.1 TO-3PF type A package information 12
4.2 TO-247 package information 14
5 **Ordering information** 16
Revision history 17

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2026 STMicroelectronics – All rights reserved