


STB40N60M2, STP40N60M2, STW40N60M2

Datasheet

N-channel 600 V, 78 mΩ typ., 34 A MDmesh M2 Power MOSFET in a D²PAK, TO-220 and TO-247 packages







Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
STB40N60M2	600 V	88 mΩ	34 A
STP40N60M2			
STW40N60M2			

- Extremely low gate charge
- Excellent output capacitance (C_{oss}) profile
- 100% avalanche tested
- Zener-protected

Applications

- Switching applications

Description

These devices are N-channel Power MOSFETs developed using the MDmesh M2 technology. Thanks to their strip layout and improved vertical structure, these devices exhibit low on-resistance and optimized switching characteristics, rendering them suitable for the most demanding high-efficiency converters.

Product status links
STB40N60M2
STP40N60M2
STW40N60M2

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	600	V
V_{GS}	Gate-source voltage	±25	V
I_D	Drain current (continuous) at T_C = 25 °C	34	A
I_D	Drain current (continuous) at T_C = 100 °C	22	A
I_{DM}(1)	Drain current (pulsed)	136	A
P_{TOT}	Total power dissipation at T_C = 25 °C	250	W
dv/dt(2)	Peak diode recovery voltage slope	15	V/ns
dv/dt(3)	MOSFET dv/dt ruggedness	50	V/ns
T_{stg}	Storage temperature range	-55 to 150	°C
T_J	Operating junction temperature range		°C

1. *Pulse width limited by safe operating area.*
2. *I_{SD} ≤ 34 A, di/dt ≤ 400 A/µs, V_{DS} (peak) < $V_{(BR)DSS}$, V_{DD} = 400 V.*
3. *V_{DD} = 480 V.*

Table 2. Thermal data

Symbol	Parameter	Value			Unit
		D^2PAK	TO-220	TO-247	
R_{thJC}	Thermal resistance, junction-to-case	0.50			°C/W
R_{thJA}	Thermal resistance, junction-to-ambient	30(1)	62.5	50	°C/W

1. *When mounted on a standard 1 inch^2 area of FR-4 PCB with 2-oz copper.*

Table 3. Avalanche characteristics

Symbol	Parameter	Value	Unit
I_{AR}	Avalanche current, repetitive or not-repetitive (pulse width limited by T_J max.)	6	A
E_{AS}	Single pulse avalanche energy (starting T_J = 25 °C, I_D = I_{AR}, V_{DD} = 50 V)	500	mJ

2 Electrical characteristics

(T_C = 25 °C unless otherwise specified)

Table 4. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	I_D = 1 mA, V_{GS} = 0 V	600	-	-	V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 600 V	-	-	1	µA
		V_{GS} = 0 V, V_{DS} = 600 V, T_C = 125 °C(1)	-	-	100	µA
I_{GSS}	Gate body leakage current	V_{DS} = 0 V, V_{GS} = ±25 V	-	-	±10	µA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	2	3	4	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 17 A	-	78	88	mΩ

1. *Specified by design, not tested in production.*

Table 5. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 100 V, f = 1 MHz, V_{GS} = 0 V	-	2500	-	pF
C_{oss}	Output capacitance		-	117	-	pF
C_{rss}	Reverse transfer capacitance		-	2.4	-	pF
$C_{oss\ eq.}$(1)	Equivalent capacitance time related	V_{DS} = 0 to 480 V, V_{GS} = 0 V	-	342	-	pF
Q_g	Total gate charge	V_{DD} = 480 V, I_D = 34 A, V_{GS} = 0 to 10 V (see the Figure 16. Test circuit for gate charge behavior)	-	57	-	nC
Q_{gs}	Gate-source charge		-	10	-	nC
Q_{gd}	Gate-drain charge		-	25.5	-	nC
R_g	Intrinsic gate resistance	f = 1 MHz, I_D = 0 A	-	4.4	-	Ω

1. *$C_{oss\ eq.}$ is defined as a constant equivalent capacitance giving the same charging time as C_{oss} when V_{DS} increases from 0 to 80% V_{DSS}.*

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 300 V, I_D = 34 A, R_G = 4.7 Ω, V_{GS} = 10 V (see the Figure 15. Test circuit for resistive load switching times and Figure 20. Switching time waveform)	-	20.5	-	ns
t_r	Rise time		-	13.5	-	ns
$t_{d(off)}$	Turn-off delay time		-	96	-	ns
t_f	Fall time		-	11	-	ns

Table 7. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-	-	34	A
I_{SDM}(1)	Source-drain current (pulsed)		-	-	136	A
V_{SD}(2)	Forward on voltage	I_{SD} = 34 A, V_{GS} = 0 V	-	-	1.6	V
t_{rr}	Reverse recovery time	I_{SD} = 34 A, di/dt = 100 A/µs, V_{DD} = 60 V (see the Figure 17. Test circuit for inductive load switching and diode recovery times)	-	440	-	ns
Q_{rr}	Reverse recovery charge		-	8.2	-	µC
I_{RRM}	Reverse recovery current		-	37	-	A
t_{rr}	Reverse recovery time	I_{SD} = 34 A, di/dt = 100 A/µs, V_{DD} = 60 V, T_J = 150 °C (see the Figure 17. Test circuit for inductive load switching and diode recovery times)	-	568	-	ns
Q_{rr}	Reverse recovery charge		-	11.5	-	µC
I_{RRM}	Reverse recovery current		-	40.5	-	A

1. *Pulse width limited by safe operating area.*
2. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%.*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area for D²PAK and TO-220




Figure 2. Normalized transient thermal impedance for D²PAK and TO-220




Figure 3. Safe operating area for TO-247




Figure 4. Normalized transient thermal impedance for TO-247




Figure 5. Typical output characteristics




Figure 6. Typical transfer characteristics




Figure 7. Typical gate charge characteristics




Figure 8. Typical capacitance characteristics




Figure 9. Typical drain-source on-resistance




Figure 10. Normalized breakdown voltage vs temperature




Figure 11. Normalized gate threshold vs temperature




Figure 12. Normalized on-resistance vs temperature




Figure 13. Typical reverse diode forward characteristics






Figure 14. Output capacitance stored energy




3 Test circuits

Figure 15. Test circuit for resistive load switching times




AM01468v1

Figure 16. Test circuit for gate charge behavior




AM01469v1

Figure 17. Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 18. Unclamped inductive load test circuit




AM01471v1

Figure 19. Unclamped inductive waveform



AM01472v1

Figure 20. Switching time waveform




AM01473v1

4 Package information

To meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 D²PAK (TO-263) type A2 package information

Figure 21. **D²PAK (TO-263) type A2 package outline**




0079457_A2_27

Table 8. D²PAK (TO-263) type A2 package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
A1	0.03		0.23
b	0.70		0.93
b2	1.14		1.70
c	0.45		0.60
c2	1.23		1.36
D	8.95		9.35
D1	7.50	7.75	8.00
D2	1.10	1.30	1.50
E	10.00		10.40
E1	8.70	8.90	9.10
E2	7.30	7.50	7.70
e		2.54	
e1	4.88		5.28
H	15.00		15.85
J1	2.49		2.69
L	2.29		2.79
L1	1.27		1.40
L2	1.30		1.75
R		0.40	
V2	0°		8°

Figure 22. D²PAK (TO-263) recommended footprint (dimensions are in mm)



4.2 TO-220 type A package information

Figure 23. **TO-220 type A package outline**





Table 9. **TO-220 type A package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
b	0.61		0.88
b1	1.14		1.55
c	0.48		0.70
D	15.25		15.75
D1		1.27	
E	10.00		10.40
e	2.40		2.70
e1	4.95		5.15
F	1.23		1.32
H1	6.20		6.60
J1	2.40		2.72
L	13.00		14.00
L1	3.50		3.93
L20		16.40	
L30		28.90	
øP	3.75		3.85
Q	2.65		2.95
Slug flatness		0.03	0.10

4.3 TO-247 package information

Figure 24. **TO-247 package outline**




0075325_10

Table 10. **TO-247 package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.85		5.15
A1	2.20		2.60
b	1.0		1.40
b1	2.0		2.40
b2	3.0		3.40
c	0.40		0.80
D	19.85		20.15
E	15.45		15.75
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2		18.50	
ØP	3.55		3.65
ØR	4.50		5.50
S	5.30	5.50	5.70
aaa		0.04	0.10

4.4 D²PAK packing information

Figure 25. **D²PAK tape drawing (dimensions are in mm)**



DM01095771_2

5 Ordering information

Table 11. **Order codes**

Order codes	Marking	Package	Packing
STB40N60M2	40N60M2	D²PAK	Tape and reel
STP40N60M2		TO-220	Tube
STW40N60M2		TO-247	

Revision history

Table 12. **Document revision history**

Date	Revision	Changes
01-Jul-2013	1	First release.
23-Sep-2013	2	Added: TO-220FP and I^2PAKFP packages. Inserted: VISO in *Table 2*. Modified: values in *Table 4*, the entire typical values in *Table 6*, *7* and *8*. Updated: *Section 4: Package mechanical data*. Minor text changes.
13-May-2014	3	The part numbers STF40N60M2 and STFI40N60M2 have been moved to a separate datasheet. Minor text changes.
09-Aug-2016	4	Updated title, features and description in cover page. Updated *Table 2: Absolute maximum ratings*, *Table 5: On /off states* and *Table 8: Source drain diode*. Updated *Section 4.1: D2PAK (TO-263) package information* and *Section 4.2: TO-220 package information*. Minor text changes.
18-Sep-2025	5	Updated Section 4: Package information. Minor text changes.

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Test circuits** 8
4 **Package information** 9
4.1 D²PAK (TO-263) type A2 package information 9
4.2 TO-220 type A package information 12
4.3 TO-247 package information 14
4.4 D²PAK packing information 16
5 **Ordering information** 17
Revision history 18

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2025 STMicroelectronics – All rights reserved