FAIRCHILD™

Is Now Part of

ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

August 2016

FDMC013P030Z

P-Channel PowerTrench® MOSFET

-30 V, -54 A, 7.0 mΩ

Features

- Max $r_{DS(on)}$ = 7.0 mΩ at V_{GS} = -10 V, I_D = -14 A
- Max $r_{DS(on)}$ = 12.0 mΩ at V_{GS} = -4.5 V, I_D = -10 A
- High Performance Trench Technology for Extremely Low $r_{DS(on)}$
- High Power and Current Handling Capability in a Widely Used Surface Mount Package
- Termination is Lead-free and RoHS Compliant
- HBM ESD Capability Level > 4 kV Typical (Note 4)

General Description

This P-Channel MOSFET is produced using Fairchild Semiconductor's advanced PowerTrench process that has been optimized for $r_{DS(on)}$, switching performance and ruggedness.

Applications

- Battery Management
- Load Switch



MLP 3.3x3.3



MOSFET Maximum Ratings T_A = 25 °C unless otherwise noted.

Symbol	Parameter			Ratings	Units
V_{DS}	Drain to Source Voltage			-30	V
V_{GS}	Gate to Source Voltage			±25	V
I_D	Drain Current -Continuous	T_C = 25 °C	(Note 5)	-54	A
	Drain Current -Continuous	T_C = 100 °C	(Note 5)	-35	
	-Continuous	T_A = 25 °C	(Note 1a)	-14	
	-Pulsed		(Note 4)	-309	
E_{AS}	Single Pulse Avalanche Energy		(Note 3)	54	mJ
P_D	Power Dissipation	T_C = 25 °C		30	W
	Power Dissipation	T_A = 25 °C	(Note 1a)	2.4	
T_J, T_{STG}	Operating and Storage Junction Temperature Range			-55 to +150	°C

Thermal Characteristics

$R_{\theta JC}$	Thermal Resistance, Junction to Case		4.2	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1a)	53	

Package Marking and Ordering Information

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
FDMC013P030Z	FDMC013P030Z	MLP 3.3x3.3	13 "	12 mm	3000 units

©2016 Fairchild Semiconductor Corporation

Electrical Characteristics T_J = 25 °C unless otherwise noted.

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
Off Characteristics						
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = -250 μA, V_{GS} = 0 V	-30			V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I_D = -250 μA, referenced to 25 °C		-13		mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = -24 V, V_{GS} = 0 V			-1	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = ±25 V, V_{DS} = 0 V			±10	μA
On Characteristics						
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = -250 μA	-1	-1.6	-3	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = -250 μA, referenced to 25 °C		5		mV/°C
$r_{DS(on)}$	Static Drain to Source On Resistance	V_{GS} = -10 V, I_D = -14 A		5.0	7.0	mΩ
		V_{GS} = -4.5 V, I_D = -10 A		8.0	12.0	
		V_{GS} = -10 V, I_D = -14 A, T_J = 125 °C		6.2	10.4	
g_{FS}	Forward Transconductance	V_{DS} = -5 V, I_D = -14 A		60		S
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS} = -15 V, V_{GS} = 0 V, f = 1 MHz		4130	5785	pF
C_{oss}	Output Capacitance			1355	1895	pF
C_{rss}	Reverse Transfer Capacitance			1335	1870	pF
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time	V_{DD} = -15 V, I_D = -14 A, V_{GS} = -4.5 V, R_{GEN} = 6 Ω		34	55	ns
t_r	Rise Time			157	251	ns
$t_{d(off)}$	Turn-Off Delay Time			55	88	ns
t_f	Fall Time			94	150	ns
Q_g	Total Gate Charge	V_{GS} = 0 V to -10 V; V_{DD} = -15 V, I_D = -14 A		96	135	nC
Q_g	Total Gate Charge	V_{GS} = 0 V to -4.5 V; V_{DD} = -15 V, I_D = -14 A		58	81	nC
Q_{gs}	Gate to Source Charge	V_{DD} = -15 V, I_D = -14 A		11		nC
Q_{gd}	Gate to Drain "Miller" Charge	V_{DD} = -15 V, I_D = -14 A		36		nC
Drain-Source Diode Characteristics						
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = -14 A (Note 2)		-0.8	-1.3	V
		V_{GS} = 0 V, I_S = -2 A (Note 2)		-0.7	-1.2	
t_{rr}	Reverse Recovery Time	I_F = -14 A, di/dt = 100 A/μs		44	77	ns
Q_{rr}	Reverse Recovery Charge			23	37	nC

NOTES:
1. $R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR-4 material. $R_{\theta CA}$ is determined by the user's board design.



a) 53°C/W when mounted on a 1 in^2 pad of 2 oz copper



b) 125°C/W when mounted on a minimum pad

2. Pulse Test: Pulse Width < 300 μs, Duty cycle < 2.0 %.
3. E_{AS} of 54 mJ is based on starting T_J = 25 °C, L = 3 mH, I_{AS} = 6 A, V_{DD} =30 V, V_{GS} = 10 V.
4. Pulsed Id please refer to Fig 11 SOA graph for more details.
5. Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro-mechanical application board design.

Typical Characteristics T_J = 25 °C unless otherwise noted.



Figure 1. On Region Characteristics



Figure 2. Normalized On-Resistance vs. Drain Current and Gate Voltage



Figure 3. Normalized On Resistance vs. Junction Temperature



Figure 4. On-Resistance vs. Gate to Source Voltage



Figure 5. Transfer Characteristics



Figure 6. Source to Drain Diode Forward Voltage vs. Source Current

Typical Characteristics T_J = 25 °C unless otherwise noted.



Figure 7. Gate Charge Characteristics



Figure 8. Capacitance vs. Drain to Source Voltage



Figure 9. Unclamped Inductive Switching Capability



Figure 10. Maximum Continuous Drain Current vs. Case Temperature



Figure 11. Forward Bias Safe Operating Area



Figure 12. Igss vs. Vgss

Typical Characteristics T_J = 25 °C unless otherwise noted.



Figure 13. Single Pulse Maximum Power Dissipation



Figure 14. Junction to Case Transient Thermal Response Curve







BOTTOM VIEW



RECOMMENDED LAND PATTERN

NOTES:

A. DOES NOT CONFORM TO JEDEC REGISTRATION MO-229

B. DIMENSIONS ARE IN MILLIMETERS.

C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 2009.

D. LAND PATTERN RECOMMENDATION IS EXISTING INDUSTRY LAND PATTERN.

E. DRAWING FILENAME: MKT-MLP08Srev3.

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative