

FH2 STACKABLE BLOCK FUSE HOLDER

for TAC® Style Blade Fuse Rated 58V



Description

Blockholder for 42V PowerNet with coding for TAC® fuses-links.
Attachable in X- and Y-direction. Rated voltage 58V; crimp terminals.

Specifications

Housing:	Out of thermoplastic (UL 94-V0, heat-resistant)
Connections:	Leaf spring connector systems, crimp contacts, copper alloy, tinned
Color:	Black
Cover:	Thermoplastic (transparent)


Ordering Information

Part Number	Package Size
178.4205.0002	1000
178.4215.0002	1000
178.6116.xxx1	200
178.6116.xxx2	1000
178.6125.0001	100
178.6125.0002	1000



Dimensions

Dimensions in mm

Chart for row-mounting



10er/pcs. Block



Ratings

Part Number	Description	Contact Temperature
178.4205.000_	Complete with DFK 1.5 - 2.5 mm²	max. 130°C
178.4215.000_	Housing	–
178.6125.000_	Cover	–
178.6116.100_ *	Complete with DFK 0.5 - 1.0 mm²	max. 130°C
178.6116.250_ *	Contacts 1.5-2.5mm²	max. 130°C
178.6116.600_ *	Contacts 4.0-6.0mm²	max. 130°C

RoHS

