P-DUKE POWER

HAE150W Series

Half-Brick DC-DC Converter
Up to 182 Watts

3 YEARS WARRANTY

RoHS COMPLIANT

REACH COMPLIANT



Railway | Automation | Datacom

IPC | Industry | Measurement

Telecom | Automobile | Boat

Charger | Medical | PV

3000 VAC Reinforced Insulation | 3000 VDC Isolation Voltage | 4 : 1 Wide Input Range | NO Min. Load Required | REMOTE ON OFF | Sync | OCP | OTP | OVP | SCP | UVP

PART NUMBER STRUCTURE

DIP Type:

HAE150- 48 S 05 W - P Y C HS

Series Name	Input Voltage (VDC)	Output Quantity	Output Voltage (VDC)	Input Range	Ctrl and Pin Options	SYNC Options	CASE Pin Options	Assembly Options
	24:8.5~36 9~36 **48:**16.5~75 **110:**43~160	**S:**Single	**3P3:**3.3 **05:**5 **12:**12 **15:**15 **24:**24 **28:**28 **48:**48	4:1	□:Negative logic; 0.20" pin length **L:**Negative logic; 0.145" pin length **P:**Positive logic; 0.20" pin length **S:**Positive logic; 0.145"pin length	□:No pin **Y:**SYNC	□:No pin **C:**CASE pin	□: None **Heat-sink type** **HS:**7G-0021A-F; H=0.45” **HS3:**7G-0024A-F; H=0.45” **HS4:** 7GA0127P01-F; H=0.65” **HS5:**7GA0128P01-F; H=1” **Through hole type** **TH:**No thread *The module can’t equip Heat-sink with TH option.

Wall Mounted Type:

HAE150- 48 S 05 W - P TF1 R

Series Name	Input Voltage (VDC)	Output Quantity	Output Voltage (VDC)	Input Range	Ctrl and Pin Options	Assembly Options	Conformal Coating Options
	24:8.5~36 9~36 **48:**16.5~75 **110:**43~160	**S:**Single	**3P3:**3.3 **05:**5 **12:**12 **15:**15 **24:**24 **28:**28 **48:**48	4:1	□:Negative logic; 0.20" pin length **P:**Positive logic; 0.20" pin length	**T:** Without EMC filter **TF1:** Integrated EMC filter and meets EN55032 Class A can be connected to PE	□: None **R:** Conformal Coating

1. No Y and C function for terminal block type, and terminal block type only for 0.20” pin length.

TECHNICAL SPECIFICATION All specifications are typical at nominal input, full load and 25℃ unless otherwise noted

Model Number	Input Range	Output Voltage	Output Current @Full Load	Input Current @No Load	Efficiency	Maximum Capacitor Load
	VDC	VDC	A	mA	%	μF
HAE150-24S3P3W	9 ~ 36	3.3	40	20	88	121000
HAE150-24S05W	9 ~ 36	5	28	25	90	56000
HAE150-24S12W	8.5 ~ 36	12	12	25	90	10000
HAE150-24S15W	8.5 ~ 36	15	9.5	25	91	6300
HAE150-24S24W	8.5 ~ 36	24	6	25	90	2500
HAE150-24S28W	8.5 ~ 36	28	5	25	90	1700
HAE150-24S48W	8.5 ~ 36	48	3	35	90	620
HAE150-48S3P3W	16.5 ~ 75	3.3	40	15	89	121000
HAE150-48S05W	16.5 ~ 75	5	30	15	91	60000
HAE150-48S12W	16.5 ~ 75	12	13	20	91	10800
HAE150-48S15W	16.5 ~ 75	15	10	20	91	6600
HAE150-48S24W	16.5 ~ 75	24	6.5	20	91	2700
HAE150-48S28W	16.5 ~ 75	28	5.5	20	91	1900
HAE150-48S48W	16.5 ~ 75	48	3.2	25	91	660
HAE150-110S3P3W	43 ~ 160	3.3	43	10	88	130000
HAE150-110S05W	43 ~ 160	5	32	10	90	64000
HAE150-110S12W	43 ~ 160	12	15	10	90	12500
HAE150-110S15W	43 ~ 160	15	12	10	90	8000
HAE150-110S24W	43 ~ 160	24	7.5	10	90	3100
HAE150-110S28W	43 ~ 160	28	6.5	10	90	2300
HAE150-110S48W	43 ~ 160	48	3.8	10	90	790

INPUT SPECIFICATIONS

Parameter	Conditions			Min.	Typ.	Max.	Unit
Operating input voltage range		24Vin(nom)	3.3 & 5Vout	9	24	36	VDC
			Others	8.5	24	36	
		48Vin(nom)		16.5	48	75	
		110Vin(nom)		43	110	160	
Start up voltage		24Vin(nom)				9	VDC
		48Vin(nom)				18	
		110Vin(nom)				43	
Shutdown voltage		24Vin(nom)		7.3	7.7	8.1	VDC
		48Vin(nom)		15.5	16	16.3	
		110Vin(nom)		33.0	34.5	36.0	
Start up time	Constant resistive load	Power up			75		ms
		Remote ON/OFF			75		
Input surge voltage	1 second, max.	24Vin(nom)				50	VDC
		48Vin(nom)				100	
		110Vin(nom)				185	
Input filter (1)					Pi type		
Remote ON/OFF	Referred to –Vin pin	Negative logic (Standard)	DC-DC ON		Short or 0 ~ 1.2VDC		
			DC-DC OFF		Open or 3 ~ 12 VDC		
		Positive logic (Option)	DC-DC ON		Open or 3 ~ 12 VDC		
			DC-DC OFF		Short or 0 ~ 1.2VDC		
		Input current of Ctrl pin		-0.5		1	mA
		Remote off input current			3		mA
Sync pin signal				-0.3		5.6	VDC

OUTPUT SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Voltage accuracy		-1.0		+1.0	%
Line regulation	Low Line to High Line at Full Load	-0.1		+0.1	%
Load regulation	No Load to Full Load	-0.1		+0.1	%
Voltage adjustability	Maximum output deviation is inclusive of remote sense	-20		+10	%
Remote sense	% of Vout(nom) If remote sense is not being used, Sense pins should be connected to corresponding polarity OUTPUT pins.			10	%
Ripple and noise	Measured by 20MHz bandwidth With a 1μF/25V X7R MLCC and a 22μF/25V POS-CAP 3.3Vout, 5Vout With a 1μF/25V X7R MLCC and a 22μF/25V POS-CAP 12Vout, 15Vout With a 4.7μF/50V X7R MLCC 24Vout, 28Vout With a 2.2μF/100V X7R MLCC 48Vout		 75 100 200 300		 mVp-p
Temperature coefficient		-0.02		+0.02	%/℃
Transient response recovery time	25% load step change		200	250	μs
Over voltage protection	% of Vout(nom); Hiccup mode	115		130	%
Over load protection	% of Iout rated; Hiccup mode	120		150	%
Short circuit protection		Continuous, automatics recovery			

GENERAL SPECIFICATIONS

Parameter	Conditions			Min.	Typ.	Max.	Unit
Isolation voltage	1 minute (Reinforced insulation)	110Vin(nom)	Input to Output Input (Output) to Case	3000 1500			VAC
	1 minute	Others	Input to Output Input (Output) to Case	3000 1600			VDC
Isolation resistance	500VDC			1			GΩ
Isolation capacitance						2500	pF
Switching frequency				225	250	275	kHz
Safety approvals	IEC/ EN/ UL62368-1					UL:E193009 CB:UL(Demko)	
Standard approvals	EN50155 EN45545-2						
Case material		24Vin(nom) and 48Vin(nom) 110Vin(nom)					Metal Aluminum base-plate with plastic case
Base material		24Vin(nom) and 48Vin(nom)					FR4 PCB
Potting material							Silicone (UL94 V-0)
Weight		Module stand alone HAE150-□□S□□W -**T** HAE150-□□S□□W -**TF1**					105g (3.70oz) 235g (8.29oz) 287g (10.12oz)
MTBF	MIL-HDBK-217F, Full load						3.500×10^5 hrs

ENVIRONMENTAL SPECIFICATIONS

Parameter	Conditions	Min.	Typ.	Max.	Unit
Operating case temperature	Base-plate	-40		+115	℃
Maximum case temperature				115	℃
Over temperature protection			120		℃
Storage temperature range	Terminal block type Others	-40 -55		+105 +125	℃
Thermal impedance	Module without assembly option Only mount on the iron base-plate Heat-sink type with 0.45" Height Heat-sink type with 0.65" Height Heat-sink type with 1" Height		6.1 2.8 4.6 3.5 2.7		℃/W
Thermal shock					MIL-STD-810F
Shock					EN61373, MIL-STD-810F
Vibration					EN61373, MIL-STD-810F
Relative humidity					5% to 95% RH

EMC SPECIFICATIONS


Parameter	Conditions		Level
EMI	EN55032, EN50121-3-2	HAE150-□□S□□W-**TF1** Other models; with external components *Connecting four screw bolts to shield plane will help to reduce the EMI.	Class A Class A, Class B
EMS	EN55035, EN50121-3-2		
ESD	EN61000-4-2	Air ± 8kV and Contact ± 6kV	Perf. Criteria A
Radiated immunity	EN61000-4-3	20V/m	Perf. Criteria A
Fast transient	EN61000-4-4	± 2kV	Perf. Criteria A
	HAE150-24S□□W HAE150-48S□□W	With 2 pcs of aluminum electrolytic capacitor (Nippon Chemi-con KY series, 220μF/100V)	
	HAE150-110S□□W	With 2 pcs of aluminum electrolytic capacitor (Nippon Chemi-con KXJ series, 150μF/200V)	
Surge	EN61000-4-5	±2kV	Perf. Criteria A
	HAE150-24S□□W HAE150-48S□□W	With 2 pcs of aluminum electrolytic capacitor (Nippon Chemi-con KY series, 220μF/100V)	
	HAE150-110S□□W	With 2 pcs of aluminum electrolytic capacitor (Nippon Chemi-con KXJ series, 150μF/200V)	
Conducted immunity	EN61000-4-6	10Vr.m.s	Perf. Criteria A
Power frequency magnetic field	EN61000-4-8	100A/m continuous; 1000A/m 1 second	Perf. Criteria A

Note:


1. Input source impedance: The power module will operate as specifications without external components, assuming that the source voltage has a very low impedance and reasonable input voltage regulation. Highly inductive source impedances can affect the stability of the power module. Since real-world voltage source has finite impedance, performance can be improved by adding external filter capacitor.
   The HAE150-24S□□W and HAE150-48S□□W recommended Nippon Chemi-con KY series, 100μF/100V.
   The HAE150-110S□□W recommended Ruby-con BXF series, 68μF/200V.

CAUTION: This power module is not internally fused. An input line fuse must always be used.


CHARACTERISTIC CURVE




HAE150-48S05W Derating Curve
(See Thermal Considerations)



HAE150-48S05W Efficiency vs. Input Voltage



HAE150-48S05W Derating Curve with Heat-sink
(See Thermal Considerations)



HAE150-48S05W Efficiency vs. Output Load

FUSE CONSIDERATION


This power module is not internally fused. An input line fuse must always be used.
This encapsulated power module can be used in a wide variety of applications, ranging from simple stand-alone operation to an integrated part of sophisticated power architecture.
To maximum flexibility, internal fusing is not included; however, to achieve maximum safety and system protection, always use an input line fuse.
The input line fuse suggest as below：

Model	Fuse Rating (A)	Fuse Type
HAE150-24S□□W	25	Fast-Acting
HAE150-48S□□W	15	Fast-Acting
HAE150-110S□□W	8	Fast-Acting

The table based on the information provided in this data sheet on inrush energy and maximum DC input current at low Vin.

MECHANICAL DRAWING

HAE150-24S□□W, HAE150-48S□□W




■ The screw locked torque: MAX 5.0kgf-cm/0.49N-m

PIN CONNECTION

PIN	DEFINE	DIAMETER
1	-Vin	0.04 Inch
2	Case (option)	0.04 Inch
3	Ctrl	0.04 Inch
4	+Vin	0.04 Inch
5	-Vout	0.08 Inch
6	-Sense	0.04 Inch
7	Trim	0.04 Inch
8	+Sense	0.04 Inch
9	+Vout	0.08 Inch
10	Sync (option)	0.04 Inch

1. All dimensions in inch [mm]
2. Tolerance :x.xx±0.02 [x.x±0.5]
   x.xxx±0.01 [x.xx±0.25]
3. Pin dimension tolerance ±0.004[0.10]


HAE150-110S□□W




■ The screw locked torque: MAX 3.5kgf-cm/0.34N-m

TERMINAL BLOCK TYPE OPTION

HAE150-□□S□□W -T



HAE150-□□S□□W -TF1




TERMINAL CONNECTION

NO.	DEFINE
1	-Vin
2	NC
3	Ctrl
4	+Vin
5	-Vout
6	-Sense
7	Trim
8	+Sense
9	+Vout

1. All dimensions in inch [mm]
2. Tolerance :x.xx±0.02 [x.x±0.5]
   x.xxx±0.01 [x.xx±0.25]
3. Screw 1 locked torque:
   MAX 11.2kgf-cm/ 1.10N-m
4. Screw 2 locked torque:
   MAX 5.2kgf-cm/ 0.51N-m
5. Screw 3 locked torque:
   MAX 16.8kgf-cm/ 1.65N-m

RECOMMENDED PAD LAYOUT



All dimensions in inch[mm]
Pad size(lead free recommended)
Through hole 1,2,3,4,6,7,8,10: Φ0.051[1.30]
Through hole 5,9: Φ0.091[2.30]
Through hole of mounting: Φ0.126[3.20]
Top view pad 1,2,3,4,6,7,8,10: Φ0.064[1.63]
Top view pad 5,9: Φ0.113[2.88]
Top view pad of mounting: Φ0.157[4.00]
Bottom view pad 1,2,3,4,6,7,8,10: Φ0.102[2.60]
Bottom view pad 5,9: Φ0.181[4.60]
Bottom view pad of mounting: Φ0.252[6.40]

THERMAL CONSIDERATIONS

The power module operates in a variety of thermal environments.
However, sufficient cooling should be provided to help ensure reliable operation of the unit.
Heat is removed by conduction, convection, and radiation to the surrounding environment.
Proper cooling can be verified by measuring the point as the figure below.
The temperature at this location should not exceed “Maximum case temperature”.
When operating, adequate cooling must be provided to maintain the test point temperature at or below “Maximum case temperature”.
You can limit this temperature to a lower value for extremely high reliability.


- Thermal test condition with vertical direction by natural convection (20LFM).
- The iron base-plate dimension is 19” X 3.5” X 0.063” (The height is EIA standard 2U).
- The heat-sink is optional and P/N: 7G-0021A-F, 7G-0024A-F, 7GA0127P01-F, 7GA0128P01-F.




BASE PLATE

HEAT-SINK TYPE OPTIONS


HAE150-□□S□□W-**HS**
7G-0021A-F




HAE150-□□S□□W-**HS3**
7G-0024A-F



HAE150-□□S□□W-**HS4**
7GA0127P01-F



HAE150-□□S□□W-**HS5**
7GA0128P01-F



1. All dimensions in inch [mm]
2. Tolerance :x.xx±0.02 [x.x±0.5]
x.xxx±0.01 [x.xx±0.25]

OUTPUT VOLTAGE ADJUSTMENT

Output voltage is adjustable for 10% trim up or -20% trim down of nominal output voltage by connecting an external resistor between the Trim pin and either the +Sense or -Sense pins.
With an external resistor between the Trim and -Sense pin, the output voltage set point decreases.
With an external resistor between the Trim and +Sense pin, the output voltage set point increases.
Maximum output deviation is +10% inclusive of remote sense.
The external TRIM resistor needs to be at least 1/8W of rated power.


■ **Trim Up Equation**

$$R_U = \left(\frac{V_{OUT}(100+\Delta\%)}{1.225\Delta\%} - \frac{100+2\Delta\%}{\Delta\%} \right) k\Omega$$

■ **Trim Down Equation**

$$R_D = \left(\frac{100}{\Delta\%} - 2 \right) k\Omega$$

EXTERNAL OUTPUT TRIMMING
Output can be externally trimmed by using the method shown below.
Trim-up



□□S3P3W

△V	(%)	1	2	3	4	5	6	7	8	9	10
Vout	(V)	3.333	3.366	3.399	3.432	3.465	3.498	3.531	3.564	3.597	3.630
RU	(kΩ)	170.082	85.388	57.156	43.041	34.571	28.925	24.892	21.867	19.515	17.633

□□S05W

△V	(%)	1	2	3	4	5	6	7	8	9	10
Vout	(V)	5.05	5.10	5.15	5.20	5.25	5.30	5.35	5.40	5.45	5.50
RU	(kΩ)	310.245	156.163	104.803	79.122	63.714	53.442	46.105	40.602	36.322	32.898

□□S12W

△V	(%)	1	2	3	4	5	6	7	8	9	10
Vout	(V)	12.12	12.24	12.36	12.48	12.60	12.72	12.84	12.96	13.08	13.20
RU	(kΩ)	887.388	447.592	300.993	227.694	183.714	154.395	133.452	117.745	105.528	95.755

□□S15W

△V	(%)	1	2	3	4	5	6	7	8	9	10
Vout	(V)	15.15	15.30	15.45	15.60	15.75	15.90	16.05	16.20	16.35	16.50
RU	(kΩ)	1134.735	572.490	385.075	291.367	235.143	197.660	170.886	150.806	135.188	122.694

□□S24W

△V	(%)	1	2	3	4	5	6	7	8	9	10
Vout	(V)	24.24	24.48	24.72	24.96	25.20	25.44	25.68	25.92	26.16	26.40
RU	(kΩ)	1876.776	947.184	637.320	482.388	389.429	327.456	283.190	249.990	224.168	203.510

□□S28W


△V	(%)	1	2	3	4	5	6	7	8	9	10
Vout	(V)	28.28	28.56	28.84	29.12	29.40	29.68	29.96	30.24	30.52	30.80
RU	(kΩ)	2206.571	1113.714	749.429	567.286	458.000	385.143	333.102	294.071	263.714	239.429

□□S48W

△V	(%)	1	2	3	4	5	6	7	8	9	10
Vout	(V)	48.48	48.96	49.44	49.92	50.40	50.88	51.36	51.84	52.32	52.80
RU	(kΩ)	3855.551	1946.367	1309.973	991.776	800.857	673.578	582.665	514.480	461.447	419.020

OUTPUT VOLTAGE ADJUSTMENT(CONTINUED)

Trim-down




□□S□□W

△V (%)	1	2	3	4	5	6	7	8	9	10
RD (kΩ)	98.000	48.000	31.333	23.000	18.000	14.667	12.286	10.500	9.111	8.000


△V (%)	11	12	13	14	15	16	17	18	19	20
RD (kΩ)	7.091	6.333	5.692	5.143	4.667	4.250	3.882	3.556	3.263	3.000

SYNCHRONOUS PIN

Multiple module can be synchronized together simply by connecting the module SYNC pins together.



Synchronous Circuits



Recommended Layout

HAE150-24S□□W-**Y**、HAE150-48S□□W -**Y**

Component	Value	Voltage	Reference
C1	220μF	100V	Nippon chemi-con KY-series
C2、C3	2.2μF	100V	1812 MLCC

HAE150-110S□□W -**Y**

Component	Value	Voltage	Reference
C1	150μF	200V	Nippon chemi-con KXJ-series
C2、C3	1μF	250V	1812 MLCC

- Care should be taken to ensure the ground potential differences between modules are minimized.
- All of the modules in this configuration will be synchronized to the highest frequency module.
- Up to three modules can be synchronized using this technique.

P-DUKE Technology Co., Ltd.
Tel +886-4-2359-0668
Fax +886-4-2359-1337
Email sales@pduke.com
Web www.pduke.com
Add No. 36, 22nd Rd., Taichung Industrial Park, Taichung, Taiwan, R.O.C.