

Wirewound, Surface-Mount, High Frequency RF Inductors



TEST EQUIPMENT

- Inductance and Q measured on HP4286A
- SRF measured on HP8753D

APPLICATIONS

- High frequency circuits, bluetooth, tuners, mobile communications
- Impedance matching to optimize power transfer in RF power amplifiers

FEATURES

- Size: 2.5 mm x 2.0 mm x 1.6 mm
- High self-resonant frequency (SRF) from 17 MHz to 6 GHz
- Inductance range: 3.3 nH to 47 μ H
- High Q value
- Core material: ceramic from 3.3 nH to 1000 nH; ferrite from 1200 nH to 47 000 nH
- Terminations: nickel underlayer, with gold plating for 3.3 nH to 1000 nH, and tin plating for 1200 nH to 47 000 nH
- Operating temperature: -40 °C to +125 °C
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912





RoHS
COMPLIANT
HALOGEN
FREE

STANDARD ELECTRICAL SPECIFICATIONS

PART NUMBER	IND. (nH)	TOL.	TEST FREQ. (MHz)		Q MIN.	SRF MIN. (MHz)	DCR MAX. (Ω)	RATED DC CURRENT (mA)
			L	Q				
IMC1008ER3N3S	3.3	0.3 nH	100	1000	50	6000	0.06	1000
IMC1008ER6N8J	6.8	5 %	100	1000	50	5500	0.06	1000
IMC1008ER8N2J	8.2	5 %	100	1000	50	5500	0.06	1000
IMC1008ER10NJ	10	5 %	100	1000	50	4300	0.08	1000
IMC1008ER12NJ	12	5 %	100	500	60	3600	0.08	1000
IMC1008ER15NJ	15	5 %	100	500	60	2700	0.08	1000
IMC1008ER18NJ	18	5 %	100	350	60	2700	0.1	1000
IMC1008ER22NJ	22	5 %	100	350	60	2500	0.1	1000
IMC1008ER27NJ	27	5 %	100	350	60	1800	0.1	1000
IMC1008ER33NJ	33	5 %	100	350	60	1700	0.1	1000
IMC1008ER39NJ	39	5 %	100	350	60	1500	0.1	1000
IMC1008ER47NJ	47	5 %	100	350	60	1500	0.1	1000
IMC1008ER56NJ	56	5 %	100	350	60	1350	0.12	1000
IMC1008ER68NJ	68	5 %	100	350	60	1300	0.15	1000
IMC1008ER82NJ	82	5 %	100	350	60	1100	0.18	1000
IMC1008ERR10J	100	5 %	100	350	60	1100	0.18	1000
IMC1008ERR12J	120	5 %	25	100	45	950	0.2	800
IMC1008ERR15J	150	5 %	25	100	45	880	0.22	800
IMC1008ERR18J	180	5 %	25	100	45	800	0.33	800
IMC1008ERR22J	220	5 %	25	100	45	730	0.45	800
IMC1008ERR27J	270	5 %	25	100	45	650	0.75	600
IMC1008ERR33J	330	5 %	25	100	45	570	0.9	500
IMC1008ERR39J	390	5 %	25	100	45	530	1.06	470
IMC1008ERR47J	470	5 %	25	100	45	480	1.17	420
IMC1008ERR56J	560	5 %	25	100	45	430	1.5	310
IMC1008ERR68J	680	5 %	25	100	45	380	2.06	230
IMC1008ERR82J	820	5 %	25	100	45	350	2.3	180
IMC1008ERR91J	910	5 %	25	100	45	330	3.18	150
IMC1008ER1R0J	1000	5 %	25	50	35	310	3.3	120
IMC1008ER1R2J	1200	5 %	7.96	7.96	20	280	1.3	230

STANDARD ELECTRICAL SPECIFICATIONS

PART NUMBER	IND. (nH)	TOL.	TEST FREQ. (MHz)		Q MIN.	SRF MIN. (MHz)	DCR MAX. (Ω)	RATED DC CURRENT (mA)
			L	Q				
IMC1008ER1R5J	1500	5 %	7.96	7.96	20	250	1.65	220
IMC1008ER1R8J	1800	5 %	7.96	7.96	20	200	2.2	210
IMC1008ER2R2J	2200	5 %	7.96	7.96	20	160	2.35	200
IMC1008ER2R7J	2700	5 %	7.96	7.96	20	130	2.6	195
IMC1008ER3R3J	3300	5 %	7.96	7.96	20	80	2.85	185
IMC1008ER3R9J	3900	5 %	7.96	7.96	20	50	4	180
IMC1008ER4R7J	4700	5 %	7.96	7.96	20	45	4.3	175
IMC1008ER5R6J	5600	5 %	7.96	7.96	20	42	2.6	170
IMC1008ER6R8J	6800	5 %	7.96	7.96	20	39	2.8	165
IMC1008ER8R2J	8200	5 %	7.96	7.96	20	36	3.05	160
IMC1008ER100J	10 000	5 %	2.52	2.52	15	33	3.5	150
IMC1008ER120J	12 000	5 %	2.52	2.52	15	30	3.6	140
IMC1008ER150J	15 000	5 %	2.52	2.52	15	26	4	130
IMC1008ER180J	18 000	5 %	2.52	2.52	15	24	4.5	120
IMC1008ER220J	22 000	5 %	2.52	2.52	15	22	5	110
IMC1008ER270J	27 000	5 %	2.52	2.52	15	21	6	95
IMC1008ER330J	33 000	5 %	2.52	2.52	15	20	6.5	85
IMC1008ER390J	39 000	5 %	2.52	2.52	15	18	8.5	60
IMC1008ER470J	47 000	5 %	2.52	2.52	15	17	14	45

DIMENSIONS in inches [millimeters]




DESCRIPTION

IMC-1008	10 nH	$\pm 5 \%$	ER	e4 ⁽¹⁾
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC® LEAD (Pb)-FREE STANDARD

Note

(1) For 3.3 nH to 1000 nH please use e4 for JEDEC lead (Pb)-free standard. For 1200 nH to 47 000 nH please use e3 for JEDEC lead (Pb)-free standard

GLOBAL PART NUMBER

I M C

PRODUCT
FAMILY

1 0 0 8

SIZE

E R

PACKAGE CODE

ER = tape and reel

1 0 N

INDUCTANCE
VALUE

10N = 0.010 μ H

J



INDUCTANCE
TOLERANCE




J = $\pm 5 \%$

Note

- For additional packaging details see [“Packaging Methods”](#)

PERFORMANCE GRAPHS



TAPE AND REEL SPECIFICATIONS in inches [millimeters]									
REEL DIMENSIONS		TAPE DIMENSIONS				RECOMMENDED PATTERN			
									
MODEL	UNITS PER REEL	MODEL	A	B	T	MODEL	A	B	C
IMC-1008	2000	IMC-1008	0.087 [2.20]	0.110 [2.80]	0.071 [1.80]	IMC-1008	0.047 [1.20]	0.150 [3.80]	0.100 [2.54]



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.