INA250-Q1 AEC-Q100, 36-V, Bidirectional, Precision Current Sense Amplifier With Integrated Shunt Resistor

1 Features

- Qualified for Automotive Applications
- AEC-Q100 Qualified With the Following Results:
  - Device Temperature Grade 1: –40°C to +125°C Ambient Operating Temperature Range
  - Device HBM ESD Classification Level 2
  - Device CDM ESD Classification Level C5
- Functional Safety-Capable
  - Documentation available to aid functional safety system design
- Precision Integrated Shunt Resistor:
  - Shunt Resistor: 2-mΩ
  - Shunt Resistor Tolerance: 0.1% (Maximum)
  - 15 A Continuous from –40°C to +85°C
  - 0°C to +125°C Temperature Coefficient: 10 ppm/°C
- High Accuracy:
  - Gain Error (Shunt and Amplifier): 0.3% (Maximum)
  - Offset Current: 50 mA (Maximum, INA250A2-Q1)
- Four Available Gains:
  - INA250A1-Q1: 200 mV/A
  - INA250A2-Q1: 500 mV/A
  - INA250A3-Q1: 800 mV/A
  - INA250A4-Q1: 2 V/A
- Wide Common-Mode Range: –0.1 V to 36 V
- Specified Operating Temperature: –40°C to +125°C

2 Applications

- Body Control Modules
- DC/DC Converter
- Battery Management Systems
- Engine Control Systems
- Suspension Systems

3 Description


The automotive qualified INA250-Q1 is a voltage-output, current-sensing amplifier family that integrates an internal precision shunt resistor to enable high-accuracy current measurements at common-mode voltages that may vary from 0 V to 36 V, independent of the supply voltage.

The INA250-Q1 family is available in four output voltage scales: 200 mV/A, 500 mV/A, 800 mV/A, and 2 V/A. This device is fully tested and specified for continuous currents up to 10 amps at the maximum temperature of +125°C. The INA250-Q1 device operates from a single 2.7-V to 36-V supply and draws a maximum of 300 µA of supply current. All INA250-Q1 gain versions are specified over the extended operating temperature range of –40°C to +125°C, and are available in a TSSOP-16 package.

Device Information

PART NUMBER	PACKAGE(1)	PACKAGE SIZE(2)
INA250-Q1	PW (TSSOP, 16)	5.00 mm × 6.40 mm

(1) For all available packages, see the orderable addendum at the end of the data sheet.
(2) The package size (length × width) is a nominal value and includes pins, where applicable.



Copyright © 2016, Texas Instruments Incorporated

Simplified Schematic

Table of Contents

1 Features....1
2 Applications....1
3 Description....1
4 Revision History....2
5 Pin Configuration and Functions....3
6 Specifications....4
6.1 Absolute Maximum Ratings....4
6.2 ESD Ratings....4
6.3 Recommended Operating Conditions....4
6.4 Thermal Information....5
6.5 Electrical Characteristics....6
6.6 Typical Characteristics....8
7 Detailed Description....13
7.1 Overview....13
7.2 Functional Block Diagram....13
7.3 Feature Description....13
7.4 Device Functional Modes....16
8 Applications and Implementation....20
8.1 Application Information....20
8.2 Typical Applications....20
8.3 Power Supply Recommendations....24
8.4 Layout....24
9 Device and Documentation Support....27
9.1 Documentation Support....27
9.2 Receiving Notification of Documentation Updates....27
9.3 Support Resources....27
9.4 Trademarks....27
9.5 Electrostatic Discharge Caution....27
9.6 Glossary....27
10 Mechanical, Packaging, and Orderable Information....28

4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Revision B (April 2020) to Revision C (September 2023) — **Page**

- Changed the numbering format for tables, figures, and cross-references throughout the document.... 1
- Changed the *Device Information* table to *Package Information* 1
- Changed the *Shunt resistance (SH+ to SH–)* minimum value for use as stand-alone resistor from: 1.9 mΩ to 1.8 mΩ in the *Electrical Characteristics* table.... 6
- Changed the *Shunt resistance (SH+ to SH–)* minimum value for use as stand-alone resistor from: 2.1 mΩ to 2.2 mΩ in the *Electrical Characteristics* table.... 6

Changes from Revision A (November 2016) to Revision B (April 2020) — **Page**

- Added Functional Safety-Capable information.... 1

Changes from Revision * (July 2016) to Revision A (November 2016) — **Page**

- Document status changed from Product Preview to Production Data 1
- Changed maximum charged-device model ESD value from ±750 to ±1000 4
- Changed maximum I_B values in the *Electrical Characteristics* table from ±35 to ±40.... 6

Copyright © 2023 Texas Instruments Incorporated

5 Pin Configuration and Functions




Figure 5-1. PW Package 16-Pin TSSOP Top View

Table 5-1. Pin Functions

PIN		I/O	DESCRIPTION
NAME	NO.		
GND	6, 8, 11	Analog	Ground
IN–	1, 2, 3	Analog input	Connect to load
IN+	14, 15, 16	Analog input	Connect to supply
OUT	9	Analog output	Output voltage
REF	7	Analog input	Reference voltage, 0 V to VS (up to 18 V)
SH–	4	Analog output	Kelvin connection to internal shunt. Connect to VIN– if no filtering is needed. See Figure 7-4 for filter recommendations.
SH+	13	Analog output	Kelvin connection to internal shunt. Connect to VIN+ if no filtering is needed. See Figure 7-4 for filter recommendations.
VIN–	5	Analog input	Voltage input from load side of shunt resistor.
VIN+	12	Analog input	Voltage input from supply side of shunt resistor.
VS	10	Analog	Device power supply, 2.7 V to 36 V

Copyright © 2023 Texas Instruments Incorporated

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

		MIN	MAX	UNIT
Supply voltage (VS)			40	V
Analog input current	Continuous current		±15	A
Analog inputs (IN+, IN–)	Common-mode	GND – 0.3	40	V
Analog inputs (VIN+, VIN–)	Common-mode	GND – 0.3	40	V
	Differential (V_{IN+}) – ($V_{IN–}$)	–40	40	
Analog inputs (REF)		GND – 0.3	VS + 0.3	V
Analog outputs (SH+, SH–)	Common-mode	GND – 0.3	40	V
Analog outputs (OUT)		GND – 0.3	(VS + 0.3) up to 18	V
Temperature	Operating, T_A	–55	150	°C
	Junction, T_J		150	
	Storage, T_{stg}	–65	150	

(1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.

6.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human-body model (HBM), per AEC Q100-002(1)	±2000	V
		Charged-device model (CDM), per AEC Q100-011	±1000	

(1) AEC Q100-002 indicates that HBM stressing shall be in accordance with the ANSI/ESDA/JEDEC JS-001 specification.

6.3 Recommended Operating Conditions

		MIN	NOM	MAX	UNIT
V_{CM}	Common-mode input voltage	0		36	V
VS	Operating supply voltage	2.7		36	V
T_A	Operating free-air temperature	–40		125	°C

Copyright © 2023 Texas Instruments Incorporated

6.4 Thermal Information

THERMAL METRIC[1]		INA250-Q1 PW (TSSOP) 16 PINS	UNIT
$R_{\theta JA}$	Junction-to-ambient thermal resistance	104.4	°C/W
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	42.3	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	48.5	°C/W
ψ_{JT}	Junction-to-top characterization parameter	4.5	°C/W
ψ_{JB}	Junction-to-board characterization parameter	48	°C/W
$R_{\theta JC(bot)}$	Junction-to-case (bottom) thermal resistance	N/A	°C/W

(1) For more information about traditional and new thermal metrics, see *Semiconductor and IC Package Thermal Metrics* (SPRA953).

Copyright © 2023 Texas Instruments Incorporated

6.5 Electrical Characteristics

at T_A = 25°C, VS = 5 V, V_{IN+} = 12 V, V_{REF} = 2.5 V, I_{SENSE} = IN+ = 0 A, unless otherwise noted.

PARAMETER		CONDITIONS	MIN	TYP	MAX	UNIT
INPUT						
V_{CM}	Common-mode input range		–0.1		36	V
CMR	Common-mode rejection	INA250A1-Q1, V_{IN+} = 0 V to 36 V, T_A = –40°C to 125°C	94	102		dB
		INA250A2-Q1, V_{IN+} = 0 V to 36 V, T_A = –40°C to 125°C	97	110		
		INA250A3-Q1, V_{IN+} = 0 V to 36 V, T_A = –40°C to 125°C	106	114		
		INA250A4-Q1, V_{IN+} = 0 V to 36 V, T_A = –40°C to 125°C	108	118		
I_{OS}	Offset current, RTI(1)	INA250A1-Q1, I_{SENSE} = 0 A		±15	±100	mA
		INA250A2-Q1, I_{SENSE} = 0 A		±12.5	±50	
		INA250A3-Q1, I_{SENSE} = 0 A		±5	±30	
		INA250A4-Q1, I_{SENSE} = 0 A		±5	±20	
dI_{OS}/dT	RTI versus temperature	T_A = –40°C to 125°C		25	250	µA/°C
PSR		VS = 2.7 V to 36 V, T_A = –40°C to 125°C		±0.03	±1	mA/V
I_B	Input bias current	I_{B+}, I_{B-}, I_{SENSE} = 0 A		±28	±40	µA
V_{REF}	Reference input range(3)		0		(VS) up to 18	V
SHUNT RESISTOR(5)						
R_{SHUNT}	Shunt resistance (SH+ to SH–)	Equivalent resistance when used with onboard amplifier	1.998	2	2.002	mΩ
		Used as stand-alone resistor(7)	1.8	2	2.2	
	Package resistance	IN+ to IN–		4.5		mΩ
	Resistor temperature coefficient	T_A = –40°C to 125°C		15		ppm/°C
		T_A = –40°C to 0°C		50		
		T_A = 0°C to 125°C		10		
I_{SENSE}	Maximum continuous current(4)	T_A = –40°C to 85°C			±15	A
	Shunt short time overload	I_{SENSE} = 30 A for 5 seconds		±0.05%		
	Shunt thermal shock	–65°C to 150°C, 500 cycles		±0.1%		
	Shunt resistance to solder heat	260°C solder, 10 s		±0.1%		
	Shunt high temperature exposure	1000 hours, T_A = 150°C		±0.15%		
	Shunt cold temperature storage	24 hours, T_A = –65°C		±0.025%		

Copyright © 2023 Texas Instruments Incorporated

at T_A = 25°C, VS = 5 V, V_{IN+} = 12 V, V_{REF} = 2.5 V, I_{SENSE} = IN+ = 0 A, unless otherwise noted.

PARAMETER		CONDITIONS	MIN	TYP	MAX	UNIT
OUTPUT						
G	Gain	INA250A1-Q1		200		mV/A
		INA250A2-Q1		500		
		INA250A3-Q1		800		
		INA250A4-Q1		2		V/A
	System gain error(6)	I_{SENSE} = –10 A to 10 A, T_A = 25°C		±0.05%	±0.3%	
		I_{SENSE} = –10 A to 10 A, T_A = –40°C to 125°C			±0.75%	
		T_A = –40°C to 125°C			45	ppm/°C
	Nonlinearity error	I_{SENSE} = 0.5 A to 10 A		±0.03%		
R_O	Output impedance			1.5		Ω
	Maximum capacitive load	No sustained oscillation		1		nF
VOLTAGE OUTPUT(2)						
	Swing to VS power-supply rail	R_L = 10 kΩ to GND		(VS) – 0.1	(VS) – 0.2	V
	Swing to GND	R_L = 10 kΩ to GND		(V_{GND}) + 25	(V_{GND}) + 50	mV
FREQUENCY RESPONSE						
BW	Bandwidth	INA250A1-Q1, C_L = 10 pF		50		kHz
		INA250A2-Q1, C_L = 10 pF		50		
		INA250A3-Q1, C_L = 10 pF		35		
		INA250A4-Q1, C_L = 10 pF		11		
SR	Slew rate	C_L = 10 pF		0.2		V/µs
NOISE, RTI(1)						
	Voltage noise density	INA250A1-Q1		51		nV/√Hz
		INA250A2-Q1		35		
		INA250A3-Q1		37		
		INA250A4-Q1		27		
POWER SUPPLY						
VS	Operating voltage range		2.7		36	V
I_Q	Quiescent current	T_A = –40°C to 125°C		200	300	µA
TEMPERATURE RANGE						
	Specified range		–40		125	°C

(1) RTI = referred-to-input.
(2) See *Output Voltage Swing vs Output Current* (Figure 6-19).
(3) The supply voltage range maximum is 36 V, but the reference voltage cannot be higher than 18 V.
(4) See Figure 7-1 and the *Layout* section for additional information on the current derating and layout recommendations to improve the current handling capability of the device at higher temperatures.
(5) See the *Integrated Shunt Resistor* section for additional information regarding the integrated current-sensing resistor.
(6) System gain error includes amplifier gain error and the integrated sense resistor tolerance. System gain error does not include the stress related characteristics of the integrated sense resistor. These characteristics are described in the *Shunt Resistor* section of the *Electrical Characteristics* table.
(7) The internal shunt resistor is intended to be used with the internal amplifier and is not intended to be used as a stand-alone resistor. See the *Integrated Shunt Resistor* section for more information.

Copyright © 2023 Texas Instruments Incorporated

6.6 Typical Characteristics

at T_A = 25°C, VS = 5 V, V_{IN+} = 12 V, V_{REF} = 2.5 V, I_{SENSE} = IN+ = 0 A, unless otherwise noted.




Figure 6-1. INA250A1-Q1 Input Offset Distribution




Figure 6-2. INA250A2-Q1 Input Offset Distribution




Figure 6-3. INA250A3-Q1 Input Offset Distribution




Figure 6-4. INA250A4-Q1 Input Offset Distribution




Figure 6-5. Input Offset vs Temperature




Figure 6-6. INA250A1-Q1 Common-Mode Rejection Ratio Distribution

Copyright © 2023 Texas Instruments Incorporated




Figure 6-7. INA250A2-Q1 Common-Mode Rejection Ratio Distribution




Figure 6-8. INA250A3-Q1 Common-Mode Rejection Ratio Distribution




Figure 6-9. INA250A4-Q1 Common-Mode Rejection Ratio Distribution




Figure 6-10. Common-Mode Rejection Ratio vs Temperature




Figure 6-11. Power-Supply Rejection Ratio Distribution




Figure 6-12. Power-Supply Rejection Ratio vs Temperature

Copyright © 2023 Texas Instruments Incorporated





Figure 6-13. System Gain Error vs Temperature



System gain error = R_{SHUNT} error + amplifier gain error, load current = 10 A

Figure 6-14. System Gain Error Distribution






Figure 6-15. Amplifier Gain Error vs Temperature




V_{CM} = 12 V, I_{SENSE} = 500 mA_{PP}

Figure 6-16. Amplifier Gain vs Frequency



V_{CM} = 12 V, V_{REF} = 2.5 V, I_{SENSE} = 0 A, VS = 5 V + 250-mV sine disturbance

Figure 6-17. Power-Supply Rejection vs Frequency



VS = 5 V, V_{REF} = 2.5 V, I_{SENSE} = 0 A, V_{CM} = 1-V sine wave

Figure 6-18. Common-Mode Rejection vs Frequency

Copyright © 2023 Texas Instruments Incorporated






Figure 6-19. Output Voltage Swing vs Output Current




I_{SENSE} = 0 A, VS = 5 V

Figure 6-20. Input Bias Current vs Common-Mode Voltage (VS = 5 V)




I_{SENSE} = 0 A, VS = 0 V, VREF = 0 V

Figure 6-21. Input Bias Current vs Common-Mode Voltage (VS = 0 V)




I_{SENSE} = 0 A, VS = 5 V

Figure 6-22. Input Bias Current vs Temperature




VREF = VS / 2

Figure 6-23. Quiescent Current vs Temperature




VREF = 2.5 V

Figure 6-24. Quiescent Current vs Supply Voltage




VS = 5 V, V_{REF} = 2.5 V, I_{SENSE} = 0 A

Figure 6-25. Input-Referred Voltage Noise vs Frequency




VS = 5 V, V_{CM} = 0 V, I_{SENSE} = 0 A

Figure 6-26. 0.1-Hz to 10-Hz Voltage Noise (Referred-to-Input)



Input = (VIN+) - (VIN-)

Figure 6-27. Step Response



Input = VIN+, V_{REF} = 2.5 V

Figure 6-28. Common-Mode Transient Response




Figure 6-29. Start-Up Response


Copyright © 2023 Texas Instruments Incorporated

7 Detailed Description

7.1 Overview

The INA250-Q1 features a 2-mΩ, precision, current-sensing resistor and a 36-V common-mode, zero-drift topology, precision, current-sensing amplifier integrated into a single package. High precision measurements are enabled through the matching of the shunt resistor value and the current-sensing amplifier gain providing a highly-accurate, system-calibrated solution. Multiple gain versions are available to allow for the optimization of the desired full-scale output voltage based on the target current range expected in the application.

7.2 Functional Block Diagram



7.3 Feature Description

7.3.1 Integrated Shunt Resistor

The INA250-Q1 features a precise, low-drift, current-sensing resistor to allow for precision measurements over the entire specified temperature range of –40°C to +125°C. The integrated current-sensing resistor ensures measurement stability overtemperature and improves layout and board constraint difficulties common in high precision measurements.

The onboard current-sensing resistor is designed as a 4-wire (or Kelvin) connected resistor that enables accurate measurements through a force-sense connection. Connecting the amplifier inputs pins (VIN– and VIN+) to the sense pins of the shunt resistor (SH– and SH+) eliminates many of the parasitic impedances commonly found in typical very-low sensing-resistor level measurements. Although the sense connection of the current-sensing resistor may be accessed through the SH+ and SH– pins, this resistor is not intended to be used as a stand-alone component. The INA250-Q1 device is system-calibrated to ensure that the current-sensing resistor and current-sensing amplifier are both precisely matched to one another. Using the shunt resistor without the onboard amplifier results in a current-sensing resistor tolerance of approximately 5%. To achieve the optimized system gain specification, the onboard sensing resistor must be used with the internal current-sensing amplifier.

The INA250-Q1 has approximately 4.5-mΩ of package resistance. 2 mΩ of this total package resistance is a precisely-controlled resistance from the Kelvin-connected current-sensing resistor used by the amplifier. The power dissipation requirements of the system and package are based on the total 4.5-mΩ package resistance between the IN+ and IN– pins. The heat dissipated across the package when current flows through the device ultimately determines the maximum current that may be safely handled by the package. The current consumption of the silicon is relatively low, leaving the total package resistance carrying the high load current as the primary contributor to the total power dissipation of the package. The maximum safe-operating current

Copyright © 2023 Texas Instruments Incorporated

level ensures that the heat dissipated across the package is limited so that the resistor and the package are not damaged, and the internal junction temperature of the silicon does not exceed a +150°C limit.

External factors (such as ambient temperature, external air flow, and PCB layout) may contribute to how effectively the heat developed from the current flowing through the total package resistance may be removed from the device. Under the conditions of no air flow, a maximum ambient temperature of +85°C, and 1-oz. copper input power planes, the INA250-Q1 device can accommodate continuous current levels up to 15 A. As shown in Figure 7-1, the current handling capability is derated at temperatures above the +85°C level with safe operation up to 10 A at a +125°C ambient temperature. With air flow and larger 2-oz. copper input power planes, the INA250-Q1 may safely accommodate continuous current levels up to 15 A over the entire –40°C to +125°C temperature range.




Figure 7-1. Maximum Current vs Temperature

7.3.2 Short-Circuit Duration

The INA250-Q1 features a physical shunt resistance that can withstand current levels higher than the continuous handling limit of 15 A without sustaining damage to the current-sensing resistor or the current-sensing amplifier if the excursions are brief. Figure 7-2 shows the short-circuit duration curve for the INA250-Q1.




Figure 7-2. Short-Circuit Duration

7.3.3 Temperature Stability

System calibration is common for many industrial applications to eliminate initial component and system-level errors that may be present. A system-level calibration may reduce the initial accuracy requirement for many of the individual components because the calibration procedure eliminates these errors associated with the components Performing this calibration may enable precision measurements at the system calibration temperature, but as the system temperature changes as a result of external ambient changes or self heating, measurement errors are reintroduced. Without using accurate temperature compensation in addition to the initial adjustment, the calibration procedure is ineffective in accounting for these temperature-induced changes.

Copyright © 2023 Texas Instruments Incorporated

One of the primary benefits of the very-low-temperature coefficient of the INA250-Q1(including the integrated current-sensing resistor and current-sensing amplifier) is that the device measurement remains highly accurate, even when the temperature changes throughout the specified temperature range.

The drift performance of the integrated current-sensing resistor is shown in Figure 7-3. Although several temperature ranges are specified in the *Electrical Characteristics* table, applications operating in ranges other than those described may use Figure 7-3 to determine how much variance in the shunt resistor value may be expected. As with any resistive element, the tolerance of the component varies when exposed to different temperature conditions. For the current-sensing resistor integrated in the INA250-Q1, the resistor varies more when operating in temperatures ranging from –40°C to 0°C than when operating in ranges from 0°C to +125°C. However, even in the –40°C to 0°C temperature range, the drift is still low at 25 ppm/°C.




Figure 7-3. Sensing Resistor vs Temperature

An additional aspect to consider is that when current flows through the current-sensing resistor, power dissipates across this component. This dissipated power results in an increase in the internal temperature of the package, including the integrated sensing resistor. This resistor self-heating effect results in an increase of the resistor temperature helping to move the component out of the colder, wider drift temperature region.

Copyright © 2023 Texas Instruments Incorporated

7.4 Device Functional Modes

7.4.1 Amplifier Operation

The INA250-Q1 current-sense amplifier may be configured to measure both unidirectional and bidirectional currents through the reference voltage level applied to the reference pin (REF). The reference voltage connected to REF sets the output level that corresponds with a zero input current condition. For unidirectional operation, tie the REF pin to ground so that when the current increases, the output signal also increases upwards from this reference voltage (or ground in this case). For bidirectional currents, an external voltage source may be used as the reference voltage connected to the REF pin to bias up the output. Set the reference voltage to enable sufficient range above and below this level based on the expected current range to be measured. Positive currents result in an output signal that increases from the zero-current output level set by the reference voltage, whereas negative currents result in an output signal that decreases.

Equation 1 shows the amplifier transfer function for both unidirectional and bidirectional amplifiers:

$$V_{OUT} = (I_{LOAD} \times GAIN) + V_{REF} \quad (1)$$

where:

- I_{LOAD} is the current being measured passing through the internal shunt resistor,
- GAIN is the corresponding gain (mA/V) of the selected device, and
- V_{REF} is the voltage applied to the REF pin

As with any difference amplifier, the INA250-Q1 common-mode rejection ratio is affected by any impedance present at the REF input. This concern is not a problem when the REF pin is connected directly to a reference or power supply. When using resistive dividers from a power supply or a reference voltage, buffer the REF pin with an op amp.

7.4.2 Input Filtering

An obvious and straightforward location for filtering is at the device output; however, this location negates the advantage of the low output impedance of the output stage buffer. The input then represents the best location for implementing external filtering. Figure 7-4 shows the typical implementation of the input filter for the device.




Figure 7-4. Input Filter

Copyright © 2023 Texas Instruments Incorporated

However, the addition of external series resistance at the input pins to the amplifier creates an additional error in the measurement. If possible, keep the value of these series resistors to 10 Ω or less to reduce the affect to accuracy. The internal bias network illustrated in Figure 7-4 at the input pins creates a mismatch in input bias currents when a differential voltage is applied between the input pins, as shown in Figure 7-5.




Figure 7-5. Input Bias Current vs Differential Input Voltage

7.4.2.1 Calculating Gain Error Resulting from External Filter Resistance

If additional external series filter resistors are added to the circuit, the mismatch in bias currents results in a mismatch of voltage drops across the filter resistors. This mismatch creates a differential error voltage that subtracts from the voltage developed across the Kelvin connection of the shunt resistor, thus reducing the voltage that reaches the amplifier input terminals. Without the additional series resistance, the mismatch in input bias currents has little effect on device operation as a result of the low input bias current of the amplifier and the typically low impedance of the traces between the shunt and amplifier input pins. The amount of error these external filter resistors add to the measurement may be calculated using Equation 3, where the gain error factor is calculated using Equation 2.

The amount of variance between the differential voltage present at the device input relative to the voltage developed at the shunt resistor is based both on the external series resistance value as well as the internal input resistors, R_{INT}, as shown in Figure 7-4. The reduction of the shunt voltage reaching the device input pins appears as a gain error when comparing the output voltage relative to the voltage across the shunt resistor. A factor may be calculated to determine the amount of gain error that is introduced by the addition of external series resistance. Equation 2 calculates the expected deviation from the shunt voltage compared to the expected voltage at the device input pins.

$$\text{Gain Error Factor} = \frac{(1250 \times R_{INT})}{(1250 \times R_S) + (1250 \times R_{INT}) + (R_S \times R_{INT})} \quad (2)$$

where:

- R_{INT} is the internal input resistor and
- R_S is the external series resistance

$$\text{Gain Error (\%)} = 100 - (100 \times \text{Gain Error Factor}) \quad (3)$$

With the adjustment factor equation including the device internal input resistance, this factor varies with each gain version, as shown in Table 7-1. Table 7-2 lists the gain error factor for each individual device.

Equation 3 calculates the expected gain error from the addition of the external series resistors.

Copyright © 2023 Texas Instruments Incorporated

Table 7-1. Input Resistance

DEVICE	GAIN	R_{INT}
INA250A1-Q1	200 mV/A	50 kΩ
INA250A2-Q1	500 mV/A	20 kΩ
INA250A3-Q1	800 mV/A	12.5 kΩ
INA250A4-Q1	2 V/A	5 kΩ

Table 7-2. Device Gain Error Factor

DEVICE	SIMPLIFIED GAIN ERROR FACTOR
INA250A1-Q1	$\frac{50{,}000}{(41 \bullet R_S) + 50{,}000}$
INA250A2-Q1	$\frac{20{,}000}{(17 \bullet R_S) + 20{,}000}$
INA250A3-Q1	$\frac{12{,}500}{(11 \bullet R_S) + 12{,}500}$
INA250A4-Q1	$\frac{1{,}000}{R_S + 1{,}000}$

For example, using an INA250A2-Q1 device and the corresponding gain error equation from Table 7-2, a series resistance of 10-Ω results in a gain error factor of 0.991. The corresponding gain error is then calculated using Equation 3, resulting in a gain error of approximately 0.84% because of the external 10-Ω series resistors.

7.4.3 Shutting Down the Device

Although the device does not have a shutdown pin, the low power consumption allows for the device to be powered from the output of a logic gate or transistor switch that may turn on and turn off the voltage connected to the device power-supply pin. However, in current-shunt monitoring applications, there is also a concern for how much current is drained from the shunt circuit in shutdown conditions. Evaluating this current drain involves considering the simplified schematic in shutdown mode, as shown in Figure 7-6.




Figure 7-6. Shutting Down the Device

Copyright © 2023 Texas Instruments Incorporated

Note that there is typically an approximate 1-MΩ impedance (from the combination of the feedback and input resistors) from each device input to the REF pin. The amount of current flowing through these pins depends on the respective configuration. For example, if the REF pin is grounded, calculating the effect of the 1-MΩ impedance from the shunt to ground is straightforward. However, if the reference or op amp is powered when the device is shut down, the calculation is direct. Instead of assuming 1 MΩ to ground, assume 1 MΩ to the reference voltage. If the reference or op amp is also shut down, some knowledge of the reference or op amp output impedance under shutdown conditions is required. For instance, if the reference source functions similar to an open circuit when un-powered, little or no current flows through the 1-MΩ path.

7.4.4 Using the Device with Common-Mode Transients Above 36 V

With a small amount of additional circuitry, the device may be used in circuits subject to transients higher than 36 V (such as in automotive applications). Use only zener diodes or zener-type transient absorbers (sometimes referred to as *transzorbs*); any other type of transient absorber has an unacceptable time delay. Start by adding a pair of resistors, as shown in Figure 7-7, as a working impedance for the zener. Keeping these resistors as small as possible is preferable; a resistor value of 10-Ω is the most common. This value limits the effect on accuracy with the addition of these external components, as described in the *Input Filtering* section. Device interconnections between the shunt resistor and amplifier have a current handling limit of 1 A. Using a 10-Ω resistor limits the allowable transient range to 10 V above the zener clamp so the device is not damaged. Larger resistor values may be used in this protection circuit to accommodate a larger transient voltage range, which results in a larger effect on gain error. Because this circuit limits only short-term transients, many applications are satisfied with a 10-Ω resistor, along with conventional zener diodes of the lowest power rating available.




Figure 7-7. Device Transient Protection

8 Applications and Implementation

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

8.1 Application Information

The INA250-Q1 measures the voltage developed across the internal current-sensing resistor when current passes through the device. The ability to drive the reference pin to adjust the functionality of the output signal offers multiple configurations, as discussed in this section.

8.2 Typical Applications

8.2.1 Current Summing




Figure 8-1. Daisy-Chain Configuration

Copyright © 2023 Texas Instruments Incorporated


8.2.1.1 Design Requirements

Three daisy-chained devices are illustrated in Figure 8-1. The reference input of the first INA250-Q1 device sets the quiescent level on the output of all the INA250-Q1 devices in the string.

8.2.1.2 Detailed Design Procedure

The outputs of multiple INA250-Q1 devices are easily summed by connecting the output signal of one INA250-Q1 device to the reference input of a second INA250-Q1 device. Summing beyond two devices is possible by repeating this configuration, connecting the output signal of the next INA250-Q1 device to the reference pin of a subsequent INA250-Q1 in the chain. The output signal of the final INA250-Q1 device in this chain includes the current level information for all channels in the chain.

8.2.1.3 Application Curve



VS = 5 V, V_{REF} = 2.5 V

Figure 8-2. Daisy-Chain Configuration Output Response

8.2.2 Parallel Multiple INA250-Q1 Devices for Higher Current




Figure 8-3. Parallel Summing Configuration


8.2.2.1 Design Requirements

The parallel connection for multiple INA250-Q1 devices may reduce the equivalent overall sense resistance, enabling monitoring of higher current levels than a single device is able to accommodate alone. This configuration also uses a summing arrangement, as described in the *Current Summing* section. A parallel summing configuration is shown in Figure 8-3.

8.2.2.2 Detailed Design Procedure

With a summing configuration, the output of the first channel is fed into the reference input of the second, adding the distributed measurements back together into a single measured value.

8.2.2.3 Application Curve



VS = 24 V, V_{REF} = 12 V

Figure 8-4. Parallel Configuration Output Response

Copyright © 2023 Texas Instruments Incorporated

8.2.3 Current Differencing




Figure 8-5. Current Differencing Configuration

8.2.3.1 Design Requirements


Occasionally, the need may arise to confirm that the current into a load is identical to the current coming out of a load, such as when performing diagnostic testing or fault detection. This procedure requires precision current differencing. This method is the same as current summing, except that the two amplifiers have the respective inputs connected opposite of each other. Under normal operating conditions, the final output is close to the reference value and proportional to any current difference. Figure 8-5 is an example of two INA250-Q1 devices connected for current differencing.

Copyright © 2023 Texas Instruments Incorporated

8.2.3.2 Detailed Design Procedure

The load current may also be measured directly at the output of the first channel. Although technically this configuration is current differencing, this connection (see Figure 8-5) is intended to allow the upper (positive) sense channel to report any positive-going excursions in the overall output, and the lower (negative) sense channel to report any negative-going excursions.

8.2.3.3 Application Curve



VS = 5 V, V_{REF} = 2.5 V

Figure 8-6. Current Differencing Configuration Output Response

8.3 Power Supply Recommendations

The input circuitry of the device may accurately measure signals on common-mode voltages beyond the power-supply voltage, VS. For example, the voltage applied to the VS power-supply pin may be 5 V, whereas the load power-supply voltage being monitored (the common-mode voltage) may be as high as 36 V. Note that the device may withstand the full 0-V to 36-V range at the input pins, regardless of whether the device has power applied or not. Power-supply bypass capacitors are required for stability, and must be placed as closely as possible to the supply and ground pins of the device. A typical value for this supply bypass capacitor is 0.1 µF. Applications with noisy or high-impedance power supplies may require additional decoupling capacitors to reject power-supply noise.

8.4 Layout

8.4.1 Layout Guidelines

- The INA250-Q1 is specified for current handling of up to 10 A over the entire –40°C to +125°C temperature range using a 1-oz. copper pour for the input power plane as well as no external airflow passing over the device.
- The primary current-handling limitation for the INA250-Q1 is how much heat is dissipated inside the package. Efforts to improve heat transfer out of the package and into the surrounding environment improve the ability of the device to handle currents of up to 15 A over the entire –40°C to +125°C temperature range.
- Heat transfer improvements primarily involve larger copper power traces and planes with increased copper thickness (2 oz.) as well as providing airflow to pass over the device. The *INA250EVM* (SBOU153) is capable of supporting 15 A at temperatures up to +125°C.
- Place the power-supply bypass capacitor as close as possible to the supply and ground pins. TI recommends a bypass capacitor value of 0.1 µF. Additional decoupling capacitance may be added to compensate for noisy or high-impedance power supplies.

Copyright © 2023 Texas Instruments Incorporated

8.4.2 Layout Examples




Figure 8-7. Recommended Layout




Figure 8-8. Recommended Layout Schematic

Copyright © 2023 Texas Instruments Incorporated

9 Device and Documentation Support

9.1 Documentation Support

9.1.1 Related Documentation

- *INA250EVM User Guide* (SBOU153).

9.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Subscribe to updates* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

9.3 Support Resources

TI E2E™ support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

9.4 Trademarks

TI E2E™ is a trademark of Texas Instruments.
All trademarks are the property of their respective owners.

9.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

9.6 Glossary

TI Glossary	This glossary lists and explains terms, acronyms, and definitions.

Copyright © 2023 Texas Instruments Incorporated

10 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Copyright © 2023 Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
INA250A1QPWRQ1	Active	Production	TSSOP (PW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	Q250A1
INA250A1QPWRQ1.B	Active	Production	TSSOP (PW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	Q250A1
INA250A2QPWRQ1	Active	Production	TSSOP (PW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	Q250A2
INA250A2QPWRQ1.B	Active	Production	TSSOP (PW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	Q250A2
INA250A3QPWRQ1	Active	Production	TSSOP (PW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	Q250A3
INA250A3QPWRQ1.B	Active	Production	TSSOP (PW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	Q250A3
INA250A4QPWRQ1	Active	Production	TSSOP (PW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	Q250A4
INA250A4QPWRQ1.B	Active	Production	TSSOP (PW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	Q250A4

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF INA250-Q1 :


- Catalog : INA250

NOTE: Qualified Version Definitions:


- Catalog - TI's standard catalog product

TAPE AND REEL INFORMATION

REEL DIMENSIONS




TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers


QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
INA250A1QPWRQ1	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
INA250A2QPWRQ1	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
INA250A3QPWRQ1	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
INA250A4QPWRQ1	TSSOP	PW	16	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
INA250A1QPWRQ1	TSSOP	PW	16	2000	353.0	353.0	32.0
INA250A2QPWRQ1	TSSOP	PW	16	2000	353.0	353.0	32.0
INA250A3QPWRQ1	TSSOP	PW	16	2000	353.0	353.0	32.0
INA250A4QPWRQ1	TSSOP	PW	16	2000	353.0	353.0	32.0

PACKAGE OUTLINE

PW0016A


TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE




NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE: 10X




SOLDER MASK DETAILS

4220204/B 12/2023

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE: 10X

4220204/B 12/2023

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale, TI’s General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025