1.7Ω, 500V

Integrated Power Module for Small Appliance Motor Drive Applications

Description

IRSM505-055 and IRSM515-055 are 3-phase Integrated Power Modules (IPM) designed for advanced appliance motor drive applications such as energy efficient fans and pumps. These advanced IPMs offers a combination of low $R_{DS(on)}$ Trench FREDFET technology and the industry benchmark half-bridge high voltage, rugged driver in a familiar package. The modules are optimized for low EMI characteristics.
IRSM505-055 includes temperature feedback while IRSM515-055 does not.

Features

- 500V 3-phase inverter including high voltage gate drivers
- Integrated bootstrap functionality
- Low 1.7Ω (max, 25°C) $R_{DS(on)}$ Trench FREDFET
- Under-voltage lockout for all channels
- Matched propagation delay for all channels
- Temperature feedback via NTC (IRSM505-055 only)
- Optimized dV/dt for loss and EMI trade offs
- Open-source for single and leg-shunt current sensing
- 3.3V logic compatible & advanced input filter
- Driver tolerant to negative transient voltage (-Vs)
- Isolation 1900V_{RMS}, 1min
- RoHS Compliant
- Certified by UL - File Number E252584







Series	NTC	Package Type	Standard Pack		Product Name
			Form	Quantity	
IRSM505-055	Yes	SOP23	Tube	240	IRSM505-055PA
		DIP23	Tube	240	IRSM505-055DA
		DIP23A	Tube	240	IRSM505-055DA2
IRSM515-055	No	SOP23	Tube	240	IRSM515-055PA
		DIP23	Tube	240	IRSM515-055DA
		DIP23A	Tube	240	IRSM515-055DA2

© 2020 Infineon Technologies

Internal Electrical Schematic



IRSM505-055



IRSM515-055

Absolute Maximum Ratings

Absolute maximum ratings indicate sustained limits beyond which damage to the module may occur. These are not tested at manufacturing. All voltage parameters are absolute voltages referenced to COM unless otherwise stated in the table.

Symbol	Description	Min	Max	Unit
BV_{DSS}	MOSFET Blocking Voltage	---	500	V
I_O @ T_C=25°C	DC Output Current per MOSFET	---	2.4	A
I_{OP} @ T_C =25°C	Pulsed Output Current per MOSFET (Note 1)	---	15	
P_d @ T_C=25°C	Maximum Power Dissipation per MOSFET	---	18	W
V_{ISO}	Isolation Voltage (1min)	---	1900	V_{RMS}
T_J	Operating Junction Temperature	-40	150	°C
T_C	Operating Case Temperature	-40	150	°C
T_S	Storage Temperature	-40	150	°C
$V_{S1,2,3}$	High Side Floating Supply Offset Voltage	$V_{B1,2,3}$ - 20	$V_{B1,2,3}$ +0.3	V
$V_{B1,2,3}$	High Side Floating Supply Voltage	-0.3	525	V
V_{CC}	Low Side and Logic Supply voltage	-0.3	25	V
V_{IN}	Input Voltage of LIN, HIN	COM -0.3	V_{CC}+0.3	V

Note 1: Pulse Width = 100µs, Single Pulse

© 2020 Infineon Technologies

Recommended Operating Conditions

Symbol	Description	Min	Max	Unit
V+	Positive DC Bus Input Voltage	---	400	V
$V_{S1,2,3}$	High Side Floating Supply Offset Voltage	(Note 2)	400	V
$V_{B1,2,3}$	High Side Floating Supply Voltage	V_S+12	V_S+20	V
V_{CC}	Low Side and Logic Supply Voltage	13.5	16.5	V
V_{IN}	Input Voltage of LIN, HIN, I_{TRIP}, EN, FLT	0	5	V
F_p	PWM Carrier Frequency	---	20	kHz

Note 2: Logic operational for Vs from COM-8V to COM+500V. Logic state held for Vs from COM-8V to COM-V_{BS}.

Static Electrical Characteristics

(V_{CC}-COM) = (V_B-V_S) = 15 V. T_C = 25ºC unless otherwise specified. The V_{IN} and I_{IN} parameters are referenced to COM and are applicable to all six channels. The $V_{CC_{UV}}$ parameters are referenced to COM. The $V_{BS_{UV}}$ parameters are referenced to V_S.

Symbol	Description	Min	Typ	Max	Units	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	500	---	---	V	T_J=25°C, I_{LK}=250µA
I_{LKH}	Leakage Current of High Side FET		12		µA	T_J=25°C, V_{DS}=500V
I_{LKL}	Leakage Current of Low Side FET Plus Gate Drive IC		14		µA	T_J=25°C, V_{DS}=500V
$R_{DS(on)}$	Drain to Source ON Resistance	---	1.3	1.7	Ω	T_J=25°C, V_{CC}=15V, Id = 1.2A
		---	3.2	---	Ω	T_J=150°C, V_{CC}=15V, Id = 1A (Note 3)
V_{SD}	Mosfet Body Diode Forward Voltage	---	0.8	---	V	T_J=25°C, V_{CC}=15V, I_D=1.2A
$V_{IN,th+}$	Positive Going Input Threshold	2.2	---	---	V	
$V_{IN,th-}$	Negative Going Input Threshold	---	---	0.8	V	
V_{CCUV+}, V_{BSUV+}	V_{CC} and V_{BS} Supply Under-Voltage, Positive Going Threshold	8	8.9	9.8	V	
V_{CCUV-}, V_{BSUV-}	V_{CC} and V_{BS} supply Under-Voltage, Negative Going Threshold	6.9	7.7	8.5	V	
V_{CCUVH}, V_{BSUVH}	V_{CC} and V_{BS} Supply Under-Voltage Lock-Out Hysteresis	---	1.2	---	V	
I_{QBS}	Quiescent V_{BS} Supply Current V_{IN}=0V	---	45	60	µA	
$I_{QBS, ON}$	Quiescent V_{BS} Supply Current V_{IN}=4V	---	45	60	µA	
I_{QCC}	Quiescent V_{CC} Supply Current V_{IN}=0V	---	1.8	4	mA	
$I_{QCC, ON}$	Quiescent V_{CC} Supply Current V_{IN}=4V	---	1.9	4	mA	
I_{IN+}	Input Bias Current V_{IN}=4V	---	5.7	18	µA	V_{IN}=3.3V
I_{IN-}	Input Bias Current V_{IN}=0V	---	---	2	µA	V_{IN}=0V
R_{BR}	Internal Bootstrap Equivalent Resistor Value	---	250	---	Ω	T_J=25°C

Note 3: Characterized, not tested at manufacturing

© 2020 Infineon Technologies

Dynamic Electrical Characteristics

(V_{CC}-COM) = (V_B-V_S) = 15 V. T_C = 25ºC unless otherwise specified.

Symbol	Description	Min	Typ	Max	Units	Conditions
T_{ON}	Input to Output Propagation Turn-On Delay Time	---	0.8	1.5	µs	I_D=120mA, V+=30V See Fig.1
T_{OFF}	Input to Output Propagation Turn-Off Delay Time	---	0.9	1.5	µs	
$T_{FIL,IN}$	Input Filter Time (HIN, LIN)	200	300	---	ns	V_{IN}=0 & V_{IN}=3.3V
DT	Deadtime Inserted	---	400	---	ns	V_{IN}=0 & V_{IN}=3.3V without external deadtime
E_{ON}	Turn-on switching energy loss	---	32	---	µJ	V_+=320V, I_D=0.5A, L=40mH, T_C=25°C (Note 4)
E_{OFF}	Turn-off switching energy loss	---	6	---	µJ	
E_{REC}	Recovery energy loss	---	5	---	µJ	
$E_{ON,150}$	Turn-on switching energy loss	---	59	---	µJ	V_+=320V, I_D=0.5A, L=40mH, T_C=150°C (Note 4)
$E_{OFF,150}$	Turn-off switching energy loss	---	7	---	µJ	
$E_{REC,150}$	Recovery energy loss	---	12	---	µJ	

Note 4: Characterized, not tested at manufacturing

Thermal and Mechanical Characteristics

Symbol	Description	Min	Typ	Max	Units	Conditions
$R_{th(J-C)}$	Junction to Case Thermal Resistance	---	6.8	---	°C/W	High Side V-Phase Mosfet (Note 5)

Note 5: Characterized, not tested at manufacturing. Case temperature (T_C) point shown in Figure 2.

Internal NTC – Thermistor Characteristics (IRSM505-055 Only)

Symbol	Description	Min	Typ	Max	Units	Conditions
R_{25}	Resistance	---	47	---	kΩ	T_C=25°C, ±5% tolerance
R_{125}	Resistance	---	1.41	---	kΩ	T_C=125°C
B	B-constant (25-50°C)	---	4050	---	K	±2% tolerance (Note 6)
Temperature Range		-40	---	125	°C	

Note 6: See application notes for usage

© 2020 Infineon Technologies

Qualification Information†

Qualification Level		Industrial††
Moisture Sensitivity Level		MSL3†††
RoHS Compliant		Yes
UL Certified		Yes – File Number E252584
ESD	**Machine Model**	Class B
	Human Body Model	Class 2

† Qualification standards can be found at International Rectifier's web site http://www.infineon.com/


†† Higher qualification ratings may be available should the user have such requirements. Please contact your International Rectifier sales representative for further information.

††† SOP23 package only. Higher MSL ratings may be available for the specific package types listed here. Please contact your International Rectifier sales representative for further information.

© 2020 Infineon Technologies

Module Pin-Out Description

Pin	Name	Description
1	COM	Logic Ground
2	V_{B1}	High Side Floating Supply Voltage 1
3	V_{CC1}	15V Supply 1
4	HIN1	Logic Input for High Side Gate Driver - Phase 1
5	LIN1	Logic Input for Low Side Gate Driver - Phase 1
6	NC	Not Connected
7	V_{B2}	High Side Floating Supply Voltage 2
8	V_{CC2}	15V Supply 2
9	HIN2	Logic Input for High Side Gate Driver - Phase 2
10	LIN2	Logic Input for Low Side Gate Driver - Phase 2
11	V_{TH}	Thermistor Output (IRSM505-055DA)
	NC	Not Connected (IRSM515-055DA)
12	V_{B3}	High Side Floating Supply Voltage 3
13	V_{CC3}	15V Supply 3
14	HIN3	Logic Input for High Side Gate Driver - Phase 3
15	LIN3	Logic Input for Low Side Gate Driver - Phase 3
16	NC	Not Connected
17	V+	DC Bus Voltage Positive
18	U/V_{S1}	Output - Phase 1, High Side Floating Supply Offset 1
19	V_{R1}	Phase 1 Low Side Source
20	V_{R2}	Phase 2 Low Side Source
21	V/V_{S2}	Output - Phase 2, High Side Floating Supply Offset 2
22	V_{R3}	Phase 3 Low Side Source
23	W/V_{S3}	Output - Phase 3, High Side Floating Supply Offset 2



© 2020 Infineon Technologies

Referenced Figures




Figure 1a: Input to Output propagation turn-on delay time.




Figure 1b: Input to Output propagation turn-off delay time.




Figure 1c: Diode Reverse Recovery.

Figure 1: Switching Parameter Definitions




Figure 2: T_C measurement point for $R_{th(j-C)}$

© 2020 Infineon Technologies

Application Notes

A basic application schematic is shown below.




Figure 3: Basic sensor-less motor drive circuit connection. Motor is connected to U, V, W

A complete reference design board for running any permanent magnet motor via sensorless sinusoidal control is available. The board – photo below – features the µIPM™-DIP module and the iMotion™ digital control IC. "Reference design kits are available on www.infineon.com/ipm website"



Figure 4: Reference design board featuring the µIPM™-DIP module and the iMotion™ IRMCF171 digital control IC

 © 2020 Infineon Technologies

Figures 5-7 show the typical current capability for this module at specified conditions. In all tests, the application board – the IRMCS1071-1-D reference board – was placed in a box to prevent cooling from ambient airflow. Figure 5 is derived from using a heat sink that maintains T_C at 125°C. Figures 6-7 represent current capability for the module as used without any heat sink. ΔT_{JA} represents the difference in temperature between the junction of the high-side V-phase Mosfet and the ambient, measured 10cm above and 6cm away from the board. Ambient temperature kept within 28-29°C.




Figure 5: Maximum sinusoidal phase current vs PWM switching frequency with a heat sink.
Space Vector Modulation, V+=320V, T_A=28°C, T_J=150°C, T_C=125°C




Figure 6: Maximum sinusoidal phase current vs PWM switching frequency, no heat sink.
Space Vector Modulation, V+=320V, T_A=28°C, T_J=128°C

 © 2020 Infineon Technologies




Figure 7: Maximum sinusoidal phase current vs PWM switching frequency, no heat sink.
Space Vector Modulation, V+=320V, T_A=28°C, T_J=98°C

The module contains an NTC – connected between COM and the V_{TH} pin – which can be used to monitor the temperature of the module. The NTC is effectively a resistor whose value decreases as the temperature rises. The NTC resistance can be calculated at any temperature as follows:

$R_{TH} = R_{25}e^{\left[B\left(\frac{1}{T_{TH}}-\frac{1}{T_{25}}\right)\right]}$, where $R_{25}$is 47kΩ and B is 4050K

An external resistor network is connected to the NTC, the simplest of which is one resistor pulled up to V_{CC} as shown in Figure 3. The V_{TH} vs NTC temperature, T_{TH} curve for this configuration is shown in Figure 8 below. The min, typical and max curves result from the NTC having a ±5% tolerance on its resistance and ±2% tolerance on the B-parameter.

Figure 9 shows the thermistor temperature, T_{TH} plotted against the high-side V-phase junction temperature, T_J for a module without a heat sink. It is thus advisable to shut down the module when T_{TH} reaches 125°C.

 © 2020 Infineon Technologies




Figure 8: V_{TH} vs T_{TH} with V_{TH} pin pulled up to V_{CC} with a 7.50kΩ (1%, 100ppm) resistor. A 15V, 1% variation in V_{CC} is assumed.





Figure 9: T_{TH} vs T_J for a module without a heat sink. V_{CC}=15.4V, R=7.50kΩ

© 2020 Infineon Technologies


SOP23 Package Outline



Dimensions in mm

© 2020 Infineon Technologies


DIP23A Package Outline



Dimensions in mm

 © 2020 Infineon Technologies


DIP23 Package Outline



Dimensions in mm

© 2020 Infineon Technologies

Top Marking



Marking Code P = Pb Free; Y = Engineering Samples

Date Code YWW format, where Y = least significant digit of the production year , WW = two digits representing the week of the production year

Revision History :

- **Nov 2014 Corrected logic in Figure 1. Added UL certification note.**
- **Jan 2020 Updated the part table on page 1. OPNs are no longer listed in the datasheet. Updated headers, footers and disclaimers on datasheet.**

© 2020 Infineon Technologies

Trademarks
All referenced product or service names and trademarks are the property of their respective owners.

Edition 2019-08-09
Published by
Infineon Technologies AG
81726 Munich, Germany

© 2019 Infineon Technologies AG.
All Rights Reserved.

Do you have a question about this document?
Email: erratum@infineon.com

IMPORTANT NOTICE
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie") .

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (**www.infineon.com**).

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.

WARNINGS
Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.