

12RS333C

Through Hole Radial Lead Shielded Inductors



Applications

Unsuitable Applications	Please be sure to read and comply with these "Precautions for use."
Specific Applications	Industrial Equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual Product.

References

Packaging	Specifications	Standard Packing Quantity
-	Carton Box	250

Mass (typ.)	
1 piece	3.3g

Appearance & Shape



12RS333C



Specifications

L size	10.5mm
W size	10.5mm
T size	10.5mm
Inductance	33 μ H $\pm$ 15%
Max. of DC resistance	0.057 Ω
Operating Temperature Range(Self-temperature rise is not included)	-40°C to 85°C
Class of magnetic shield	Shielded
Brand	Murata Power Solutions
Rated Current	2.7A
Series	1200RS

Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.