BTA16-600BW3G, BTA16-800BW3G,




Description

Designed for high performance full–wave ac control applications where high noise immunity and high commutating di/dt are required.

Features


- Blocking Voltage to 800 V
- On-State Current Rating of 16 A RMS at 80°C
  Uniform Gate Trigger Currents in Three Quadrants
- High Immunity to dV/dt – 1500 V/μs minimum at 125°C
- Minimizes Snubber Networks for Protection
- Industry Standard TO-220AB Package
- High Commutating dI/dt – 4.0 A/ms minimum at 125°C
- Internally Isolated (2500 V_{RMS})
- These Devices are Pb–Free

Pin Out



TO–220AB
CASE 221A
STYLE 4

Functional Diagram



Additional Information

Datasheet | **Resources** | **Samples**

© 2019 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 06/06/19

Maximum Ratings (T_J = 25°C unless otherwise noted)

Rating		Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Note 1) (Gate Open, Sine Wave 50 to 60 Hz, T_J = -40° to 125°C)	BTA16–600BW3G BTA16–800BW3G	V_{DRM}, V_{RRM}	600 800	V
On-State RMS Current (Full Cycle Sine Wave, 60 Hz, T_C = 80°C)		$I_{T\ (RMS)}$	16	A
Peak Non-Repetitive Surge Current (One Full Cycle Sine Wave, 60 Hz, T_C = 25°C)		I_{TSM}	170	A
Circuit Fusing Consideration (t = 8.3 ms)		I^2t	120	A^2sec
Non–Repetitive Surge Peak Off–State Voltage (T_J = 25°C, t = 10ms)		V_{DSM}/V_{RSM}	V_{DSM}/V_{RSM} +100	V
Peak Gate Current (T_J = 125°C, t = 20ms)		I_{GM}	4.0	A
Peak Gate Power (Pulse Width ≤ 1.0 µs, T_C = 80°C)		$P_{G(AV)}$	20	W
Average Gate Power (T_J = 125°C)		$P_{G(AV)}$	1.0	W
Operating Junction Temperature Range		T_J	-40 to +125	°C
Storage Temperature Range		T_{stg}	-40 to +125	°C
RMS Isolation Voltage (t = 300 ms, R.H. ≤ 30%, T_A = 25°C)		V_{iso}	2500	V

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

Thermal Characteristics

Rating		Symbol	Value	Unit
Thermal Resistance,	Junction–to–Case (AC) Junction–to–Ambient	$R_{\theta JC}$ $R_{\theta JA}$	2.5 60	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 10 seconds		T_L	260	°C

© 2019 Littelfuse, Inc.
Specifications are subject to change without notice.

Electrical Characteristics - OFF (T_J = 25°C unless otherwise noted ; Electricals apply in both directions)

Characteristic		Symbol	Min	Typ	Max	Unit
Peak Repetitive Blocking Current ($V_D = V_{DRM} = V_{RRM}$; Gate Open)	T_J = 25°C	I_{DRM}, I_{RRM}	-	-	0.005	mA
	T_J = 125°C		-	-	2.0	

Electrical Characteristics - ON (T_J = 25°C unless otherwise noted; Electricals apply in both directions)

Characteristic		Symbol	Min	Typ	Max	Unit
Forward On-State Voltage (Note 2) (I_{TM} = ±22.5 A Peak)		V_{TM}	–	–	1.55	V
Gate Trigger Current (Continuous dc) (V_D = 12 V, R_L = 30 Ω)	MT2(+), G(+)	I_{GT}	2.5	–	50	mA
	MT2(+), G(–)		2.5	–	50	
	MT2(–), G(–)		2.5	–	50	
Holding Current (V_D = 12 V, Gate Open, Initiating Current = ±150 mA)		I_H	–	–	60	mA
Latching Current (V_D = 12 V, I_G = 50 mA)	MT2(+), G(+)	I_L	–	–	70	mA
	MT2(+), G(–)		–	–	90	
	MT2(–), G(–)		–	–	70	
Gate Trigger Voltage (V_D = 12 V, R_L = 30 Ω)	MT2(+), G(+)	V_{GT}	0.5	–	1.7	V
	MT2(+), G(–)		0.5	–	1.1	
	MT2(–), G(–)		0.5	–	1.1	
Gate Non–Trigger Voltage (T_J = 125°C)	MT2(+), G(+)	t_{gt}	0.2	–	–	V
	MT2(+), G(–)		0.2	–	–	
	MT2(–), G(–)		0.2	–	–	

2. Indicates Pulse Test: Pulse Width ≤ 2.0 ms, Duty Cycle ≤ 2%.


© 2019 Littelfuse, Inc.
Specifications are subject to change without notice.

Dynamic Characteristics


Characteristic	Symbol	Min	Typ	Max	Unit
Rate of Change of Commutating Current, See Figure 10. (Gate Open, T_J = 125°C, No Snubber)	(dI/dt)c	4.0	–	–	A/ms
Critical Rate of Rise of On–State Current (T_J = 125°C, f = 120 Hz, I_G = 2 x I_{GT}, tr ≤100 ns)	dI/dt	–	–	50	A/µs
Critical Rate of Rise of Off-State Voltage (V_D = 0.66 x V_{DRM}, Exponential Waveform, Gate Open, T_J = 125°C)	dV/dt	1500	–	–	V/µs

Voltage Current Characteristic of SCR

Symbol	Parameter
V_{DRM}	Peak Repetitive Forward Off State Voltage
I_{DRM}	Peak Forward Blocking Current
V_{RRM}	Peak Repetitive Reverse Off State Voltage
I_{RRM}	Peak Reverse Blocking Current
V_{TM}	Maximum On State Voltage
I_H	Holding Current



Quadrant Definitions for a Triac



All polarities are referenced to MT1.
With in–phase signals (using standard AC lines) quadrants I and III are used

© 2019 Littelfuse, Inc.
Specifications are subject to change without notice.

Figure 1. RMS Current Derating




Figure 2. On-State Power Dissipation




Figure 3. On–State Characteristics




Figure 4. Thermal Response





Figure 5. Hold Current Variation



© 2019 Littelfuse, Inc.
Specifications are subject to change without notice.

Figure 6. Gate Trigger Current Variation




Figure 7. Gate Trigger Voltage Variation




Figure 8. Critical Rate of Rise of Off-State Voltage (Exponential Waveform)





Figure 9. Simplified Test Circuit to Measure the Critical Rate of Rise of Commutating Current (di/dt)



Note: Component values are for verification of rated (di/dt)c. See AN1048 for additional information


Note: Component values are for verification of rated (di/dt)c. See AN1048 for additional information

© 2019 Littelfuse, Inc.
Specifications are subject to change without notice.

Thyristors

Surface Mount – 600V-800V > BTA16-600BW3G, BTA16-800BW3G,


Dimensions




Dim	Inches		Millimeters	
	Min	Max	Min	Max
A	0.590	0.620	14.99	15.75
B	0.380	0.420	9.65	10.67
C	0.178	0.188	4.52	4.78
D	0.025	0.035	0.64	0.89
F	0.142	0.147	3.61	3.73
G	0.095	0.105	2.41	2.67
H	0.110	0.130	2.79	3.30
J	0.018	0.024	0.46	0.61
K	0.540	0.575	13.72	14.61
L	0.060	0.075	1.52	1.91
N	0.195	0.205	4.95	5.21
Q	0.105	0.115	2.67	2.92
R	0.085	0.095	2.16	2.41
S	0.045	0.060	1.14	1.52
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	---	1.15	---
Z	---	0.080	---	2.04

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

Part Marking System



TO–220AB
CASE 221A
STYLE 12



x =6 or 8
Y =Year
M =Month
A =Assembly Site
XX =Lot Serial Code
G =Pb-Free Package

Pin Assignment	
1	Main Terminal 1
2	Main Terminal 2
3	Gate
4	No Connection

Ordering Information

Device	Package	Shipping
BTA16–600BW3G	TO–220AB (Pb–Free)	500 Units / Rail
BTA16–800BW3G	TO–220AB (Pb–Free)	500 Units / Rail

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications.
Read complete Disclaimer Notice at http://www.littelfuse.com/disclaimer-electronics.

© 2019 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 06/06/19