
# Low-Voltage CMOS Octal Buffer

## With 5 V-Tolerant Inputs and Outputs (3-State, Non-Inverting)


# MC74LCX244



SOIC-20 WB
DW SUFFIX
CASE 751D



TSSOP-20
DT SUFFIX
CASE 948E



QFN20
MN SUFFIX
CASES 485AA
& 485CB


The MC74LCX244 is a high performance, non-inverting octal buffer operating from a 1.65 to 5.5 V supply. High impedance TTL compatible inputs significantly reduce current loading to input drivers while TTL compatible outputs offer improved switching noise performance. A $V_I$ specification of 5.5 V allows MC74LCX244 inputs to be safely driven from 5 V devices. The MC74LCX244 is suitable for memory address driving and all TTL level bus oriented transceiver applications.

Current drive capability is 24 mA at the outputs. The Output Enable ($\overline{OE}$) input, when HIGH, disables the output by placing them in a HIGH Z condition.


### Features

- Designed for 1.65 to 5.5 V $V_{CC}$ Operation
- 5 V Tolerant – Interface Capability With 5 V TTL Logic
- Supports Live Insertion and Withdrawal
- $I_{OFF}$ Specification Guarantees High Impedance When $V_{CC}$ = 0 V
- LVTTL Compatible
- LVCMOS Compatible
- 24 mA Balanced Output Sink and Source Capability
- Near Zero Static Supply Current in All Three Logic States (10 μA) Substantially Reduces System Power Requirements
- Latchup Performance Exceeds 500 mA
- ESD Performance:
  - Human Body Model >2000 V
- –Q Suffix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant


### MARKING DIAGRAMS





SOIC-20 WB




TSSOP-20




QFN20 – 485AA




QFN20 – 485CB

| | | |
|---|---|---|
| A | = | Assembly Location |
| L, WL | = | Wafer Lot |
| Y, YY | = | Year |
| W, WW | = | Work Week |
| G or ▪ | = | Pb-Free Package |

(Note: Microdot may be in either location)

### ORDERING INFORMATION

See detailed ordering and shipping information on page 8 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 8.

© Semiconductor Components Industries, LLC, 2016





**Figure 1. Pinouts: 20-Lead** (Top View)





**Figure 2. Logic Diagram**

**PIN NAMES**

| PINS | FUNCTION |
|---|---|
| n$\overline{OE}$ | Output Enable Inputs |
| 1Dn, 2Dn | Data Inputs |
| 1On, 2On | 3-State Outputs |

**TRUTH TABLE**

| INPUTS | | OUTPUTS |
|---|---|---|
| **1$\overline{OE}$<br>2$\overline{OE}$** | **1Dn<br>2Dn** | **1On, 2On** |
| L | L | L |
| L | H | H |
| H | X | Z |

H = High Voltage Level
L = Low Voltage Level
Z = High Impedance State
X = High or Low Voltage Level and Transitions are Acceptable
For $I_{CC}$ reasons, DO NOT FLOAT Inputs


Share Feedback
Your Opinion Matters

## MAXIMUM RATINGS

| Symbol | Parameter | | Value | Unit |
|---|---|---|---|---|
| $V_{CC}$ | DC Supply Voltage | | −0.5 to +6.5 | V |
| $V_I$ | DC Input Voltage (Note 1) | | −0.5 to +6.5 | V |
| $V_O$ | DC Output Voltage (Note 1) | Active-Mode (High or Low State) | −0.5 to $V_{CC}$ + 0.5 | V |
| | | Tri-State Mode | −0.5 to +6.5 | |
| | | Power-Down Mode ($V_{CC}$ = 0 V) | −0.5 to +6.5 | |
| $I_{IK}$ | DC Input Diode Current | $V_{IN}$ < GND | −50 | mA |
| $I_{OK}$ | DC Output Diode Current | $V_{OUT}$ < GND | −50 | mA |
| $I_O$ | DC Output Source/Sink Current | | ±50 | mA |
| $I_{CC}$ or $I_{GND}$ | DC Supply Current per Supply Pin or Ground Pin | | ±100 | mA |
| $T_{STG}$ | Storage Temperature Range | | −65 to +150 | °C |
| $T_L$ | Lead Temperature, 1 mm from Case for 10 secs | | 260 | °C |
| $T_J$ | Junction Temperature Under Bias | | +150 | °C |
| $\theta_{JA}$ | Thermal Resistance (Note 2) | SOIC-20W | 96 | °C/W |
| | | WQFN20 | 99 | |
| | | QFN20 | 111 | |
| | | TSSOP-20 | 150 | |
| $P_D$ | Power Dissipation in Still Air | SOIC-20W | 1302 | mW |
| | | WQFN20 | 1256 | |
| | | QFN20 | 1127 | |
| | | TSSOP-20 | 833 | |
| MSL | Moisture Sensitivity | SOIC-20W<br>All Other Packages | Level 3<br>Level 1 | – |
| $F_R$ | Flammability Rating | Oxygen Index: 28 to 34 | UL 94 V-0 @ 0.125 in | – |
| $V_{ESD}$ | ESD Withstand Voltage (Note 3) | Human Body Model<br>Charged Device Model | > 2000<br>N/A | V |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. $I_O$ absolute maximum rating must be observed.
2. Measured with minimum pad spacing on an FR4 board, using 76mm-by-114mm, 2-ounce copper trace no air flow per JESD51-7.
3. HBM tested to EIA / JESD22-A114-A. CDM tested to JESD22-C101-A. JEDEC recommends that ESD qualification to EIA/JESD22-A115A (Machine Model) be discontinued.



Share Feedback
Your Opinion Matters

## RECOMMENDED OPERATING CONDITIONS

| Symbol | Parameter | | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| $V_{CC}$ | Supply Voltage | Operating | 1.65 | 3.3 | 5.5 | V |
| | | Data Retention Only | 1.5 | 3.3 | 5.5 | |
| $V_I$ | Digital Input Voltage | | 0 | | 5.5 | V |
| $V_O$ | Output Voltage | Active Mode (High or Low State) | 0 | | $V_{CC}$ | V |
| | | Tri-State Mode | 0 | | 5.5 | |
| | | Power Down Mode ($V_{CC}$ = 0 V) | 0 | | 5.5 | |
| $T_A$ | Operating Free-Air Temperature | | −55 | | +125 | °C |
| $t_r$, $t_f$ | Input Rise or Fall Rate | $V_{CC}$ = 1.65 V to 1.95 V | 0 | | 20 | nS/V |
| | | $V_{CC}$ = 2.3 V to 2.7 V | 0 | | 20 | |
| | | $V_I$ from 0.8 V to 2.0 V, $V_{CC}$ = 3.0 V | 0 | | 10 | |
| | | $V_{CC}$ = 4.5 V to 5.5 V | 0 | | 5 | |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

4. Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or $V_{CC}$). Unused outputs must be left open.

## DC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Conditions | $V_{CC}$ (V) | $T_A$ = −40 °C to +85 °C | | $T_A$ = −55 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | | | Min | Max | Min | Max | |
| $V_{IH}$ | High-Level Input Voltage | | 1.65 to 1.95 | 0.65 x $V_{CC}$ | | 0.65 x $V_{CC}$ | | V |
| | | | 2.3 to 2.7 | 1.7 | | 1.7 | | |
| | | | 2.7 to 3.6 | 2.0 | | 2.0 | | |
| | | | 4.5 to 5.5 | 0.7 x $V_{CC}$ | | 0.7 x $V_{CC}$ | | |
| $V_{IL}$ | Low-Level Input Voltage | | 1.65 to 1.95 | | 0.35 x $V_{CC}$ | | 0.35 x $V_{CC}$ | V |
| | | | 2.3 to 2.7 | | 0.7 | | 0.7 | |
| | | | 2.7 to 3.6 | | 0.8 | | 0.8 | |
| | | | 4.5 to 5.5 | | 0.3 x $V_{CC}$ | | 0.3 x $V_{CC}$ | |
| $V_{OH}$ | High-Level Output Voltage | $V_I$ = $V_{IH}$ or $V_{IL}$ | | | | | | V |
| | | $I_{OH}$ = −100 μA | 1.65 to 5.5 | $V_{CC}$ − 0.1 | | $V_{CC}$ − 0.1 | | |
| | | $I_{OH}$ = −4 mA | 1.65 | 1.2 | | 1.2 | | |
| | | $I_{OH}$ = −8 mA | 2.3 | 1.8 | | 1.8 | | |
| | | $I_{OH}$ = −12 mA | 2.7 | 2.2 | | 2.2 | | |
| | | $I_{OH}$ = −16 mA | 3.0 | 2.4 | | 2.4 | | |
| | | $I_{OH}$ = −24 mA | 3.0 | 2.2 | | 2.2 | | |
| | | $I_{OH}$ = −32 mA | 4.5 | 3.8 | | 3.8 | | |
| $V_{OL}$ | Low-Level Output Voltage | $V_I$ = $V_{IH}$ or $V_{IL}$ | | | | | | V |
| | | $I_{OL}$ = 100 μA | 1.65 to 5.5 | | 0.1 | | 0.1 | |
| | | $I_{OL}$ = 4 mA | 1.65 | | 0.45 | | 0.45 | |
| | | $I_{OL}$ = 8 mA | 2.3 | | 0.6 | | 0.6 | |
| | | $I_{OL}$ = 12 mA | 2.7 | | 0.4 | | 0.4 | |
| | | $I_{OL}$ = 16 mA | 3.0 | | 0.4 | | 0.4 | |
| | | $I_{OL}$ = 24 mA | 3.0 | | 0.55 | | 0.55 | |
| | | $I_{OL}$ = 32 mA | 4.5 | | 0.6 | | 0.6 | |



Share Feedback
Your Opinion Matters

## DC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Conditions | $V_{CC}$ (V) | $T_A$ = −40 °C to +85 °C | | $T_A$ = −55 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | | | Min | Max | Min | Max | |
| $I_I$ | Input Leakage Current | $V_I$ = 0 to 5.5 V | 3.6 | | ±5.0 | | ±5.0 | μA |
| $I_{OZ}$ | 3-State Output Leakage Current | $V_I = V_{IH}$ or $V_{IL}$, $V_O$ = 0 V to 5.5 V | 3.6 | | ±5.0 | | ±5.0 | μA |
| $I_{OFF}$ | Power Off Leakage Current | $V_I$ = 5.5 V or $V_O$ = 5.5 V | 0 | | 10 | | 10 | μA |
| $I_{CC}$ | Quiescent Supply Current | $V_I$ = 5.5 V or GND | 3.6 | | 10 | | 10 | μA |
| $\Delta I_{CC}$ | Increase in $I_{CC}$ per Input | $V_{IH} = V_{CC}$ − 0.6 V | 2.3 to 3.6 | | 500 | | 500 | μA |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. These values of $V_I$ are used to test DC electrical characteristics only.

## AC ELECTRICAL CHARACTERISTICS

| Symbol | Parameter | Test Condition | $V_{CC}$ (V) | $T_A$ = −40 °C to +85 °C | | $T_A$ = −55 °C to +125 °C | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | | | Min | Max | Min | Max | |
| $t_{PLH}$, $t_{PHL}$ | Propagation Delay, D to O | See Figures 3 and 4 | 1.65 to 1.95 | | 10.3 | | 10.3 | ns |
| | | | 2.3 to 2.7 | | 7.8 | | 7.8 | |
| | | | 2.7 | | 7.5 | | 7.5 | |
| | | | 3.0 to 3.6 | | 6.5 | | 6.5 | |
| | | | 4.5 to 5.5 | | 5.9 | | 5.9 | |
| $t_{PZH}$, $t_{PZL}$ | Output Enable Time,OE to $\overline{OE}$ to O | See Figures 3 and 4 | 1.65 to 1.95 | | 13.0 | | 13.0 | ns |
| | | | 2.3 to 2.7 | | 10.0 | | 10.0 | |
| | | | 2.7 | | 9.0 | | 9.0 | |
| | | | 3.0 to 3.6 | | 8.0 | | 8.0 | |
| | | | 4.5 to 5.5 | | 7.3 | | 7.3 | |
| $t_{PHZ}$, $t_{PLZ}$ | Output Disable Time, $\overline{OE}$ to O | See Figures 3 and 4 | 1.65 to 1.95 | | 11.0 | | 11.0 | ns |
| | | | 2.3 to 2.7 | | 8.4 | | 8.4 | |
| | | | 2.7 | | 8.0 | | 8.0 | |
| | | | 3.0 to 3.6 | | 7.0 | | 7.0 | |
| | | | 4.5 to 5.5 | | 6.0 | | 6.0 | |
| $t_{OSHL}$, $t_{OSLH}$ | Output to Output Skew (Note 5) | | 1.65 to 1.95 | | | | | ns |
| | | | 2.3 to 2.7 | | | | | |
| | | | 2.7 | | | | | |
| | | | 3.0 to 3.6 | | 1.0 | | 1.0 | |

6. Skew is defined as the absolute value of the difference between the actual propagation delay for any two separate outputs of the same device. The specification applies to any outputs switching in the same direction, either HIGH-to-LOW ($t_{OSHL}$) or LOW-to-HIGH ($t_{OSLH}$); parameter guaranteed by design.



Share Feedback
Your Opinion Matters

## DYNAMIC SWITCHING CHARACTERISTICS

| Symbol | Characteristic | Condition | $T_A$ = +25 °C | | | Unit |
|---|---|---|---|---|---|---|
| | | | Min | Typ | Max | |
| $V_{OLP}$ | Dynamic LOW Peak Voltage (Note 7) | $V_{CC}$ = 3.3 V, $C_L$ = 50 pF, $V_{IH}$ = 3.3 V, $V_{IL}$ = 0 V<br>$V_{CC}$ = 2.5 V, $C_L$ = 30 pF, $V_{IH}$ = 2.5 V, $V_{IL}$ = 0 V | | 0.8<br>0.6 | | V |
| $V_{OLV}$ | Dynamic LOW Valley Voltage (Note 7) | $V_{CC}$ = 3.3 V, $C_L$ = 50 pF, $V_{IH}$ = 3.3 V, $V_{IL}$ = 0 V<br>$V_{CC}$ = 2.5 V, $C_L$ = 30 pF, $V_{IH}$ = 2.5 V, $V_{IL}$ = 0 V | | −0.8<br>−0.6 | | V |

7. Number of outputs defined as “n”. Measured with “n-1” outputs switching from HIGH-to-LOW or LOW-to-HIGH. The remaining output is measured in the LOW state.


## CAPACITIVE CHARACTERISTICS

| Symbol | Parameter | Condition | Typ | Unit |
|---|---|---|---|---|
| $C_{IN}$ | Input Capacitance | $V_{CC}$ = 3.3 V, $V_I$ = 0 V or $V_{CC}$ | 7 | pF |
| $C_{OUT}$ | Output Capacitance | $V_{CC}$ = 3.3 V, $V_I$ = 0 V or $V_{CC}$ | 8 | pF |
| $C_{PD}$ | Power Dissipation Capacitance (Note 8) | 10 MHz, $V_{CC}$ = 3.3 V, $V_I$ = 0 V or $V_{CC}$ | 25 | pF |

8. $C_{PD}$ is defined as the value of the internal equivalent capacitance which is calculated from the dynamic operating current consumption without load. Average operating current can be obtained by the equation $I_{CC(OPR)} = C_{PD} \bullet V_{CC} \bullet f_{in} + I_{CC}$. $C_{PD}$ is used to determine the no-load dynamic power consumption: $P_D = C_{PD} \bullet V_{CC2} \bullet f_{in} + I_{CC} \bullet V_{CC}$.




Share Feedback
Your Opinion Matters




| Test | Switch Position |
|---|---|
| $t_{PLH}$ / $t_{PHL}$ | Open |
| $t_{PLZ}$ / $t_{PZL}$ | $V_{LOAD}$ |
| $t_{PHZ}$ / $t_{PZH}$ | GND |

$C_L$ includes probe and jig capacitance
$R_T$ is $Z_{OUT}$ of pulse generator (typically 50 Ω)
f = 1 MHz

**Figure 3. Test Circuit**




| $V_{CC}$, V | $R_L$, Ω | $C_L$, pF | $V_{LOAD}$ | $V_{mi}$, V | $V_{mo}$, V | $V_Y$, V |
|---|---|---|---|---|---|---|
| 1.65 to 1.95 | 500 | 30 | 2 x $V_{CC}$ | $V_{CC}$/2 | $V_{CC}$/2 | 0.15 |
| 2.3 to 2.7 | 500 | 30 | 2 x $V_{CC}$ | $V_{CC}$/2 | $V_{CC}$/2 | 0.15 |
| 2.7 | 500 | 50 | 6 V | 1.5 | $V_{CC}$/2 | 0.3 |
| 3.0 to 3.6 | 500 | 50 | 6 V | 1.5 | $V_{CC}$/2 | 0.3 |
| 4.5 to 4.5 | 500 | 50 | 2 x $V_{CC}$ | $V_{CC}$/2 | $V_{CC}$/2 | 0.3 |

**Figure 4. Switching Waveforms**



Share Feedback
Your Opinion Matters

## ORDERING INFORMATION

| Device | Marking | Package | Shipping† |
|---|---|---|---|
| MC74LCX244DWG | LCX244 | SOIC-20 WB | 38 Units / Rail |
| MC74LCX244DWR2G | LCX244 | SOIC-20 WB | 1000 / Tape & Reel |
| MC74LCX244DTG | LCX<br>244 | TSSOP-20 | 75 Units / Rail |
| MC74LCX244DTR2G | LCX<br>244 | TSSOP-20 | 2500 / Tape & Reel |
| MC74LCX244DTR2G-Q* | LCX<br>244 | TSSOP-20 | 2500 / Tape & Reel |
| MC74LCX244MNTWG | LCX<br>244 | QFN20, 2.5x4.5 | 3000 / Tape & Reel<br>(4 mm pitch carrier tape) |
| MC74LCX244MN2TWG | 244 | QFN20, 2.5x3.5<br>(Pb-Free) | 3000 / Tape & Reel<br>(4 mm pitch carrier tape) |

**DISCONTINUED** (Note 9)

| | | | |
|---|---|---|---|
| NLV74LCX244DTR2G* | | TSSOP-20<br>(Pb-Free) | 2500 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

*–Q Suffx for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable

9. **DISCONTINUED:** These devices are not recommended for new design. Please contact your **onsemi** representative for information. The most current information on these devices may be available on www.onsemi.com.



Share Feedback
Your Opinion Matters

## REVISION HISTORY

| Revision | Description of Changes | Date |
|---|---|---|
| 23 | Edit to the ordering information table | 6/3/2026 |

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.




Share Feedback
Your Opinion Matters

# MECHANICAL CASE OUTLINE
## PACKAGE DIMENSIONS


ON Semiconductor®

**QFN20, 2.5x4.5 MM**
CASE 485AA−01
ISSUE B

DATE 30 APR 2010





**SCALE 2:1**




NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSIONS b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

| | MILLIMETERS | |
|---|---|---|
| DIM | MIN | MAX |
| A | 0.80 | 1.00 |
| A1 | 0.00 | 0.05 |
| A3 | 0.20 REF | |
| b | 0.20 | 0.30 |
| D | 2.50 BSC | |
| D2 | 0.85 | 1.15 |
| E | 4.50 BSC | |
| E2 | 2.85 | 3.15 |
| e | 0.50 BSC | |
| K | 0.20 | --- |
| L | 0.35 | 0.45 |

### GENERIC MARKING DIAGRAM*




XXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

| | | |
|---|---|---|
| **DOCUMENT NUMBER:** | **98AON12653D** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. |
| **DESCRIPTION:** | **QFN20. 2.5X4.5 MM** | **PAGE 1 OF 1** |

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.


© Semiconductor Components Industries, LLC, 2019

**QFN20, 2.5x3.5, 0.4P**
CASE 485CB
ISSUE O


DATE 25 OCT 2011




**SCALE 2:1**





**TOP VIEW**





**DETAIL A**
**ALTERNATE TERMINAL CONSTRUCTIONS**




**DETAIL B**
**ALTERNATE CONSTRUCTIONS**




**SIDE VIEW**




**BOTTOM VIEW**

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSIONS b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

| | MILLIMETERS | |
|---|---|---|
| DIM | MIN | MAX |
| A | 0.80 | 1.00 |
| A1 | 0.00 | 0.05 |
| A3 | 0.20 REF | |
| b | 0.15 | 0.25 |
| D | 2.50 BSC | |
| D2 | 0.90 | 1.10 |
| E | 3.50 BSC | |
| E2 | 2.00 | 2.20 |
| e | 0.40 BSC | |
| L | 0.35 | 0.45 |
| L1 | --- | 0.15 |

## GENERIC MARKING DIAGRAM*





XXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

## SOLDERING FOOTPRINT*




DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


| | | | |
|---|---|---|---|
| **DOCUMENT NUMBER:** | **98AON65196E** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. | |
| **DESCRIPTION:** | **QFN20, 2.5X3.5, 0.4P** | | **PAGE 1 OF 1** |

**onsemi** and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.


© Semiconductor Components Industries, LLC, 2011

**SOIC−20 WB**
CASE 751D−05
ISSUE H

DATE 22 APR 2015




**SCALE 1:1**




NOTES:
1. DIMENSIONS ARE IN MILLIMETERS.
2. INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 1994.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 PER SIDE.
5. DIMENSION B DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.13 TOTAL IN EXCESS OF B DIMENSION AT MAXIMUM MATERIAL CONDITION.

| | MILLIMETERS | |
|---|---|---|
| DIM | MIN | MAX |
| A | 2.35 | 2.65 |
| A1 | 0.10 | 0.25 |
| b | 0.35 | 0.49 |
| c | 0.23 | 0.32 |
| D | 12.65 | 12.95 |
| E | 7.40 | 7.60 |
| e | 1.27 BSC | |
| H | 10.05 | 10.55 |
| h | 0.25 | 0.75 |
| L | 0.50 | 0.90 |
| θ | 0° | 7° |


## RECOMMENDED SOLDERING FOOTPRINT*




DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## GENERIC MARKING DIAGRAM*




XXXXX = Specific Device Code
A = Assembly Location
WL = Wafer Lot
YY = Year
WW = Work Week
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

| | | |
|---|---|---|
| **DOCUMENT NUMBER:** | **98ASB42343B** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| **DESCRIPTION:** | **SOIC−20 WB** | **PAGE 1 OF 1** |

**onsemi** and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

**TECHNICAL PUBLICATIONS**:
**Technical Library:** www.onsemi.com/design/resources/technical−documentation
**onsemi Website:** www.onsemi.com

**ONLINE SUPPORT**: www.onsemi.com/support
**For additional information, please contact your local Sales Representative at** www.onsemi.com/support/sales