MOSFET – Power, N-Channel, Shielded Gate

40 V, 2.75 mΩ, 104 A

NTTFS2D8N04HL

General Description

This N-Channel MOSFET is produced using **onsemi**'s advanced MOSFET process that incorporates Shielded Gate technology. This process has been optimized to minimize on-state resistance and yet maintain superior switching performance with best in class soft body diode.


Features

- Shielded Gate MOSFET Technology
- Max $r_{DS(on)}$ = 2.75 mΩ at V_{GS} = 10 V, I_D = 16 A
- Max $r_{DS(on)}$ = 4.3 mΩ at V_{GS} = 4.5 V, I_D = 13 A
- Lowers Switching Noise/EMI
- MSL1 Robust Package Design
- 100% UIL Tested
- RoHS Compliant


Applications

- Primary DC-DC MOSFET
- Synchronous Rectifier in DC-DC and AC-DC
- Motor Drive

ELECTRICAL CONNECTION



N-Channel MOSFET



WDFN8
(3.3x3.3, 0.65 P)
CASE 511DY

MARKING DIAGRAM



04HL	= Device Code
A	= Assembly Location
Y	= Year Code
WW	= Work Week Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2019

MOSFET MAXIMUM RATINGS (T_A = 25 °C unless otherwise noted)

Symbol	Parameter				Ratings	Unit
V_{DS}	Drain to Source Voltage				40	V
V_{GS}	Gate to Source Voltage				±20	V
I_D	Drain Current	− Continuous	T_C = 25 °C	(Note 5)	104	A
		− Continuous	T_C = 100 °C	(Note 5)	66	
		− Continuous	T_A = 25 °C	(Note 1a)	24	
		− Pulsed		(Note 4)	216	
E_{AS}	Single Pulse Avalanche Energy			(Note 3)	109	mJ
P_D	Power Dissipation		T_C = 25 °C		63	W
	Power Dissipation		T_A = 25 °C	(Note 1a)	3.2	
T_J, T_{STG}	Operating and Storage Junction Temperature Range				−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Symbol	Parameter		Ratings	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case		2	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1a)	39	

PACKAGE MARKING AND ORDERING INFORMATION

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
04HL	NTTFS2D8N04HL	WDFN8 (3.3x3.3)	7”	12 mm	1500 Units

ELECTRICAL CHARACTERISTICS (T_J = 25 °C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = 250 μA, V_{GS} = 0 V	40			V
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Breakdown Voltage Temperature Coefficient	I_D = 250 μA, referenced to 25 °C		22		mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 32 V, V_{GS} = 0 V			10	μA
I_{GSS}	Gate to Source Leakage Current	V_{GS} = +20 V, V_{DS} = 0 V			100	nA
ON CHARACTERISTICS						
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 80 μA	1.2	1.6	2.0	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = 80 μA, referenced to 25 °C		−4.9		mV/°C
$r_{DS(on)}$	Static Drain to Source On Resistance	V_{GS} = 10 V, I_D = 16 A		2.4	2.75	mΩ
		V_{GS} = 4.5 V, I_D = 13 A		3.4	4.3	
DYNAMIC CHARACTERISTICS						
C_{ISS}	Input Capacitance	V_{DS} = 20 V, V_{GS} = 0 V, f = 1 MHz		1960		pF
C_{OSS}	Output Capacitance			460		
C_{RSS}	Reverse Transfer Capacitance			30		
R_G	Gate Resistance			0.8		Ω

Share Feedback
Your Opinion Matters


ELECTRICAL CHARACTERISTICS (T_J = 25 °C unless otherwise noted) (continued)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
SWITCHING CHARACTERISTICS						
$t_{d(ON)}$	Turn-On Delay Time	V_{DD} = 20 V, I_D = 16 A, V_{GS} = 10 V, R_{GEN} = 2.5 Ω		7.5		ns
$t_{rd(ON)}$	Rise Time			16.6		
$t_{d(OFF)}$	Turn-Off Delay Time			30		
t_f	Fall Time			2.8		
Q_g	Total Gate Charge	V_{GS} = 0 V to 10 V; V_{DD} = 20 V, I_D = 16 A		32		nC
Q_g	Total Gate Charge	V_{GS} = 0 V to 4.5 V; V_{DD} = 20 V, I_D = 16 A		15		
Q_{gs}	Gate to Source Charge	V_{DD} = 20 V, I_D = 16 A		5.6		
Q_{gd}	Gate to Drain “Miller” Charge	V_{DD} = 20 V, I_D = 16 A		3.4		
DRAIN-SOURCE DIODE CHARACTERISTICS						
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 16 A (Note 2)		0.78	1.2	V
		V_{GS} = 0 V, I_S = 16 A (Note 2)		0.63	1.3	
t_{rr}	Reverse Recovery Time	I_F = 16 A, di/dt = 100 A/μs		32.2		ns
Q_{rr}	Reverse Recovery Charge			27.4		nC


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

NOTES:

1. $R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 × 1.5 in. board of FR-4 material. $R_{\theta CA}$ is determined by the user’s board design.



a) 53 °C/W when mounted on a 1 in^2 pad of 2 oz copper.



b) 125 °C/W when mounted on a minimum pad of 2 oz copper.

2. Pulse Test: Pulse Width < 300 μs, Duty cycle < 2.0%.
3. E_{AS} of 109 mJ is based on starting T_J = 25 °C; L = 0.3 mH, I_{AS} = 27 A, V_{DD} = 32 V, V_{GS} = 10 V. 100% test at L = 0.3 mH, I_{AS} = 27 A.
4. Pulsed I_D please refer to SOA graph for more details.
5. Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro-mechanical application board design.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area




Figure 12. Maximum Drain Current vs. Time in Avalanche

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 13. Transient Thermal Impedance

Share Feedback
Your Opinion Matters

REVISION HISTORY


Revision	Description of Changes	Date
2	Rebranded the Data Sheet to **onsemi** format.	10/17/2025

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.


Share Feedback
Your Opinion Matters

WDFN8 3.3x3.3, 0.65P
CASE 511DY
ISSUE A


DATE 21 AUG 2018



TOP VIEW




SIDE VIEW




BOTTOM VIEW

NOTES:
1. CONTROLLING DIMENSION: MILLIMETERS
2. DIMENSIONS D1 & E1 DO NOT INCLUDE MOLD FLASH PROTRUSIONS NOR GATE BURRS.



END VIEW



RECOMMENDED LAND PATTERN

DIM	MILLIMETERS		
	MIN	NOM	MAX
A	0.70	0.75	0.80
A1	0.00	-	0.05
b	0.23	0.33	0.43
c	0.15	0.20	0.25
D	3.20	3.30	3.40
D1	2.95	3.13	3.30
D2	1.98	2.20	2.40
E	3.20	3.30	3.40
E1	2.80	3.00	3.15
E2	1.40	1.60	1.80
E3	0.15	0.25	0.40
e	0.65 BSC		
G	0.30	0.43	0.55
G1	0.25	0.35	0.45
K	0.55	0.75	0.95
L	0.35	0.52	0.65
L1	0.06	0.15	0.30
M	1.35	1.50	1.60
Θ	0	-	12

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year Code
WW = Work Week Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON90827G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**WDFN8 3.3x3.3, 0.65P**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales