

## Extension Cord Y Splitter, NEMA 5-15P to 2x NEMA 5-15R - 13A, 120V, 16 AWG, 18-in. (45.72 cm), Black

MODEL NUMBER: **P024-18N-13A-2R**



Extension cord splitter allows 2 devices with NEMA 5-15P plugs to share one AC power input cord and one NEMA 5-15R outlet.

### Features

**Y-Style Power Cord Splitter Connects 2 Devices with NEMA 5-15P Plugs to One AC Outlet** This extension cable splitter allows two devices with NEMA 5-15P plugs to share one AC input cord and one NEMA 5-15R outlet. By connecting two devices to one outlet, the extension cord splitter frees up space in a PDU, UPS system or surge protector and helps reduce cable clutter. You can also free up valuable PDU space by connecting bulky power adapters to this splitter, preventing the adapters from blocking adjacent outlets.

**Dual Cable Powers a Wide Variety of Essential Electronics** With this splitter, a single NEMA 5-15R outlet can power two devices, such as computers, monitors, printers, instrument amplifiers and other equipment compatible with a 5-15P connector. Ideal for areas where AC outlets are limited, such as rack cabinets, this dual power cable is compatible with most power and extension cords.

### Highlights

- Connects 2 devices to one AC outlet to save space and reduce cable clutter
- Recommended for powering dual computers, monitors or other compatible peripherals
- Ideal replacement for worn-out or missing extension cord Y splitter
- NEMA 5-15P plug connects to AC power; 5-15R ends connect to devices' power cords

### Applications

- Connect 2 devices like computers, monitors, scanners and printers to one power outlet up to 1.5 ft. away in your home office, work space or dorm room
- Cut cable clutter by powering both monitors in a dual-monitor display mount with a single cord
- Save space in a 0U vertical rack-mount PDU by plugging two rack devices into one outlet

### Package Includes

- P024-18N-13A-2R Extension Cord Y Splitter, 5-15P to 2x 5-15R, 1.5 ft., Black

## Specifications

| OVERVIEW                    |                                                   |
|-----------------------------|---------------------------------------------------|
| UPC Code                    | 037332180636                                      |
| Product Type                | Splitter                                          |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Server; UPS; PDU |
| Country/Region              | North America                                     |
| INPUT                       |                                                   |
| Maximum Input Amps          | 13                                                |
| Voltage Compatibility (VAC) | 125                                               |



Powering Business Worldwide

TRIPP LITE  
SERIES

| CONNECTIONS                        |                             |
|------------------------------------|-----------------------------|
| Side A - Connector 1               | NEMA 5-15P                  |
| Side B - Connector 1               | (2) NEMA 5-15R              |
| Connector Style                    | Straight                    |
| PHYSICAL                           |                             |
| Color                              | Black                       |
| Plug Color                         | Black                       |
| Cable Jacket Color                 | Black                       |
| Connector Color                    | Black                       |
| Cable Jacket Material              | PVC                         |
| Cable Jacket Rating                | VW-1                        |
| Power Cord Jacket Type             | SJT                         |
| Cable Outer Diameter (OD)          | 8.30mm                      |
| Number of Conductors               | 3                           |
| Wire Gauge (AWG)                   | 16                          |
| Wire Gauge (OD - mm <sup>2</sup> ) | 1.31                        |
| Power Cord Color                   | Black                       |
| Cable Length (ft.)                 | 1.5                         |
| Cable Length (m)                   | 0.46                        |
| Shipping Dimensions (hwd / in.)    | 10.00 x 7.10 x 0.10         |
| Shipping Dimensions (hwd / cm)     | 25.40 x 18.03 x 0.25        |
| Shipping Weight (lbs.)             | 0.41                        |
| Shipping Weight (kg)               | 0.19                        |
| ENVIRONMENTAL                      |                             |
| Operating Temperature Range        | -4° to 140°F (-20° to 60°C) |
| Storage Temperature Range          | -4° to 140°F (-20° to 60°C) |
| Operating Humidity Range           | 10% to 65% RH               |
| Storage Humidity Range             | 10% to 65% RH               |
| FEATURES & SPECIFICATIONS          |                             |
| Antibacterial                      | No                          |
| Angled Plug                        | No                          |
| High Voltage                       | No                          |
| Locking Plug                       | No                          |

|                                     |                           |
|-------------------------------------|---------------------------|
| Coiled Power Cord                   | No                        |
| Locking Power Cord                  | No                        |
| Locking                             | No                        |
| <b>STANDARDS &amp; COMPLIANCE</b>   |                           |
| Product Certifications              | cUL Listed; UL Listed     |
| Product Compliance                  | RoHS                      |
| <b>WARRANTY &amp; SUPPORT</b>       |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2026 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.