Product Line

- Single Pair Ethernet
- ZConnect
- Ceres
- X-Lok
- M Series
- FLOS & FLOS+
- Power
- RBL
- HS-Lok
- NMEA 2000
- Heavy Duty Shielded
- RJ
- USB
- SSL
- HDMI
  - HDMI
  - Accessory
- DVI
- RF
- Cable Joiner
- Cable Gland
- Pressure Relief Vent
- LED Light Guide
- D-Sub







HP-19AFMM-SL7A01

- Operating Temperature: -20°C ~ +80°C
- Transmission Speed: N/A
- Shielded: Metal, Shielded
- Jacket Material: PVC
- Certificate: N/A

You must login first for view the price

Quantity − 1 +

Add to Cart | Inquiry

Can't find? Customize your part

Mating Pair & Accessories

Connector Type

Search



HDMI, Metal, 0.5A, 19...

− 0 +

Add to Cart | Inquiry

Specifications | Download / CAD

Nominal Current **0.5A**	Connector Type **Overmolded**
Shielded **Metal, Shielded**	No. of Contacts **19**
Connector Gender **Plug**	Backshell **Straight**
Mating Style **Screw Thread**	IP Rating **IPX7**
Assembly Style **N/A**	

More Options

People Also Bought