

15,000 Watt Transient Voltage Suppressor

M15KP22A – MXL15KP280CA(e3)



Product Overview

The M15KP22A – MXL15KP280CA series of axial lead 15,000 watt transient voltage suppressors provide a selection of standoff voltages (V_{WM}) from 22 to 280 V. These high-reliability devices are available in either unidirectional or bidirectional versions. RoHS compliant versions are available. These are available with a variety of upscreening options for enhanced reliability in reference to MIL-PRF-19500. They can protect against the secondary effects of lightning per IEC61000-4-5 and against voltage pulses from inductive switching environments and induced by RFI. Since their response time is virtually instantaneous, they can also be used in protection from ESD and EFT per IEC61000-4-2 and IEC61000-4-4.

Features

- Available in both unidirectional and bidirectional configurations
- 3σ lot norm screening performed on standby current I_D for all M prefix devices
- 100% surge tested devices
- Suppress transients up to 15,000 watts at 10/1000 μ s (see [Figure 4-1](#))
- Enhanced reliability screening in reference to MIL-PRF-19500 are available. Refer to [High Reliability Non-Hermetic Product Portfolio](#) for more details on the screening options. (See [part nomenclature](#) for all options.)
- High reliability controlled devices have wafer fabrication and assembly lot traceability for all M prefix devices.
- Moisture classification is level 1 with no dry pack required per IPC/JEDEC J-STD-020F for all M prefix devices.
- RoHS compliant versions are available.

Applications/Benefits

- Available in working standoff voltage (V_{WM}) range 22 to 280 volts
- Economical axial-lead plastic encapsulated TVS series for thru-hole mounting
- Protects sensitive components such as IC's, CMOS, Bipolar, BiCMOS, ECL, DTL, T2L, etc
- Protection from switching transients & induced RFI
- Compliant to IEC 61000-4-2 and IEC 61000-4-4 for ESD and EFT protection respectively
- Secondary lightning protection per IEC61000-4-5 with 42 ohms source impedance:
 - Class 1, 2, 3, 4: M15KP22A to MXL15KP280CA
 - Class 5: M15KP22A to MXL15KP280CA (short distance)
 - Class 5: M15KP22A to MXL15KP110CA (long distance)
- Secondary lightning protection per IEC61000-4-5 with 12 ohms source impedance:
 - Class 1 and 2: M15KP22A to MXL15KP280CA
 - Class 3: M15KP22A to MXL15KP240CA
 - Class 4: M15KP22A to MXL15KP120CA
- Secondary lightning protection per IEC61000-4-5 with 2 ohms source impedance:
 - Class 2: M15KP22A to MXL15KP220CA
 - Class 3: M15KP22A to MXL15KP110CA
 - Class 4: M15KP22A to MXL15KP54CA

Figure 1. DO-204AR Package



Table of Contents

Product Overview.....1

1. Maximum Ratings.....3

 1.1. Mechanical Packaging.....3

2. Part Nomenclature.....4

 2.1. Symbols and Definitions.....4

3. Electrical Characteristics.....5

4. Graphs.....7

5. Package Dimensions.....9

6. Revision History.....10

Microchip Information.....11

 The Microchip Website.....11

 Product Change Notification Service.....11

 Customer Support.....11

 Microchip Devices Code Protection Feature.....11

 Legal Notice.....11

 Trademarks.....12

 Quality Management System.....13

 Worldwide Sales and Service.....14

1. Maximum Ratings

Table 1-1. Maximum Ratings at 25 °C Unless Otherwise Noted

Parameters/Test Conditions	Symbol	Value	Unit
Junction and storage temperature	T_J and T_{STG}	–65 to +150	°C
Thermal resistance, junction to lead ¹	$R_{\theta JL}$	20	°C/W
Thermal resistance, junction to ambient ²	$R_{\theta JA}$	80	°C/W
Peak pulse power	At $T_L = +25\text{ °C}$ ³ P_{PP}	15,000	W
Average power dissipation	At $T_L = +30\text{ °C}$ ¹ At $T_A = +25\text{ °C}$ ² P_D	6 1.56	W
$t_{clamping}$ (0 volts to $V_{(BR)}$ min, theoretical)	Unidirectional Bidirectional —	<100 <5	ps ns
Surge peak forward current ⁴	I_{FSM}	200	A
Solder temperature at 10 seconds	—	260	°C

Notes:


1. At 0.375 inch (10 mm) from body
2. Mounted on FR4 PC board with 4 mm² copper pads (1 oz) and track width 1 mm, length 25 mm.
3. At 10/1000 μ s with repetition rate of 0.01% or less (see [Figure 4-1](#))
4. At 8.3 ms half-sine wave for unidirectional devices only

1.1 Mechanical Packaging

- Case: Void-free transfer molded thermosetting epoxy body meeting UL94V-0
- Terminals: Tin-lead or RoHS compliant annealed matte-tin plating. Solderable per MIL-STD-750, method 2026.
- Marking: Reliability level, part number, date code
- Polarity: Cathode indicated by band. No cathode band on bidirectional devices.
- Tape and reel option: Standard per EIA-296 (add “TR” suffix to part number). Consult factory for quantities.
- Weight: Approximately 1.4 grams
- See [Package Dimensions](#)

2. Part Nomenclature

Figure 2-1. Part Nomenclature



2.1 Symbols and Definitions

Table 2-1. Symbols and Definitions

Symbol	Definition
$\alpha_{V(BR)}$	Temperature coefficient of breakdown voltage: The change in breakdown voltage divided by the change in temperature that caused it expressed in %/°C or mV/°C.
C_T	Total capacitance: The total small signal capacitance between the diode terminals of a complete device.
$I_{(BR)}$	Breakdown current: The current used for measuring breakdown voltage $V_{(BR)}$.
I_D	Standby current: The current through the device at working standoff voltage.
I_{FSM}	Surge peak forward current: The forward current including all nonrepetitive transient currents but excluding all repetitive transients (ref JEDEC282-B).
I_{PP}	Peak impulse current: The peak current during an impulse.
P_{PP}	Peak pulse power: The peak power that can be applied for a specific pulse width and waveform. The product of I_{PP} and V_C .
$V_{(BR)}$	Breakdown voltage: The voltage across the device at a specified current $I_{(BR)}$ in the breakdown region.
V_C	Clamping voltage: The voltage across the device in a region of low differential resistance during the application of an impulse current (I_{PP}) for a specified waveform.
V_{WM}	Working standoff voltage: The maximum-rated value of DC or repetitive peak positive cathode-to-anode voltage that may be continuously applied over the standard operating temperature.

3. Electrical Characteristics

Table 3-1. Electrical Characteristics at 25 °C

Part Number	Working Standoff Voltage V_{WM}	Minimum Breakdown Voltage $V_{(BR)}$ at $I_{(BR)}$		Maximum Clamping Voltage V_C at I_{PP}	Maximum Standby Current I_D at V_{WM}	Maximum Peak Pulse Current at 10/1000 μs I_{PP} (Figure 4-2)	Maximum Temperature Coefficient of $V_{(BR)}$ $\alpha_{V(BR)}$
	V	V	mA	V	μA	A	mV/°C
M15KP22(C)A	22	24.4	10	37.1	500	404	24
M15KP24(C)A	24	26.7	5	40.7	150	369	27
M15KP26(C)A	26	28.9	5	44.0	50	341	29
M15KP28(C)A	28	31.1	5	47.5	25	316	31
M15KP30(C)A	30	33.3	5	50.7	15	296	34
M15KP33(C)A	33	36.7	5	54.8	10	274	38
M15KP36(C)A	36	40.0	5	59.7	10	251	41
M15KP40(C)A	40	44.4	5	65.8	10	228	46
M15KP43(C)A	43	47.8	5	69.7	10	215	50
M15KP45(C)A	45	50.0	5	73.0	10	205	52
M15KP48(C)A	48	53.3	5	77.7	10	193	56
M15KP51(C)A	51	56.7	5	82.8	10	181	60
M15KP54(C)A	54	60.0	5	87.5	10	171	63
M15KP58(C)A	58	64.4	5	94.0	10	160	68
M15KP60(C)A	60	66.7	5	97.3	10	154	71
M15KP64(C)A	64	71.1	5	104	10	144	76
M15KP70(C)A	70	77.8	5	114	10	132	83
M15KP75(C)A	75	83.3	5	122	10	123	89
M15KP78(C)A	78	86.7	5	126	10	119	93
M15KP85(C)A	85	94.4	5	137	10	109	102
M15KP90(C)A	90	100	5	146	10	103	109
M15KP100(C)A	100	111	5	162	10	93	121
M15KP110(C)A	110	122	5	178	10	84	133
M15KP120(C)A	120	133	5	193	10	78	145
M15KP130(C)A	130	144	5	209	10	72	157
M15KP150(C)A	150	167	5	243	10	62	183
M15KP160(C)A	160	178	5	259	10	58	195
M15KP170(C)A	170	189	5	275	10	55	207
M15KP180(C)A	180	200	5	291	10	52	219
M15KP200(C)A	200	222	5	322	10	47	243
M15KP220(C)A	220	245	5	356	10	42	269
M15KP240(C)A	240	267	5	388	10	39	293
M15KP260(C)A	260	289	5	419	10	36	317
M15KP280(C)A	280	311	5	452	10	33	342

Notes:

1. Normal selection criteria for TVS devices is by working standoff voltage (V_{WM}) and should be equal or greater than DC or continuous peak operating voltage.
2. TVS devices are tested to maximum peak pulse current (I_{PP}) with clamping voltage monitored. This surge capability is one of the most significant electrical characteristics of the device and should be considered as part of customer quality inspections.

4. Graphs

Figure 4-1. Peak Pulse Power Rating Curve




Figure 4-2. Pulse Waveform for 10/1000 μ s Exponential Surge







Figure 4-3. Typical Junction Capacitance

For bidirectional construction, capacitance will be half that shown.

Figure 4-4. Derating Curve

5. Package Dimensions

Figure 5-1. Package Dimensions



Dim.	Dimensions			
	Inch		Millimeters	
	Min.	Max.	Min.	Max.
LL	1.100	1.500	27.95	38.1
BL	0.365	0.375	9.27	9.52
BD	0.240	0.250	6.1	6.35
LD	0.048	0.052	1.22	1.32

6. Revision History

The revision history describes the changes that were implemented in the document. The changes are listed by revision, starting with the most current publication.

Revision	Date	Description
B	02/2024	- Changed RF radiation to RFI in Product Overview. - Changed the average power dissipation at T_L to +30 °C in Table 1-1.
A	01/2024	Initial revision.

Microchip Information

The Microchip Website

Microchip provides online support via our website at www.microchip.com/. This website is used to make files and information easily available to customers. Some of the content available includes:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Product Change Notification Service

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Embedded Solutions Engineer (ESE)
- Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.

Technical support is available through the website at: www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is "unbreakable". Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure

that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, TimeCesium, TimeHub, TimePictra, TimeProvider, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, Clockstudio, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, EyeOpen, GridTime, IdealBridge, IGaT, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, IntelliMOS, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, MarginLink, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, mSiC, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICKit, PICtail, Power MOS IV, Power MOS 7, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, Trusted Time, TSHARC, Turing, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2024, Microchip Technology Incorporated and its subsidiaries. All Rights Reserved.

ISBN: 978-1-6683-3981-7

Quality Management System

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.

Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: www.microchip.com/support Web Address: www.microchip.com	Australia - Sydney Tel: 61-2-9868-6733 China - Beijing Tel: 86-10-8569-7000 China - Chengdu Tel: 86-28-8665-5511 China - Chongqing Tel: 86-23-8980-9588 China - Dongguan Tel: 86-769-8702-9880 China - Guangzhou Tel: 86-20-8755-8029 China - Hangzhou Tel: 86-571-8792-8115 China - Hong Kong SAR Tel: 852-2943-5100 China - Nanjing Tel: 86-25-8473-2460 China - Qingdao Tel: 86-532-8502-7355 China - Shanghai Tel: 86-21-3326-8000 China - Shenyang Tel: 86-24-2334-2829 China - Shenzhen Tel: 86-755-8864-2200 China - Suzhou Tel: 86-186-6233-1526 China - Wuhan Tel: 86-27-5980-5300 China - Xian Tel: 86-29-8833-7252 China - Xiamen Tel: 86-592-2388138 China - Zhuhai Tel: 86-756-3210040	India - Bangalore Tel: 91-80-3090-4444 India - New Delhi Tel: 91-11-4160-8631 India - Pune Tel: 91-20-4121-0141 Japan - Osaka Tel: 81-6-6152-7160 Japan - Tokyo Tel: 81-3-6880-3770 Korea - Daegu Tel: 82-53-744-4301 Korea - Seoul Tel: 82-2-554-7200 Malaysia - Kuala Lumpur Tel: 60-3-7651-7906 Malaysia - Penang Tel: 60-4-227-8870 Philippines - Manila Tel: 63-2-634-9065 Singapore Tel: 65-6334-8870 Taiwan - Hsin Chu Tel: 886-3-577-8366 Taiwan - Kaohsiung Tel: 886-7-213-7830 Taiwan - Taipei Tel: 886-2-2508-8600 Thailand - Bangkok Tel: 66-2-694-1351 Vietnam - Ho Chi Minh Tel: 84-28-5448-2100	Austria - Wels Tel: 43-7242-2244-39 Fax: 43-7242-2244-393 Denmark - Copenhagen Tel: 45-4485-5910 Fax: 45-4485-2829 Finland - Espoo Tel: 358-9-4520-820 France - Paris Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79 Germany - Garching Tel: 49-8931-9700 Germany - Haan Tel: 49-2129-3766400 Germany - Heilbronn Tel: 49-7131-72400 Germany - Karlsruhe Tel: 49-721-625370 Germany - Munich Tel: 49-89-627-144-0 Fax: 49-89-627-144-44 Germany - Rosenheim Tel: 49-8031-354-560 Israel - Ra'anana Tel: 972-9-744-7705 Italy - Milan Tel: 39-0331-742611 Fax: 39-0331-466781 Italy - Padova Tel: 39-049-7625286 Netherlands - Drunen Tel: 31-416-690399 Fax: 31-416-690340 Norway - Trondheim Tel: 47-72884388 Poland - Warsaw Tel: 48-22-3325737 Romania - Bucharest Tel: 40-21-407-87-50 Spain - Madrid Tel: 34-91-708-08-90 Fax: 34-91-708-08-91 Sweden - Gothenberg Tel: 46-31-704-60-40 Sweden - Stockholm Tel: 46-8-5090-4654 UK - Wokingham Tel: 44-118-921-5800 Fax: 44-118-921-5820