

N-Channel Super Junction Power MOSFET III

General Description

The series of devices use advanced trench gate super junction technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. This super junction MOSFET fits the industry's AC-DC SMPS requirements for PFC, AC/DC power conversion, and industrial power applications.


Features

- New technology for high voltage device
- Low on-resistance and low conduction losses
- Small package
- Ultra Low Gate Charge cause lower driving requirements
- 100% Avalanche Tested
- ROHS compliant

Application

- Power factor correction (PFC)
- Switched mode power supplies(SMPS)
- Uninterruptible Power Supply (UPS)

V_{DS}	800	V
$R_{DS(ON)MAX}$	900	mΩ
I_D	6	A



Schematic diagram

Package Marking And Ordering Information

Device	Device Package	Marking
RM6N800LD	TO-252	6N800
RM6N800IP	TO-251	6N800



TO-252



TO-251

Table 1. Absolute Maximum Ratings ($T_C=25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Drain-Source Voltage ($V_{GS}=0V$)	V_{DS}	800	V
Gate-Source Voltage ($V_{DS}=0V$), AC ($f>1\text{ Hz}$)	V_{GS}	± 30	V
Continuous Drain Current at $T_C=25^\circ\text{C}$	$I_{D(DC)}$	6	A
Continuous Drain Current at $T_C=100^\circ\text{C}$	$I_{D(DC)}$	3.8	A
Pulsed drain current (Note 1)	$I_{DM(pluse)}$	24	A
Maximum Power Dissipation ($T_C=25^\circ\text{C}$)	P_D	98	W
Derate above 25°C		0.78	W/ $^\circ\text{C}$
Single pulse avalanche energy (Note2)	E_{AS}	100	mJ
Avalanche current (Note 1)	I_{AR}	5	A
Repetitive Avalanche energy, t_{AR} limited by T_{Jmax} (Note 1)	E_{AR}	0.3	mJ

Parameter	Symbol	Value	Unit
Drain Source voltage slope, $V_{DS} \leq 480\text{ V}$,	dv/dt	50	V/ns
Reverse diode dv/dt , $V_{DS} \leq 480\text{ V}, I_{SD} < I_D$	dv/dt	15	V/ns
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55...+150	°C

Table 2. Thermal Characteristic

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case (Maximum)	R_{thJC}	1.27	°C /W
Thermal Resistance, Junction-to-Ambient (Maximum)	R_{thJA}	62	°C /W

Table 3. Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
On/off states						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V I _D =250μA	800			V
Zero Gate Voltage Drain Current(Tc=25℃)	I _{DSS}	V _{DS} =800V,V _{GS} =0V			1	μA
Zero Gate Voltage Drain Current(Tc=125℃)	I _{DSS}	V _{DS} =800V,V _{GS} =0V			100	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V,V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} ,I _D =250μA	3	3.5	4	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =4A		780	900	mΩ
Dynamic Characteristics						
Forward Transconductance	g _{FS}	V _{DS} = 20V, I _D =4A		6		S
Input Capacitance	C _{iss}	V _{DS} =50V,V _{GS} =0V, F=1.0MHz		1290		pF
Output Capacitance	C _{Oss}			55		pF
Reverse Transfer Capacitance	C _{rss}			3		pF
Total Gate Charge	Q _g	V _{DS} =640V,I _D =6A, V _{GS} =10V		24		nC
Gate-Source Charge	Q _{gs}			8.5		nC
Gate-Drain Charge	Q _{gd}			7.5		nC
Switching times						
Turn-on Delay Time	t _{d(on)}	V _{DD} =400V,I _D =3A, R _G =3Ω,V _{GS} =10V		10		nS
Turn-on Rise Time	t _r			5		nS
Turn-Off Delay Time	t _{d(off)}			53	70	nS
Turn-Off Fall Time	t _f			6	9	nS
Source- Drain Diode Characteristics						
Source-drain current(Body Diode)	I _{SD}	T _C =25℃			6	A
Pulsed Source-drain current(Body Diode)	I _{SDM}				24	A
Forward on voltage	V _{SD}	T _j =25℃,I _{SD} =6A,V _{GS} =0V		0.9	1.2	V
Reverse Recovery Time	t _{rr}	T _j =25℃,I _F =3A, di/dt=100A/μs		260		nS
Reverse Recovery Charge	Q _{rr}			1.7		uC
Peak Reverse Recovery Current	I _{rrm}			13		A

Notes: 1.Repetitive Rating: Pulse width limited by maximum junction temperature

2. $T_J=25^\circ\text{C}, V_{DD}=50\text{V}, V_G=10\text{V}, R_G=25\Omega$

RATING AND CHARACTERISTICS CURVES(RM6N800IP/LD)

Figure1. Safe operating area




Figure2. Transient Thermal Impedance




Figure3. Source-Drain Diode Forward Voltage




Figure4. Output characteristics




Figure5. Transfer characteristics





Figure6. Static drain-source on resistance



RATING AND CHARACTERISTICS CURVES (RM6N800IP/LD)

Figure7. $R_{DS(ON)}$ vs Junction Temperature




Figure8. BV_{DSS} vs Junction Temperature




Figure9. Maximum I_D vs Junction Temperature






Figure10. Gate charge waveforms



Figure11. Capacitance

Test circuit



1) Gate charge test circuit & Waveform




2) Switch Time Test Circuit:



3) Unclamped Inductive Switching Test Circuit & Waveforms




TO-251 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.100	2.500	0.083	0.099
A1	0.850	1.150	0.034	0.045
B	0.718	1.018	0.028	0.040
b	0.700	0.900	0.028	0.036
b1	0.700	1.000	0.028	0.040
c	0.408	0.608	0.016	0.024
c1	0.408	0.508	0.016	0.020
D	6.400	6.800	0.253	0.269
D1	5.180	5.480	0.205	0.217
E	5.950	6.350	0.235	0.251
e	2.286		0.090	
e1	2.286		0.090	
L	6.700	7.300	0.265	0.289

TO-252 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.056	0.061
A1	0.970	1.17	0.025	0.030
b	0.720	0.850	0.018	0.022
b1	0.720	0.930	0.018	0.024
b2	5.230	5.460	0.133	0.139
b3	4.270	4.370	0.108	0.111
c	0.470	0.580	0.012	0.015
D	6.000	6.200	0.152	0.157
D1	5.300 TYP.		0.135	
E	6.500	6.700	0.165	0.170
E1	4.700	4.920	0.119	0.125
e	2.286 TYP		0.058	
L	1.400	1.700	0.036	0.043
L1	2.900 TYP.		0.074	
L2	0.510 TYP.		0.013	
L3	0.900	1.250	0.023	0.032
L4	0.600	1.000	0.015	0.025
L5	1.700	1.900	0.043	0.048
L6	0	0.1223	0.000	0.003

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.