

SCTL90N65G2V

Datasheet

Silicon carbide Power MOSFET 650 V, 18 mΩ typ., 40 A in a PowerFLAT 8x8 HV package



PowerFLAT 8x8 HV



Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
SCTL90N65G2V	650 V	24 mΩ	40 A

- Very fast and robust intrinsic body diode
- Low capacitances
- Source sensing pin for increased efficiency

Applications

- Switching mode power supply
- DC-DC converters
- Industrial motor control

Description

This silicon carbide Power MOSFET device has been developed using ST's advanced and innovative 2nd generation SiC MOSFET technology. The device features remarkably low on-resistance per unit area and very good switching performance. The variation of switching loss is almost independent of junction temperature.

Product status link
SCTL90N65G2V

Product summary	
Order code	SCTL90N65G2V
Marking	90N65G2V
Package	PowerFLAT 8x8 HV
Packing	Tape and reel

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	650	V
V_{GS}	Gate-source voltage	-10 to 22	V
	Gate-source voltage (recommended operating values)	-5 to 18	
I_D (1)	Drain current (continuous) at T_C = 25 °C	40	A
	Drain current (continuous) at T_C = 100 °C	40	
I_{DM} (2)	Drain current (pulsed)	160	A
P_{TOT}	Total power dissipation at T_C = 25 °C	935	W
T_{stg}	Storage temperature range	-55 to 175	°C
T_J	Operating junction temperature range		°C

1. *Value limited by package.*
2. *Pulse width is limited by safe operating area.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	0.16	°C/W
R_{thJB} (1)	Thermal resistance, junction-to-board	45	°C/W

1. *When mounted on an 1-inch² FR-4, 2 Oz copper board.*

2 Electrical characteristics

(T_C = 25 °C unless otherwise specified).

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 1 mA	650			V
I_{DSS}	Zero gate voltage drain current	V_{DS} = 650 V, V_{GS} = 0 V			10	µA
I_{GSS}	Gate-body leakage current	V_{DS} = 0 V, V_{GS} = -10 to 22 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 1 mA	1.8	3.2	5.0	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 18 V, I_D = 40 A		18	24	mΩ
		V_{GS} = 18 V, I_D = 40 A, T_J = 175 °C		27		

Table 4. Dynamic, based on HiP247 package option

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 400 V, f = 1 MHz, V_{GS} = 0 V	-	3380	-	pF
C_{oss}	Output capacitance		-	294	-	pF
C_{rss}	Reverse transfer capacitance		-	49	-	pF
R_g	Gate input resistance	f = 1 MHz, I_D = 0 A	-	1	-	Ω
Q_g	Total gate charge	V_{DD} = 400 V, I_D = 50 A, V_{GS} = -5 V to 18 V	-	157	-	nC
Q_{gs}	Gate-source charge		-	43	-	nC
Q_{gd}	Gate-drain charge		-	42	-	nC

Table 5. Switching energy (inductive load), based on HiP247 package option

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
E_{on}	Turn-on switching energy	V_{GS} = -5 to 18 V, V_{DD} = 400 V, I_D = 50 A, R_G = 2.2 Ω	-	130	-	µJ
E_{off}	Turn-off switching energy		-	210	-	µJ
E_{on}	Turn-on switching energy	V_{GS} = -5 to 18 V, V_{DD} = 400 V, I_D = 50 A, R_G = 2.2 Ω, T_C = 150 °C	-	135	-	µJ
E_{off}	Turn-off switching energy		-	200	-	µJ

Table 6. Switching times, based on HiP247 package option

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 400 V, I_D = 50 A, R_G = 2.2 Ω, V_{GS} = -5 V to 18 V	-	26	-	ns
t_f	Fall time		-	16	-	ns
$t_{d(off)}$	Turn-off delay time		-	58	-	ns
t_r	Rise time		-	38	-	ns

Table 7. Reverse SiC diode characteristics, based on HiP247 package option

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{SD}	Forward on voltage	I_F = 30 A, V_{GS} = 0 V	-	2.5	-	V
t_{rr}	Reverse recovery time	I_F = 50 A, di/dt = 4000 A/µs, V_{DD} = 400 V	-	17	-	ns
Q_{rr}	Reverse recovery charge		-	308	-	nC
I_{RRM}	Reverse recovery current		-	30	-	A

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Maximum transient thermal impedance




Figure 3. Typical output characteristics (T_J = -50 °C)




Figure 4. Typical output characteristics (T_J = 25 °C)




Figure 5. Typical output characteristics (T_J = 175 °C)




Figure 6. Typical transfer characteristics




Figure 7. Typical capacitance characteristics, based on HiP247 package option




Figure 8. Typical gate charge characteristics, based on HiP247 package option




Figure 9. Total power dissipation




Figure 10. Normalized on-resistance vs temperature




Figure 11. Normalized gate threshold vs temperature




Figure 12. Normalized breakdown voltage vs temperature




Figure 13. Typical switching energy vs drain current, based on HiP247 package option




Figure 14. Typical switching energy vs temperature




Figure 15. Typical reverse conduction characteristics (T_J = -50 °C)




Figure 16. Typical reverse conduction characteristics (T_J = 25 °C)





Figure 17. Typical reverse conduction characteristics (T_J = 150 °C)



3 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

3.1 PowerFLAT 8x8 HV type A package information

Figure 18. PowerFLAT 8x8 HV type A package outline





Table 8. PowerFLAT 8x8 HV type A mechanical data

Ref.	Dimensions (in mm)		
	Min.	Typ.	Max.
A	0.75	0.85	0.95
A1	0.00		0.05
A3	0.10	0.20	0.30
b	0.90	1.00	1.10
D	7.90	8.00	8.10
E	7.90	8.00	8.10
D2	7.10	7.20	7.30
E1	2.65	2.75	2.85
E2	4.25	4.35	4.45
e		2.00 BSC	
L	0.40	0.50	0.60


Figure 19. PowerFLAT 8x8 HV footprint



Note: All dimensions are in millimeters.

3.2 PowerFLAT 8x8 HV packing information

Figure 20. PowerFLAT 8x8 HV tape



Note: All dimensions are in millimeters.

Figure 21. PowerFLAT 8x8 HV package orientation in carrier tape





Figure 22. **PowerFLAT 8x8 HV reel**



8229819_Reel_revA

Note: All dimensions are in millimeters.

Revision history

Table 9. **Document revision history**

Date	Version	Changes
10-Dec-2020	1	First release.

Contents

1 **Electrical ratings** 2

2 **Electrical characteristics** 3

2.1 Electrical characteristics (curves) 5

3 **Package information** 8

3.1 PowerFLAT 8x8 HV type A package information 8

3.2 PowerFLAT 8x8 HV packing information 10

Revision history 12

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved