

STP80N240K6

Datasheet

N-channel 800 V, 197 mΩ typ., 16 A MDmesh K6 Power MOSFET in a TO-220 package



TO-220



AM01476v1_tab

Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
STP80N240K6	800 V	220 mΩ	16 A

- Worldwide best $R_{DS(on)}$ x area
- Worldwide best FOM (figure of merit)
- Ultra low gate charge
- 100% avalanche tested
- Zener-protected

Applications

- Flyback converter
- Adapters for tablets, notebook and AIO
- LED lighting

Description

This very high voltage N-channel Power MOSFET is designed using the ultimate MDmesh K6 technology based on 20 years STMicroelectronics experience on super junction technology. The result is the best-in-class on-resistance per area and gate charge for applications requiring superior power density and high efficiency.

Product status link
STP80N240K6

Product summary	
Order code	STP80N240K6
Marking	80N240K6
Package	TO-220
Packing	Tube

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{GS}	Gate-source voltage	±30	V
I_D	Drain current (continuous) at T_C = 25 °C	16	A
	Drain current (continuous) at T_C = 100 °C	10	
I_{DM}(1)	Drain current (pulsed)	35	A
P_{TOT}	Total power dissipation at T_C = 25 °C	140	W
dv/dt(2)	Peak diode recovery voltage slope	5	V/ns
di/dt(2)	Peak diode recovery current slope	100	A/µs
dv/dt(3)	MOSFET dv/dt ruggedness	120	V/ns
T_{stg}	Storage temperature range	-55 to 150	°C
T_J	Operating junction temperature range		

1. *Pulse width limited by safe operating area.*
2. *I_{SD} ≤ 4 A; V_{DS} (peak) = 400 V.*
3. *V_{DS} ≤ 640 V.*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	0.89	°C/W
R_{thJA}	Thermal resistance, junction-to-ambient	62.5	°C/W

Table 3. Avalanche characteristics

Symbol	Parameter	Value	Unit
I_{AR}	Avalanche current, repetitive or not repetitive (pulse width limited by T_J max.)	3.3	A
E_{AS}	Single pulse avalanche energy (starting T_J = 25 °C, I_D = I_{AR}, V_{DD} = 50 V)	200	mJ

2 Electrical characteristics

T_C = 25 °C unless otherwise specified.

Table 4. On/off-state

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS} = 0 V, I_D = 1 mA	800			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 800 V			1	µA
		V_{GS} = 0 V, V_{DS} = 800 V, T_C = 125 °C(1)			50	
I_{GSS}	Gate body leakage current	V_{DS} = 0 V, V_{GS} = ±20 V			±1	µA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 100 µA	3.0	3.5	4.0	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 7 A		197	220	mΩ

1. *Specified by design, not tested in production.*

Table 5. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 400 V, f = 1 MHz, V_{GS} = 0 V	-	1350	-	pF
C_{oss}	Output capacitance		-	20	-	pF
$C_{o(er)}$(1)	Equivalent capacitance energy related	V_{DS} = 0 to 640 V, V_{GS} = 0 V	-	25	-	pF
$C_{o(tr)}$(2)	Equivalent capacitance time related		-	139	-	pF
R_G	Intrinsic gate resistance	f = 1 MHz , I_D = 0 A	-	1.8	-	Ω
Q_g	Total gate charge	V_{DD} = 640 V, I_D = 7 A, V_{GS} = 0 to 10 V (see Figure 18. Test circuit for gate charge behavior)	-	25.9	-	nC
Q_{gs}	Gate-source charge		-	6.9	-	nC
Q_{gd}	Gate-drain charge		-	8.4	-	nC

1. *$C_{o(er)}$ is a constant capacitance value that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 V to the stated value.*
2. *$C_{o(tr)}$ is a constant capacitance value that gives the same charging time as C_{oss} while V_{DS} is rising from 0 V to the stated value.*

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{DD} = 400 V, I_D = 7 A, R_G = 4.7 Ω, V_{GS} = 10 V see (Figure 16. Test circuit for resistive load switching times and Figure 17. Switching time waveform)	-	16	-	ns
t_r	Rise time		-	5.3	-	ns
$t_{d(off)}$	Turn-off delay time		-	47.8	-	ns
t_f	Fall time		-	12	-	ns

Table 7. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		16	A
I_{SDM}(1)	Source-drain current (pulsed)		-		35	A
V_{SD}(2)	Forward on voltage	I_{SD} = 14 A, V_{GS} = 0 V	-		1.5	V
t_{rr}	Reverse recovery time	I_{SD} = 14 A, di/dt = 100 A/µs, V_{DD} = 60 V (see Figure 19. Test circuit for inductive load switching and diode recovery times)	-	335		ns
Q_{rr}	Reverse recovery charge		-	5.4		µC
I_{RRM}	Reverse recovery current		-	27.5		A
t_{rr}	Reverse recovery time	I_{SD} = 14 A, di/dt = 100 A/µs, V_{DD} = 60 V, T_J = 150 °C (see Figure 19. Test circuit for inductive load switching and diode recovery times)	-	430		ns
Q_{rr}	Reverse recovery charge		-	7.4		µC
I_{RRM}	Reverse recovery current		-	28		A

1. *Pulse width limited by safe operating area.*
2. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%.*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Maximum transient thermal impedance




Figure 3. Typical output characteristics




Figure 4. Typical transfer characteristics




Figure 5. Typical drain-source on-resistance




Figure 6. Normalized on-resistance vs temperature




Figure 7. Typical gate charge characteristics




Figure 8. Typical capacitance characteristics




Figure 9. Normalized gate threshold vs temperature




Figure 10. Normalized breakdown voltage vs temperature




Figure 11. Typical output capacitance stored energy




Figure 12. Maximum avalanche energy vs temperature




Figure 13. Typical reverse diode forward characteristics




Figure 14. Typical inductive load switching energy vs I_D






Figure 15. Typical inductive load switching energy vs R_G




3 Test circuits

Figure 16. Test circuit for resistive load switching times




AM01468v1

Figure 17. Switching time waveform




GADG280620211209SA

Figure 18. Test circuit for gate charge behavior




AM01469v10

Figure 19. Test circuit for inductive load switching and diode recovery times




AM01470v1

Figure 20. Unclamped inductive load test circuit



AM01471v1

Figure 21. Unclamped inductive waveform



AM01472v1

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 TO-220 type A package information

Figure 22. TO-220 type A package outline




Table 8. **TO-220 type A package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
b	0.61		0.88
b1	1.14		1.55
c	0.48		0.70
D	15.25		15.75
D1		1.27	
E	10.00		10.40
e	2.40		2.70
e1	4.95		5.15
F	1.23		1.32
H1	6.20		6.60
J1	2.40		2.72
L	13.00		14.00
L1	3.50		3.93
L20		16.40	
L30		28.90	
øP	3.75		3.85
Q	2.65		2.95
Slug flatness		0.03	0.10

Revision history

Table 9. **Document revision history**

Date	Revision	Changes
30-Jun-2021	1	Initial release.
11-Feb-2022	2	Updated *Applications* on cover page. Updated *Table 5. Dynamic*. Updated *Figure 15. Typical inductive load switching energy vs I_D*. Updated *Figure 16. Typical inductive load switching energy vs R_G*. Minor text changes.
29-Sep-2022	3	Removed "*Figure 8. Typical output capacitance stored energy*". Minor text changes.
19-Feb-2024	4	Replaced Figure 1. Safe operating area.

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Test circuits** 8
4 **Package information** 9
4.1 TO-220 type A package information 9
Revision history 11

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved