


APPROVED: _____

DATE: _____ TITLE: _____


Rev	AWO #	Description	Date	Appr
-		RELEASED	8/11/21	
A		UPDATED SPEC.	5/27/22	JJ/MC
B		UPDATED SPEC.	11/22/22	WX/AC1









RECOMMENDED
PANEL CUT-OUT



2 WAY



(DPDT) ON-ON



3 WAY

SW-T2-4X-B-A2-MA2

- B=ON-ON (2 WAY)
- D=ON-(ON) (2 WAY)
- E=ON-OFF-ON (3 WAY)
- F=ON-OFF-(ON) (3 WAY)
- G=(ON)-OFF-(ON) (3 WAY)
- H=ON-ON-ON (3 WAY)

SPECIFICATIONS:

Material:

Body: Bakelite, Color: Red (B)

Lever: Brass, Nickel plated

Terminal: Brass, Silver plated

Electrical:

Rating: 3A @ 250V AC
6A @ 125V AC

Contact resistance: 20 mΩ max

Insulation resistance: 1000 MΩ min (500VDC)

Dielectric withstanding voltage: 1500V AC for 1 minute

Electrical Life: 10,000 cycles

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant (RoHS COMPLIANT)

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED

INCHES		HOLES	
.X	± .10	Ø.X	±.10
.XX	± .020	Ø.XX	±.015
.XXX	± .015	Ø.XXX	±.010

DRAWN	JJ	8/11/21
CHECKED	RC	8/11/21
APPROVED		

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH

ADAM TECH
909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

TITLE: SWITCH, TOGGLE MINIATURE, DPDT, PCB VERTICAL TYPE

SIZE	PART NO.	REV.
X	SW-T2-4X-B-A2-MA2	B

REF: - SCALE: NTS SHEET 1 OF 1