
REGISTER

SY100E142

- **700MHz min. shift frequency**
- **Extended 100E V_{EE} range of –4.2V to –5.5V**
- **9 bits wide for byte-parity applications**
- **Asynchronous Master Reset**
- **Dual clocks**
- **Fully compatible with industry standard 10KH, 100K ECL levels**
- **Internal 75KΩ input pulldown resistors**
- **Fully compatible with Motorola MC10E/100E142**
- **Available in 28-pin PLCC package**




The SY10/100E142 are high-speed 9-bit shift registers designed for use in new, high-performance ECL systems. The E142 can accept serial or parallel data to be shifted out in one direction as both serial and parallel outputs. The nine inputs, D_0-D_8, accept parallel input data, while S-IN accepts serial input data.

The SEL (Select) control pin serves to determine the mode of operation, either SHIFT or LOAD. The shift direction is from bit 0 to bit 8. The input data has to meet the set-up time before being clocked into the nine input registers on the rising edge of CLK_1 or CLK_2. Shifting is also performed on the rising edge of either CLK_1 or CLK_2. The MR (Master Reset) control signal asynchronously resets all nine registers to a logic LOW when a logic HIGH is applied to MR.

The E142 is designed for applications such as diagnostic scan registers, parallel-to-serial conversions and is also suitable for byte-wide parity.

	Function
D_0-D_8	Parallel Data Inputs
S-IN	Serial Data Input
SEL	Mode Select Input
CLK_1, CLK_2	Clock Inputs
MR	Master Reset
Q_0-Q_8	Data Outputs
V_{CCO}	V_{CC} to Output



28-Pin PLCC (J28-1)

(1)

Part Number	Package Type	Operating Range	Package Marking	Lead Finish
SY10E142JC	J28-1	Commercial	SY10E142JC	Sn-Pb
SY10E142JCTR[2]	J28-1	Commercial	SY10E142JC	Sn-Pb
SY100E142JC	J28-1	Commercial	SY100E142JC	Sn-Pb
SY100E142JCTR[2]	J28-1	Commercial	SY100E142JC	Sn-Pb
SY10E142JY[3]	J28-1	Industrial	SY10E142JY with Pb-Free bar-line indicator	Matte-Sn
SY10E142JYTR[2, 3]	J28-1	Industrial	SY10E142JY with Pb-Free bar-line indicator	Matte-Sn
SY100E142JZ[3]	J28-1	Commercial	SY100E142JZ with Pb-Free bar-line indicator	Matte-Sn
SY100E142JZTR[2, 3]	J28-1	Commercial	SY100E142JZ with Pb-Free bar-line indicator	Matte-Sn

Notes:

1. Contact factory for die availability. Dice are guaranteed at $T_A = 25°C$, DC Electricals only.
2. Tape and Reel.
3. Pb-Free package is recommended for new designs.

L	LOAD
H	SHIFT

VEE = VEE (Min.) to VEE (Max.); VCC = VCCO = GND


Symbol	Parameter	TA = 0°C			TA = +25°C			TA = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
I_{IH}	Input HIGH Current	—	—	150	—	—	150	—	—	150	µA	—
I_{EE}	Power Supply Current										mA	—
	10E	—	120	145	—	120	145	—	120	145		
	100E	—	120	145	—	120	145	—	138	165		

VEE = VEE (Min.) to VEE (Max.); VCC = VCCO = GND

Symbol	Parameter	TA = 0°C			TA = +25°C			TA = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
f_{SHIFT}	Max. Shift Frequency	700	900	—	700	900	—	700	900	—	MHz	—
t_{PD}	Propagation Delay to Output										ps	—
	CLK	600	800	1000	600	800	1000	600	800	1000		
	MR	600	800	1000	600	800	1000	600	800	1000		
t_S	Set-up Time										ps	—
	D	50	–100	—	50	–100	—	50	–100	—		
	SEL	300	150	—	300	150	—	300	150	—		
t_H	Hold Time										ps	—
	D	300	100	—	300	100	—	300	100	—		
	SEL	75	–150	—	75	–150	—	75	–150	—		
t_{RR}	Reset Recovery Time	900	700	—	900	700	—	900	700	—	ps	—
t_{PW}	Minimum Pulse Width CLK, MR	400	—	—	400	—	—	400	—	—	ps	—
t_{skew}	Within-Device Skew	—	75	—	—	75	—	—	75	—	ps	1
t_r t_f	Rise/Fall Time 20% to 80%	300	525	800	300	525	800	300	525	800	ps	—

Note:

1. Within-device skew is defined as identical transitions on similar paths through a device.



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03

MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA

TEL + 1 (408) 944-0800 FAX + 1 (408) 474-1000 WEB http://www.micrel.com

The information furnished by Micrel in this data sheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is at Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2006 Micrel, Incorporated.