

- **700ps max. propagation delay**
- **Extended 100E V_{EE} range of –4.2V to –5.5V**
- **Differential outputs**
- **Fully compatible with industry standard 10KH, 100K ECL levels**
- **Internal 75KΩ input pulldown resistors**
- **Fully compatible with Motorola MC10E/100E150**
- **Available in 28-pin PLCC package**

The SY10/100E150 are 6-bit D latches with differential outputs designed for use in new, high- performance ECL systems. When both Latch Enables (LEN_1, LEN_2) are at a logic LOW, the latch is in the transparent mode and input data propagates through to the output. A logic HIGH on either LEN_1 or LEN_2 (or both) latches the input data. The Master Reset (MR) overrides all other signals to set the Q outputs to a logic LOW.



D_0–D_5	Data Inputs
LEN_1, LEN_2	Latch Enables
MR	Master Reset
Q_0–Q_5	True Outputs
$\overline{Q_0}$–$\overline{Q_5}$	Inverting Outputs
V_{CCO}	V_{CC} to Output



28-Pin PLCC (J28-1)

(1)

Part Number	Package Type	Operating Range	Package Marking	Lead Finish
SY10E150JC	J28-1	Commercial	SY10E150JC	Sn-Pb
SY10E150JCTR[2]	J28-1	Commercial	SY10E150JC	Sn-Pb
SY100E150JC	J28-1	Commercial	SY100E150JC	Sn-Pb
SY100E150JCTR[2]	J28-1	Commercial	SY100E150JC	Sn-Pb
SY10E150JZ[3]	J28-1	Commercial	SY10E150JZ with Pb-Free bar-line indicator	Matte-Sn
SY10E150JZTR[2, 3]	J28-1	Commercial	SY10E150JZ with Pb-Free bar-line indicator	Matte-Sn
SY100E150JZ[3]	J28-1	Commercial	SY100E150JZ with Pb-Free bar-line indicator	Matte-Sn
SY100E150JZTR[2, 3]	J28-1	Commercial	SY100E150JZ with Pb-Free bar-line indicator	Matte-Sn

Notes:

1. Contact factory for die availability. Dice are guaranteed at $T_A = 25°C$, DC Electricals only.
2. Tape and Reel.
3. Pb-Free package is recommended for new designs.

(Each Latch)

INPUTS				OUTPUTS		Operating
D_n	LEN_1	LEN_2	MR	Q_n	$\overline{Q}_n$	Mode
H	L	L	L	H	L	Latch
L	L	L	L	L	H	
X	X	H	L	Latched(2)	Latched(2)	
X	H	X	L	Latched(2)	Latched(2)	
X	X	X	H	L	H	Asynchronous

Notes:

1. H = HIGH state
   L = LOW state
   X = Don't care
2. Retains Data that is present before the LEN positive transition.

EE = VEE (Min.) to VEE (Max.); VCC = VCCO = GND


Symbol	Parameter	T_A = 0°C			T_A = +25°C			T_A = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
I_{IH}	Input HIGH Current										µA	—
	D	—	—	200	—	—	200	—	—	200		
	LEN MR	—	—	150	—	—	150	—	—	150		
I_{EE}	Power Supply Current										mA	—
	10E	—	52	62	—	52	62	—	52	62		
	100E	—	52	62	—	52	62	—	60	72		

EE = VEE (Min.) to VEE (Max.); VCC = VCCO = GND

Symbol	Parameter	T_A = 0°C			T_A = +25°C			T_A = +85°C			Unit	Condition
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.		
t_{PD}	Propagation Delay to Output										ps	—
	D	250	375	550	250	375	550	250	375	550		
	LEN	375	500	700	375	500	700	375	500	700		
	MR	450	625	750	450	625	750	450	625	750		
t_S	Set-up Time, D	200	50	—	200	50	—	200	50	—	ps	—
t_H	Hold Time, D	200	–50	—	200	–50	—	200	–50	—	ps	—
t_{RR}	Reset Recovery Time	750	650	—	750	650	—	750	650	—	ps	—
t_{PW}	Minimum Pulse Width, MR	400	—	—	400	—	—	400	—	—	ps	—
t_{skew}	Within-Device Skew	—	50	—	—	50	—	—	50	—	ps	1
t_r t_f	Rise/Fall Time 20% to 80%	300	450	650	300	450	650	300	450	650	ps	—

Note:

1. Within-device skew is defined as identical transitions on similar paths through a device.



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03

MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA

TEL + 1 (408) 944-0800 FAX + 1 (408) 474-1000 WEB http://www.micrel.com

The information furnished by Micrel in this data sheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is at Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2006 Micrel, Incorporated.