LOW-POWER HEX ECL-to-TTL TRANSLATOR

SY100S325

Features


- **Max. propagation delay of 3.7ns**
- **I_{EE} min. of –37mA**
- **TTL outputs**
- **Extended supply voltage option: V_{EE} = –4.2V to –5.5V**
- **25% faster than National's 325**
- **Differential inputs with built-in offset**
- **Voltage and temperature compensation for improved noise immunity**
- **V_{BB} output for single-ended use**
- **Internal 75KΩ input pull-down resistors**
- **Function and pinout compatible with Fairchild F100K**
- **Available in 28-pin PLCC package**

General Description

The SY100S325 are hex translators for converting 100K ECL logic levels to TTL logic levels. Inputs can be used as inverting, non-inverting or differential receivers. An internal reference voltage generator provides V_{BB} for single-ended operation or for use in Schmitt trigger applications. All inputs have 75KΩ pull-down resistors. The outputs will go LOW when the inputs are either open or have the same potential.


When used in single-ended operation, the apparent input threshold of the true inputs is 20mV to 40mV higher (positive) than the threshold of the complementary inputs. The V_{TTL} and V_{EE} power may be applied in either order.

Logic Diagram



Pin Description

	Function
D_0–D_5	Data Inputs
$\overline{D}_0$–$\overline{D}_5$	Inverting Data Inputs
Q_0–Q_5	Data Outputs
V_{EES}	V_{EE} Substrate
V_{TTL}	TTL V_{CC} Power Supply
V_{CCA}	V_{CCO} for ECL Outputs



28-Pin PLCC (J28-1)

Part Number	Package Type	Operating Range	Package Marking	Lead Finish
SY100S325JC	J28-1	Commercial	SY100S325JC	Sn-Pb
SY100S325JCTR[1]	J28-1	Commercial	SY100S325JC	Sn-Pb
SY100S325JY[2]	J28-1	Industrial	SY100S325JY with Pb-Free bar-line indicator	Matte-Tin
SY100S325JYTR[1, 2]	J28-1	Industrial	SY100S325JY with Pb-Free bar-line indicator	Matte-Tin

Notes:


1. Tape and Reel.
2. Pb-Free package is recommended for new designs.

V_{EE} = –4.2V to –4.8V unless otherwise specified, V_{CC} =V_{CCA} = GND, V_{TTL} = +4.5V to +5.5V

Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition	
V_{OH}	Output HIGH Voltage	2.5	—	—	V	I_{OH} = –2.0mA	V_{IN} = V_{IH} (Max.)
V_{OL}	Output LOW Voltage	—	—	0.5	V	I_{OL} = 24mA	V_{IN} = V_{IL} (Min.)
V_{DIFF}	Input Voltage Differential	150	—	—	mV	Required for Full Output Swing	
V_{CM}	Common Mode Voltage	—	—	1.0	V	Permissible ±V_{CM} with Respect to V_{BB}	
I_{IH}	Input HIGH Current	—	—	350	µA	V_{IN} = V_{IH} (Max.), D_0–D_5 = V_{BB}, $\overline{D_0}$–$\overline{D_5}$ = V_{IL} (Min.)	
I_{IL}	Input LOW Current	0.5	—	—	µA	V_{IN} = V_{IH} (Min.), D_0–D_5 = V_{BB}	
I_{OS}	Output Short Circuit Current	–150	–80	–60	mA	V_{OUT} = GND	
I_{EE}	V_{EE} Power Supply Current	–37	–24	–17	mA	D_0–D_5 = V_{BB}	
I_{TTL}	V_{TTL} Power Supply Current	—	42	65	mA	D_0–D_5 = V_{BB}	
V_{BB}	Ouptut Reference Voltage	–1380	–1320	–1260	mV	I_{VBB} = –2.1mA	
V_{IH}	Single-Ended Input HIGH Voltage	–1165	—	–880	mV	Guaranteed HIGH Signal for All Inputs (with One Tied to V_{BB})	
V_{IL}	Single-Ended Input LOW Voltage	–1810	—	–1475	mV	Guaranteed LOW Signal for All Inputs (with One Tied to V_{BB})	


V_{EE} = –4.2V to –5.5V unless otherwise specified, V_{CC} = V_{CCA} = GND, V_{TTL} = +4.5V to +5.5V

Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
t_{PLH} t_{PHL}	Propagation Delay Data to Output	900	2100	2900	ps	C_L = 15pF, Figure 2
t_{PLH} t_{PHL}	Propagation Delay Data to Output	900	3100	3700	ps	C_L = 50pF, Figure 2



Note:

V_{EE} = –4.2V to –5.5V unless otherwise specified, V_{CC} = V_{CCA} = GND



Notes:

V_{CC} = 0V, V_{EE} = –4.5V, V_{TTL} = +5V


L1 and L2 = equal length 50Ω impedance lines

R_T = 50Ω terminator internal to scope

Decoupling 0.1µF from GND to V_{CC}, V_{EE} and V_{TTL}

All unused outputs are loaded with 500Ω to GND

C_L = Fixture and stray capacitance = 3pF



NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03

MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA

TEL + 1 (408) 944-0800 FAX + 1 (408) 474-1000 WEB http://www.micrel.com

The information furnished by Micrel in this data sheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is at Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2006 Micrel, Incorporated.