

- **Max. propagation delay of 900ps**
- **I_{EE} min. of –92mA**
- **Industry standard 100K ECL levels**
- **Extended supply voltage option: V_{EE} = –4.2V to –5.5V**
- **Voltage and temperature compensation for improved noise immunity**
- **Internal 75kΩ input pull-down resistors**
- **60% faster than Fairchild 300K at lower power**
- **Function and pinout compatible with Fairchild F100K**
- **Available in 28-pin PLCC packages**

for use in new, high-performance ECL systems. The three Data Select inputs (S_0, S_1, S_2) determine the bits from each of the inputs (A_n, B_n) that will be passed on through the two outputs. The same bit will be selected from the two groups of 8 inputs. The inputs on this device have 75kΩ pull-down resistors.

Pin	Function
S_0 – S_2	Data Select Inputs
A_0 – A_7	A Data Inputs
B_0 – B_7	B Data Inputs
Z_a, Z_b	Data Outputs
V_{EES}	V_{EE} Substrate
V_{CCA}	V_{CCO} for ECL Outputs





Ordering Information

Part Number	Package Type	Operating Range	Package Marking	Lead Finish
SY100S363JC	J28-1	Commercial	SY100S363JC	Sn-Pb
SY100S363JCTR[1]	J28-1	Commercial	SY100S363JC	Sn-Pb
SY100S363JZ[2]	J28-1	Commercial	SY100S363JZ with Pb-Free bar-line indicator	Matte-Sn
SY100S363JZTR[1, 2]	J28-1	Commercial	SY100S363JZ with Pb-Free bar-line indicator	Matte-Sn

Notes:

1. Tape and Reel.
2. Pb-Free package is recommended for new designs.

Inputs											Outputs
Select			Data								
S_2	S_1	S_0	A_7/B_7	A_6/B_6	A_5/B_5	A_4/B_4	A_3/B_3	A_2/B_2	A_1/B_1	A_0/B_0	Z_a/Z_b
L L	L L	L L								L H	L H
L L	L L	H H							L H		L H
L L	H H	L L						L H			L H
L L	H H	H H					L H				L H
H H	L L	L L				L H					L H
H H	L L	H H			L H						L H
H H	H H	L L		L H							L H
H H	H H	H H	L H								L H


1. H = HIGH Voltage Level
   L = LOW Voltage Level
   Blank = X = Don't Care

V_{EE} = –4.2V to –5.5V unless otherwise specified; V_{CC} = V_{CCA} = GND


Symbol	Parameter	Min.	Typ.	Max.	Unit	Condition
I_{IH}	Input HIGH Current S_n A_n, B_n	 — —	 — —	 200 200	µA	V_{IN} = V_{IH} (Max.)
I_{EE}	Power Supply Current	–92	–66	–45	mA	Inputs Open

V_{EE} = –4.2V to –5.5V unless otherwise specified; V_{CC} = V_{CCA} = GND


Symbol	Parameter	T_A = 0°C		T_A = +25°C		T_A = +85°C		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.		
t_{PLH} t_{PHL}	Propagation Delay A_0 – A_7, B_0 – B_7 to Output	300	900	300	900	300	900	ps	
t_{PLH} t_{PHL}	Propagation Delay S_0 – S_2 to Output	400	1300	400	1300	400	1300	ps	
t_{TLH} t_{THL}	Transition Time 20% to 80%, 80% to 20%	300	900	300	900	300	900	ps	




V_{EE} = –4.2V to –5.5V unless otherwise specified; V_{CC} = V_{CCA} = GND




TOP VIEW



BOTTOM VIEW



SIDE VIEW



DETAIL "A"

Rev. A

NOTES:
1. DIMENSIONS ARE IN INCHES [MM].
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008 [0.203].
4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

MICREL, INC. 2180 FORTUNE DRIVE SAN JOSE, CA 95131 USA

TEL + 1 (408) 944-0800 FAX + 1 (408) 474-1000 WEB http://www.micrel.com

The information furnished by Micrel in this datasheet is believed to be accurate and reliable. However, no responsibility is assumed by Micrel for its use. Micrel reserves the right to change circuitry and specifications at any time without notification to the customer.

Micrel Products are not designed or authorized for use as components in life support appliances, devices or systems where malfunction of a product can reasonably be expected to result in personal injury. Life support devices or systems are devices or systems that (a) are intended for surgical implant into the body or (b) support or sustain life, and whose failure to perform can be reasonably expected to result in a significant injury to the user. A Purchaser's use or sale of Micrel Products for use in life support appliances, devices or systems is at Purchaser's own risk and Purchaser agrees to fully indemnify Micrel for any damages resulting from such use or sale.

© 2006 Micrel, Incorporated.