T2535T-8G

Datasheet

25 A - 800 V - T-series Triac in D²PAK



D²PAK

A2: Anode2
A1: Anode1
G: Gate



Product status link
T2535T-8G

Product summary	
$I_{T(RMS)}$	25 A
V_{DRM}, V_{RRM}	800 V
V_{DSM}, V_{RSM}	900 V
I_{GT}	35 mA

Features

- 25 A medium current Triac
- 150 °C maximum junction temperature T_J
- Surge capability V_{DSM}, V_{RSM} = 900 V
- Three triggering quadrants
- High noise immunity - static dV/dt
- Robust dynamic turn-off commutation - (dI/dt)c
- ECOPACK2 compliant component

Applications

- General purpose AC line load control
- AC induction and universal motor control
- Heating: water heater, e-bidet
- Power tools
- Cooker, oven
- Lighting and automation I/O control
- Inrush current limiting circuits
- Overvoltage crowbar protection

Description

The T2535T-8G Triac in SMD D^{2}PAK package can be used for the on/off or phase angle control function in general purpose AC switching.

Based on the ST Snubberless technology, it offers higher specified turn-off commutation and noise immunity levels up to 150 °C.

SMD D^{2}PAK package is suitable for automatic assembly line.

The T2535T-8G safely optimizes the control of the motors and heaters loads for the most constraining environments of home appliances.

1 Characteristics

Table 1. Absolute maximum ratings (limiting values)

Symbol	Parameter			Value	Unit
$I_{T(RMS)}$	RMS on-state current (full sine wave)		T_c = 121 °C	25	A
I_{TSM}	Non repetitive surge peak on-state current (full cycle, T_j initial = 25 °C)		t = 16.7 ms	210	A
			t = 20 ms	200	
I^2t	I^2t value for fusing		t_p = 10 ms	264	A^2s
dI/dt	Critical rate of rise of on-state current, I_G = 2 x I_{GT}, tr ≤ 100 ns, f = 100 Hz		f = 120 Hz	100	A/µs
V_{DRM}/ V_{RRM}	Repetitive peak off-state voltage		T_j = 125 °C	800	V
			T_j = 150 °C	600	
V_{DSM}/ V_{RSM}	Non Repetitive peak off-state voltage	t_p = 10 ms	T_j = 25 °C	900	V
I_{GM}	Peak gate current	t_p = 20 µs	T_j = 150 °C	4	A
P_{GM}	Maximum gate power dissipation	t_p = 20 µs	T_j = 150 °C	5	W
$P_{G(AV)}$	Average gate power dissipation		T_j = 150 °C	1	W
T_{stg}	Storage temperature range			-40 to +150	°C
T_j	Operating junction temperature range			-40 to +150	°C
T_L	Maximum lead temperature for soldering during 10 s			260	°C

Table 2. Electrical characteristics (T_j = 25 °C, unless otherwise specified)

Symbol	Test conditions	Quadrants		Value	Unit
I_{GT}	V_D = 12 V, R_L = 30 Ω	I - II - III	Min.	5	mA
			Max.	35	
V_{GT}			Max.	1	V
V_{GD}	V_D = V_{DRM}, R_L = 3.3 kΩ, T_j = 150 °C	I - II - III	Min.	0.15	V
I_L	I_G = 1.2 x I_{GT}	I - III	Max.	50	mA
		II	Max.	80	
I_H (1)	I_T = 500 mA, gate open		Max.	35	mA
dV/dt (1)	V_D = 536 V, gate open	T_j = 125 °C	Min.	1500	V/µs
	V_D = 402 V, gate open	T_j = 150 °C	Min.	1000	V/µs
(dI/dt)c (1)	Without snubber network	T_j = 125 °C	Min.	28	A/ms
		T_j = 150 °C	Min.	18	A/ms

1. *For both polarities of A2 referenced to A1.*

Table 3. Static characteristics

Symbol	Test conditions			Value	Unit
V_{TM} (1)	I_{TM} = 35 A, t_p = 380 µs	T_j = 25 °C	Max.	1.5	V
V_{TO} (1)	Threshold voltage	T_j = 150 °C	Max.	0.80	V
R_D (1)	Dynamic resistance	T_j = 150 °C	Max.	17	mΩ
I_{DRM}/I_{RRM}	V_D = V_R = 800 V, peak voltage	T_j = 25 °C	Max.	5	µA
		T_j = 125 °C		5	mA
	V_D = V_R = 600 V, peak voltage	T_j = 150 °C	Max.	6	mA
	V_D = V_R = 400 V, peak voltage	T_j = 150 °C	Max.	5	

1. *For both polarities of A2 referenced to A1.*

Table 4. Thermal resistance

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	Junction to case (AC)	Max.	1	°C/W
$R_{th(j-a)}$	Junction to ambient (S_{CU} = 2 cm2)	Typ.	45	

1. *Scu : copper pad surface under tab, 35 µm copper thickness on FR4 PCB.*

1.1 Characteristics (curves)

Figure 1. Maximum power dissipation versus on-state RMS current (full cycle)



Figure 2. On-state RMS current versus case temperature (full cycle)



Figure 3. On-state RMS current versus ambient temperature (free air convection)



Figure 4. On-state characteristics (maximum)



Figure 5. Relative variation of I_{GT},I_H, I_L vs junction temperature (typical values)



Figure 6. Relative variation of critical rate of decrease of main current versus junction temperature



Figure 7. Relative variation of critical rate of decrease of current (dI/dt)c versus reapplied (dV/dt)c



Figure 8. Surge peak on-state current versus number of cycles



Figure 9. Non repetitive surge peak on-state current for a sinusoidal pulse width t_P < 10 ms



Figure 10. Relative variation of thermal impedance versus pulse duration



Figure 11. Leakage current versus junction temperature for different values of blocking voltage (typical values)



2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: www.st.com. ECOPACK is an ST trademark.

2.1 D²PAK package information

- ECOPACK2 compliant
- Lead-free package leads finishing
- Molding compound resin is halogen-free and meets UL94 flammability standard level V0

Figure 12. D²PAK package outline



(1) Resin gate is accepted in each of position shown on the drawing, or their symmetrical.

Table 5. D²PAK package mechanical data

Ref.	Dimensions					
	Millimeters			Inches[1]		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.30		4.60	0.1693		0.1811
A1	2.49		2.69	0.0980		0.1059
A2	0.03		0.23	0.0012		0.0091
A3		0.25			0.0098	
b	0.70		0.93	0.0276		0.0366
b2	1.25		1.7	0.0492		0.0669
c	0.45		0.60	0.0177		0.0236
c2	1.21		1.36	0.0476		0.0535
D	8.95		9.35	0.3524		0.3681
D1	7.50		8.00	0.2953		0.3150
D2	1.30		1.70	0.0512		0.0669
e	2.54			0.10000		
E	10.00		10.28	0.3937		0.4047
E1	8.30		8.70	0.3268		0.3425
E2	6.85		7.25	0.2697		0.2854
G	4.88		5.28	0.1921		0.2079
H	15		15.85	0.5906		0.6240
L	1.78		2.28	0.0701		0.0898
L2	1.19		1.40	0.0460		0.0551
L3	1.40		1.75	0.0551		0.0689
R		0.40			0.0157	
V2[2]	0°		8°	0°		8°

1. *Dimensions in inches are given for reference only*
2. *Degrees*

Figure 13. D²PAK recommended footprint (dimensions are in mm)



Figure 14. D²PAK stencil definitions (dimensions are in mm)



3 Ordering information

Figure 15. **Ordering information scheme**



Table 6. **Ordering information**

Order code	Marking	Package	Weight	Base Qty.	Delivery mode
T2535T-8G	T2535T-8G	D²PAK	1.6 g	50	Tube
T2535T-8G-TR	T2535T-8G			2500	Tape and reel

Revision history

Table 7. **Document revision history**

Date	Version	Changes
23-Sep-2020	1	Initial release.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved