

- I/O isolation 3000 VACrms rated for 1000 Vrms (1410 Vpk) working voltage
- Medical safety to UL 60601-1 and IEC/EN 60601-1 3rd edition, 2 x MOOP
- Ultra compact DIP-24 package
- Wide 2:1 input voltage ranges
- Operating temperature range -40°C to $+75^{\circ}\text{C}$
- Low leakage current
- Short circuit protection
- Input filter to meet EN 55032, Class A
- 3-year product warranty



ES 60601-1 IEC 60601-1
UL 60950-1 IEC 60950-1

The THB 6 series is a new range of high performance, regulated DC/DC converters in a DIP-24 plastic package. A reinforced I/O-isolation system and a wide 2:1 input voltage range make this product the best choice for many demanding applications like transportation systems, industrial controls, medical equipment, instrumentation, everywhere where high basic-, supplementary- or reinforced insulation is required to meet requested safety standards. A high efficiency allows safe operation in a temperature range of -40°C to $+71^{\circ}\text{C}$. Other features of this product are over voltage protection and internal EMI-input filter to meet EN 55032 class A without additional components. Full SMD-design with exclusive use of ceramic capacitors ensures a very high reliability and a long product lifetime.

Models						
Order Code	Input Voltage Range	Output 1		Output 2		Efficiency typ.
		Vnom	I _{max}	Vnom	I _{max}	
THB 6-1211	9 - 18 VDC (12 VDC nom.)	5 VDC	1'000 mA			75 %
THB 6-1212		12 VDC	500 mA			78 %
THB 6-1222		+12 VDC	250 mA	-12 VDC	250 mA	78 %
THB 6-1223		+15 VDC	200 mA	-15 VDC	200 mA	78 %
THB 6-2411	18 - 36 VDC (24 VDC nom.)	5 VDC	1'000 mA			77 %
THB 6-2412		12 VDC	500 mA			80 %
THB 6-2422		+12 VDC	250 mA	-12 VDC	250 mA	80 %
THB 6-2423		+15 VDC	200 mA	-15 VDC	200 mA	80 %
THB 6-4811	36 - 75 VDC (48 VDC nom.)	5 VDC	1'000 mA			77 %
THB 6-4812		12 VDC	500 mA			80 %
THB 6-4822		+12 VDC	250 mA	-12 VDC	250 mA	80 %
THB 6-4823		+15 VDC	200 mA	-15 VDC	200 mA	80 %

Input Specifications

Input Current	- At no load	12 Vin models: 30 mA typ. 24 Vin models: 20 mA typ. 48 Vin models: 10 mA typ.
	- At full load	12 Vin models: 570 mA typ. (5 Vout model) 640 mA typ. (12 Vout model) 640 mA typ. (12 / -12 Vout model) 640 mA typ. (15 / -15 Vout model) 24 Vin models: 280 mA typ. (5 Vout model) 315 mA typ. (12 Vout model) 315 mA typ. (12 / -12 Vout model) 315 mA typ. (15 / -15 Vout model) 48 Vin models: 140 mA typ. (5 Vout model) 155 mA typ. (12 Vout model) 155 mA typ. (12 / -12 Vout model) 155 mA typ. (15 / -15 Vout model)
Surge Voltage		12 Vin models: 25 VDC max. (1 s max.) 24 Vin models: 50 VDC max. (1 s max.) 48 Vin models: 100 VDC max. (1 s max.)
Start-up Voltage		12 Vin models: 7 VDC min. / 8 VDC typ. / 9 VDC max. 24 Vin models: 13 VDC min. / 15 VDC typ. / 18 VDC max. 48 Vin models: 30 VDC min. / 33 VDC typ. / 36 VDC max.
Under Voltage Lockout		12 Vin models: 8.5 VDC max. 24 Vin models: 16 VDC max. 48 Vin models: 34 VDC max.
Reflected Ripple Current		12 Vin models: 60 mA typ. 24 Vin models: 30 mA typ. 48 Vin models: 15 mA typ.
Recommended Input Fuse		12 Vin models: 1'200 mA (slow blow) 24 Vin models: 600 mA (slow blow) 48 Vin models: 300 mA (slow blow) (The need of an external fuse has to be assessed in the final application.)
Input Filter		Internal Pi-Type
Short Circuit Input Power		3 W max.

Output Specifications

Voltage Set Accuracy		±1% max.
Regulation	- Input Variation (Vmin - Vmax)	single output models: 0.5% max. dual output models: 0.5% max.
	- Load Variation (25 - 100%)	single output models: 1% max. dual output models: 1% max. (Output 1) 1% max. (Output 2)
Ripple and Noise (20 MHz Bandwidth)	- single output	5 Vout models: 100 mVp-p max. 12 Vout models: 150 mVp-p max.
	- dual output	12 / -12 Vout models: 150 / 150 mVp-p max. 15 / -15 Vout models: 150 / 150 mVp-p max.
	- single output	5 Vout models: 75 mVp-p typ. 12 Vout models: 100 mVp-p typ.
	- dual output	12 / -12 Vout models: 100 / 100 mVp-p typ. 15 / -15 Vout models: 100 / 100 mVp-p typ.
	- single output	5 Vout models: 1'000 µF max. 12 Vout models: 470 µF max.
	- dual output	12 / -12 Vout models: 220 / 220 µF max. 15 / -15 Vout models: 220 / 220 µF max.

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Minimum Load	20 % of I _{out} max. (Operation at lower load will not damage the converter, but it may not meet all specifications)
Temperature Coefficient	±0.05 %/K max.
Short Circuit Protection	Continuous, Automatic recovery
Overload Protection	Foldback Mode
Output Current Limitation	120% min. of I _{out} max. 150% typ. of I _{out} max.
Transient Response	- Response Deviation - Response Time
	3% typ. / 6% max. (75% to 100% Load Step) 300 µs typ. / 500 µs max. (75% to 100% Load Step)

Safety Specifications

Standards	- IT / Multimedia Equipment - Medical Equipment - Certification Documents	CSA-C22.2, No. 60950-1 Designed for IEC/EN/UL 62368-1 (not certified) EN 60950-1 IEC 60950-1 UL 60950-1 EN 60601-1 IEC 60601-1 ANSI/AAMI ES 60601-1 CSA-C22.2, No 60601-1 2 x MOOP (Means Of Operator Protection) MOPP (Means Of Patient Protection) www.tracopower.com/thb6-safety-cert
Pollution Degree		PD 2
Over Voltage Category		Not mains connected

EMC Specifications

EMI (Emissions)	- Conducted Emissions - Radiated Emissions	EN 60601-1-2 edition 4 (Medical Devices) EN 55032 class A (internal filter) EN 55032 class A (internal filter)
EMS (Immunity)		EN 60601-1-2 edition 4 (Medical Devices)

General Specifications

Relative Humidity		95% max. (non condensing)
Temperature Ranges	- Operating Temperature - Case Temperature - Storage Temperature	-40°C to +75°C +95°C max. -50°C to +125°C
Power Derating	- High Temperature	2.5 %/K above 55°C
	See application note: www.tracopower.com/thb6-cc	
Cooling System		Natural convection (20 LFM)
Altitude During Operation		5'000 m max.
Switching Frequency		150 kHz typ. (PWM)
Insulation System		Reinforced Insulation
Working Voltage (rated)		1'000 VAC
Isolation Test Voltage	- Input to Output, 60 s	4'000 VDC
Isolation Resistance	- Input to Output, 500 VDC	10'000 MΩ min.
Isolation Capacitance	- Input to Output, 100 kHz, 1 V	7 pF typ. 13 pF max.
Reliability	- Calculated MTBF	1'000'000 h (MIL-HDBK-217F, ground benign)
Washing Process		According to Cleaning Guideline www.tracopower.com/info/cleaning.pdf
Housing Material		Non-conductive Plastic (UL 94 V-0 rated)
Potting Material		Silicone (UL 94 V-0 rated)


All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Pin Material	Copper Alloy (C6801)
Pin Foundation Plating	Nickel (2.5 µm min.)
Pin Surface Plating	Gold (75 - 125 nm), glossy
Housing Type	Plastic Case
Mounting Type	PCB Mount
Connection Type	THD (Through-Hole Device)
Footprint Type	DIP24
Soldering Profile	Lead-Free Wave Soldering 260°C / 10 s max.
Weight	18 g
Environmental Compliance	- REACH Declaration www.tracopower.com/info/reach-declaration.pdf REACH SVHC list compliant REACH Annex XVII compliant www.tracopower.com/info/rohs-declaration.pdf Exemptions: 7(a), 7(c)-I (RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule).) b96497e2-5138-4c12-9ba3-0f6e5882b328
	- RoHS Declaration
	- SCIP Reference Number

Additional Information

Supporting Documents	www.tracopower.com/overview/thb6
Frequently Asked Questions	www.tracopower.com/glossary-faq
Glossary	www.tracopower.com/info/glossary.pdf

Outline Dimensions



Pinout		
Pin	Single	Dual
1	+Vin (Vcc)	
11	No pin	Common
12	-Vout	No pin
13	+Vout	-Vout
15	No pin	+Vout
23	-Vin (GND)	
24	-Vin (GND)	