- **High-Speed Drive Controller for PNP Power Transistor**
- **Internal-Regulator Provides a Stable 1.5 V Reference Supply**
- **Low Start-Up Voltage 3.1 V**
- **Internal Short-Circuit Protection**
- **Internal Undervoltage Lockout Protection**
- **Internal Shut-Down Circuit by Channel**
- **Controllable Base Current of External Transistor**

description

The TL1464I incorporates on a single monolithic chip all the functions required in the construction of a pulse-width-modulation control circuit. Designed primarily for power supply control, the TL1464I contains an on-chip 1.5 V regulator, four error amplifiers, an oscillator, two dead-time comparators, undervoltage lockout circuitry, short circuit protection, standby control circuitry, and output circuits.

The external speed-up capacitors provide exceptional rise and fall time performance for the PNP power transistor.

The TL1464I operates from 3.1 V supply voltage and 2 pair of four-outputs (CH-1/CH-3, CH-2/CH-4 the same period) at the inverse phase of each other. As a result, the TL1464I provides high-efficiency power supply.

FUNCTION TABLE

INPUTS		OUTPUT FUNCTIONS				
STANDBY	**STANDBY-2 TO4**	**VREF**	**OUTPUT-1**	**OUTPUT-2**	**OUTPUT-3**	**OUTPUT-4**
$V_I \le 0.4$ V	$V_I \le 0.4$ V, $V_I \ge 2.4$ V	L	OFF	OFF	OFF	OFF
$V_I \ge 2.4$ V	$V_I \ge 2.4$ V	H	ON	ON	ON	ON
	$V_I \ge 0.4$ V	H	ON	See Note	See Note	See Note

NOTE: When the STANDBY input is high (≥ 2.4 V), OUTPUT-2 to 4 are controlled individually. If STANDBY-2 input is low (≤ 0.4 V), OUTPUT-2 is turned off. When CH-2 standby mode is released, CH-2 can do the soft-start function.




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.


PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 2000, Texas Instruments Incorporated

PT PACKAGE
(TOP VIEW)



functional block diagram



Terminal Functions

TERMINAL NAME	NO.	I/O	DESCRIPTION
BOOT CAP.H-1	33		Boot-strap capacitor connect pin (CH-1)
BOOT CAP.L-1	34		
BOOT CAP.H-2	39		Boot-strap capacitor connect pin (CH-2)
BOOT CAP.L-2	40		
BOOT CAP.H-3	46		Boot-strap capacitor connect pin (CH-3)
BOOT CAP.L-3	45		
BOOT CAP.H-4	4		Boot-strap capacitor connect pin (CH-4)
BOOT CAP.L-4	3		
C_T	14		Timing capacitor connect pin
DTC-1	31		Dead-time control input pin (CH-1)
DTC-2	26		Dead-time control input pin (CH-2)
FEEDBACK-1	27		Error amplifier output pin (CH-1)
FEEDBACK-2	22		Error amplifier output pin (CH-2)
FEEDBACK-3	11		Error amplifier output pin (CH-3)
FEEDBACK-4	8		Error amplifier output pin (CH-4)
GND	17		Ground pin
$\overline{\text{INV INPUT-1}}$	28		Error amplifier inverting input pin (CH-1)
$\overline{\text{INV INPUT-2}}$	23		Error amplifier inverting input pin (CH-2)
$\overline{\text{INV INPUT-3}}$	10		Error amplifier inverting input pin (CH-3)
$\overline{\text{INV INPUT-4}}$	7		Error amplifier inverting input pin (CH-4)
$\overline{\text{NONINV INPUT-1}}$	29		Error amplifier noninverting input pin (CH-1)
$\overline{\text{NONINV INPUT-2}}$	24		Error amplifier noninverting input pin (CH-2)
$\overline{\text{NONINV INPUT-3}}$	9		Error amplifier noninverting input pin (CH-3)
$\overline{\text{NONINV INPUT-4}}$	6		Error amplifier noninverting input pin (CH-4)
OUTPUT-1	35		Output pin (CH-1)
OUTPUT-2	41		Output pin (CH-2)
OUTPUT-3	44		Output pin (CH-3)
OUTPUT-4	2		Output pin (CH-4)
OUTPUT BIAS-1	32		Output ON current setup pin (CH-1)
OUTPUT BIAS-2	38		Output ON current setup pin (CH-2)
OUTPUT BIAS-3	47		Output ON current setup pin (CH-3)
OUTPUT BIAS-4	5		Output ON current setup pin (CH-4)
OUTPUT GND-1,2	37		Output ground pin (CH-1,2)
OUTPUT GND-3,4	48		Output ground pin (CH-3,4)
OUTPUT MONITOR-1	30		Output monitor comparator input pin (CH-1)
OUTPUT MONITOR-2	25		Output monitor comparator input pin (CH-2)
OUTPUT V_{CC-1}	36		Output supply pin (CH-1)
OUTPUT V_{CC-2}	42		Output supply pin (CH-2)
OUTPUT V_{CC-3}	43		Output supply pin (CH-3)
OUTPUT V_{CC-4}	1		Output supply pin (CH-4)
R_T	13		Timing resistor connect pin
SCP	15		Short-circuit protection capacitor connect pin

Terminal Functions (Continued)

TERMINAL NAME	NO.	I/O	DESCRIPTION
STANDBY	21		Output-1 to 4 control pin. Input L level voltage (0.4 V max). All outputs function and VREF are shutdown.
STANDBY-2	20		Output-2 control pin. Input L level voltage (0.4 V max), output-2 function is shutdown.
STANDBY-3	19		Output-3 control pin. Input L level voltage (0.4 V max), output-3 function is shutdown.
STANDBY-4	18		Output-4 control pin. Input L level voltage (0.4 V max), output-4 function is shutdown.
V_{CC}	12		Power supply pin

absolute maximum ratings over operating free-air temperature (unless otherwise noted)†

Supply voltage range, V_{CC} (see Note 1) . . . . . 13 V
Amplifier input voltage, V_{IC} . . . . . 13 V
Output voltage, V_O . . . . . 13 V
Peak output current (sink), $I_{(SINK)}$ . . . . . 100 mA
Peak output current (source), I_{SOURCE} . . . . . 1 A
Continuous total dissipation at (or below) 25°C free-air temperature (unit), P_D . . . . . 695 mW
Continuous total dissipation at (or below) 25°C free-air temperature (using board), P_D
(see Note 2) . . . . . 1315 mW
Operating free-air temperature range, T_A . . . . . –20°C to 75°C
Storage temperature range, T_{stg} . . . . . –65°C to 150°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds . . . . . 260°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage4 value are with respect to network ground terminal.
2. Using t1.6 × 50 × 50 mm glass epoxy resin.

recommended operating conditions

		MIN	NOM	MAX	UNIT
Supply voltage, V_{CC}		3.1		12	V
Amplifier input voltage, V_{IC}	CH-1,2	–0.1		V_{CC}–1.8	V
	CH-3,4	0		V_{CC}–1.8	
Standby input voltage, V_I (pins 18, 19. 20. 21)	H level	2.4		V_{CC}	V
	L level			0.4	
Output voltage, V_O				12	V
Current into feedback terminal, $I_{(CAMP)}$				–45	µA
Feedback resistor, $R_{(NF)}$		100			kΩ
Boot-strap capacitor, $C_{(BOOT)}$		100	500		pF
Bias resistor, $R_{(BIAS)}$		1.2		20	
Bias capacitor, $C_{(BIAS)}$			30	200	pF
Timing resistor, $R_{(T)}$		7		50	kΩ
Timing capacitor, $C_{(T)}$		68		1000	pF
Oscillation frequency, $f_{(OSC)}$		0.05		2	MHz
Operating free-air temperature, T_A		–20		75	°C

electrical characteristics over recommended operating free-air temperature range, V_{CC} = 6 V, f = 1 MHz (unless otherwise noted)

reference section

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{ref}	Output voltage (pin 16)	T_A = 25°C, $I_{(OR)}$ = –1 mA	1.485	1.50	1.515	V
$R_{(EGIN)}$	Input regulation	V_{OS} = 3.1 V to 12 V, $I_{(OR)}$ = –1 mA		2	12.5	mV
$R_{(EFL)}$	Output regulation	$I_{(OR)}$ = –0.1 mA to –1 mA		1	7.5	mV
$V_{(RTC1)}$	Output voltage change with temperature	T_A = 20°C to 25°C		–0.2%	±2%	
$R_{(RTC2)}$		T_A = 25°C to 75°C		–0.2%	±2%	
I_{OS}	Short-circuit output current	V_{ref} = 0 V	4	8		mA

undervoltage lockout section

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{IH}	Upper threshold voltage	T_A = 25°C		2.7		V
V_{IL}	Lower threshold voltage			2.5		V
V_{hys}	Hysteresis		0.1	0.2		V
V_R	Reset threshold voltage (V_{CC})		2.2	2.3		V

output voltage monitor section

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{IO(M)}$	Input offset voltage	T_A = 25°C (CH-1,2)		0		V
		V_I = 1.5 V (pins 6 and 9), T_A = 25°C (CH-3,4)		10.5		
$I_{(BOM)}$	Input bias current	V_I = 0 V		–200	–500	nA
$V_{(IOM)}$	Input voltage range	V_{CC} = 3.1 V ~ 12 V	0 to V_{CC}–1.8			V

protection control section

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$V_{(tPC)}$	Input threshold voltage (pin 15)	T_A = 25°C	1.45	1.50	1.55	V
$V_{(stby)}$	Standby voltage (pin 15)		40	70	100	mV
V_I	Latched input voltage (pin 15)			10	30	mV
$I_{(bPC)}$	Input source current (pin 15)	T_A = 25°C	–1	–3	–6	µA

oscillator section

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$f_{(OSC)}$	Frequency	C_t = 100 pF, R_t = 10 kΩ		1		MHz
$f_{(dev)}$	Standard deviation of frequency	All values are constant		7%		
$f_{(dV)}$	Frequency change with voltage	V_{CC} = 3 V ~ 12 V		1%		
$f_{(dT1)}$	Frequency change with temperature	T_A = 20°C to 25°C		–0.5%	±4%	
$f_{(dT2)}$		T_A = 25°C to 75°C		0.5%	±4%	

electrical characteristics over recommended operating free-air temperature range, V_{CC} = 6 V, f = 1 MHz (unless otherwise noted) (continued)

dead-time control section

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$I_{(Idt)}$	Input current			–1	–4	μA
$I_{(dt)}$	Latched mode sink current	T_A = 25°C	0.3	1	2	mA
$V_{(dt)}$	Latched input voltage	$I_{(dt)}$ = 100 μA			0.5	V
V_{IO}	Input threshold voltage	Zero duty cycle	0.6	0.7	0.8	V
$V_{(tt00)}$		100% duty cycle	1.3	1.4	1.5	

error-amplifier section

PARAMETER			TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{IO}	Input offset voltage		V_O = 1 V			±10	mV
I_{IO}	Input offset current		V_O = 1 V			±100	nA
I_{IB}	Input bias current		V_O = 1 V		–200	–500	nA
V_{ICR}	Common-mode input voltage	CH-1,2	V_{CC} = 3.1 V ~ 12 V	–0.1 to V_{CC}–1.8			V
		CH-3,4		0 to V_{CC}–1.8			
$A_{(v)}$	Open-loop voltage amplification		R_l = 200 kΩ	60	75		dB
B1	Unity-gain bandwidth				6		MHz
CMRR	Common-mode rejection ratio		V_{IC} = –0.1 V ~ V_{CC} – 1.8 V	60	80		dB
V_{OM+}	Maximum output voltage swing			V_{ref}–0.1			V
$V_{OM–}$						0.2	
$I_{O(vr+)}$	Output current (sink)		V_{ID} = –0.1 V, V_O = 1.25 V	0.5	1		mA
I_{I+}	Sink current (pin 24) (standby mode)		V_I = 0.3 V (pin 24) V_I = 0 V (pin 20)	0.1	0.5		mA
$I_{OM–}$	Output current (source)		V_{ID} = 0.1 V, V_O = 0.75 V	–45	–85		μA

output section

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$I_{(SINK)}$	Output current (sink)	$R_{(BIAS)}$ = 2.4 kΩ	15	20	25	mA
		$R_{(BIAS)}$ = 5.8 kΩ	7.5	10	12.5	

total device

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$I_{O(CS)}$	Standby supply current	Standby pin input voltage = 0 V		1	200	μA
$I_{O(CA)}$	Average supply current	R_t = 10 kΩ		4	7	mA




Figure 1. Timing Diagram (CH-1/CH-2)





Figure 2. Timing Diagram (CH-3/CH-4)

NOTES: A. Oscillator waveform of CH-1 and CH-2 is inverting output each other.
B. Va = input voltage of pin 29 (pin 24)

MECHANICAL DATA

PT (S-PQFP-G48) **PLASTIC QUAD FLATPACK**



NOTES: A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS-026
D. This may also be a thermally enhanced plastic package with leads conected to the die pads.

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TL1464IPT	Active	Production	LQFP (PT) | 48	250 | JEDEC TRAY (10+1)	Yes	NIPDAU	Level-1-260C-UNLIM	-20 to 75	Z1464
TL1464IPT.A	Active	Production	LQFP (PT) | 48	250 | JEDEC TRAY (10+1)	Yes	NIPDAU	Level-1-260C-UNLIM	-20 to 75	Z1464

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.


(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TRAY



Chamfer on Tray corner indicates Pin 1 orientation of packed units.

*All dimensions are nominal

Device	Package Name	Package Type	Pins	SPQ	Unit array matrix	Max temperature (°C)	L (mm)	W (mm)	K0 (µm)	P1 (mm)	CL (mm)	CW (mm)
TL1464IPT	PT	LQFP	48	250	10 x 25	150	315	135.9	7620	12.2	11.1	11.25
TL1464IPT.A	PT	LQFP	48	250	10 x 25	150	315	135.9	7620	12.2	11.1	11.25

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale, TI’s General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025