Excalibur™ LOW-NOISE HIGH-SPEED PRECISION OPERATIONAL AMPLIFIER


FEATURES

- **Controlled Baseline**
  - **One Assembly Site**
  - **One Test Site**
  - **One Fabrication Site**
- **Extended Temperature Performance of –55°C to 125°C**
- **Enhanced Diminishing Manufacturing Sources (DMS) Support**
- **Enhanced Product-Change Notification**
- **Qualification Pedigree(1)**


(1) Component qualification in accordance with JEDEC and industry standards to ensure reliable operation over an extended temperature range. This includes, but is not limited to, Highly Accelerated Stress Test (HAST) or biased 85/85, temperature cycle, autoclave or unbiased HAST, electromigration, bond intermetallic life, and mold compound life. Such qualification testing should not be viewed as justifying use of this component beyond specified performance and environmental limits.

- **Low Noise**
  - **10 Hz...15 nV/$\sqrt{Hz}$**
  - **1 kHz...10.5 nV/$\sqrt{Hz}$**
- **10 000-pF Load Capability**
- **20-mA (Min) Short-Circuit Output Current**
- **27-V/μs Slew Rate (Min)**
- **High Gain-Bandwidth Product...5.9 MHz**
- **Low V_{IO}...900 μV (Max) at 25°C**
- **Single or Split Supply...4 V to 44 V**
- **Fast Settling Time**
  - **340 ns to 0.1%**
  - **400 ns to 0.01%**
- **Saturation Recovery...150 ns**
- **Large Output Swing... $V_{CC–}$ + 0.1 V to V_{CC+} – 1 V**


TLE2141
D PACKAGE
(TOP VIEW)



TLE2142
D PACKAGE
(TOP VIEW)



TLE2144
DW PACKAGE
(TOP VIEW)



NC – No internal connection

DESCRIPTION

The TLE214x devices are high-performance, internally compensated operational amplifiers built using the Texas Instruments complementary bipolar Excalibur™ process. They are pin-compatible upgrades to standard industry products.

The design incorporates an input stage that simultaneously achieves low audio-band noise of 10.5 nV/$\sqrt{Hz}$ with a 10-Hz 1/f corner and symmetrical 40-V/μs slew rate typically with loads up to 800 pF. The resulting low distortion and high power bandwidth are important in high-fidelity audio applications. A fast settling time of 340 ns to 0.1% of a 10-V step with a 2-kΩ/100-pF load is useful in fast actuator/positioning drivers. Under similar test conditions, settling time to 0.01% is 400 ns.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Excalibur is a trademark of Texas Instruments.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of the Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 2008, Texas Instruments Incorporated

The devices are stable with capacitive loads up to 10 nF, although the 6-MHz bandwidth decreases to 1.8 MHz at this high loading level. As such, the TLE214x are useful for low-droop sample-and-holds and direct buffering of long cables, including 4-mA to 20-mA current loops.

The special design also exhibits an improved insensitivity to inherent integrated circuit component mismatches as is evidenced by a 900-μV maximum offset voltage and 1.7-μV/°C typical drift. Minimum common-mode rejection ratio and supply-voltage rejection ratio are 85 dB and 90 dB, respectively.

Device performance is relatively independent of supply voltage over the ±2-V to ±22-V range. Inputs can operate between V_{CC-} – 0.3 V to V_{CC+} – 1.8 V without inducing phase reversal, although excessive input current may flow out of each input exceeding the lower common-mode input range. The all-npn output stage provides a nearly rail-to-rail output swing of V_{CC-} – 0.1 V to V_{CC+} – 1 V under light current-loading conditions. The device can sustain shorts to either supply since output current is internally limited, but care must be taken to ensure that maximum package power dissipation is not exceeded.

Both versions can also be used as comparators. Differential inputs of $V_{CC\pm}$ can be maintained without damage to the device. Open-loop propagation delay with TTL supply levels is typically 200 ns. This gives a good indication as to output stage saturation recovery when the device is driven beyond the limits of recommended output swing.


The TLE214x devices are available in industry-standard 8-pin and 16-pin small-outline packages. The devices are characterized for operation from –55°C to 125°C.

ORDERING INFORMATION(1)

T_A	PACKAGE(2)			ORDERABLE PART NUMBER	TOP-SIDE MARKING
–55°C to 125°C	Single	SOIC – D (8 pin)	Reel of 2500	TLE2141MDREP	2141EP
	Dual	SOIC – D (8 pin)	Reel of 2500	TLE2142MDREP(3)	TBD
	Quad	SOIC – DW (16 pin)	Reel of 2000	TLE2144MDWREP(3)	TBD

(1) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI web site at www.ti.com.
(2) Package drawings, thermal data, and symbolization are available at www.ti.com/packaging.
(3) Product Preview. Contact your TI sales representative for availability.


SYMBOL



A. OFFSET N1 and OFFSET N2 are available only on the TLE2141.

Copyright © 2008, Texas Instruments Incorporated

EQUIVALENT SCHEMATIC



DEVICE COMPONENT COUNT

COMPONENT	TLE2141	TLE2142	TLE2144
Transistors	46	65	130
Resistors	24	43	86
Diodes	8	14	28
Capacitors	4	8	16
Epi-FET	1	1	2

A. OFFSET N1 and OFFSET N2 are available only on the TLE2141.

ABSOLUTE MAXIMUM RATINGS(1)

over operating free-air temperature range (unless otherwise noted)

V_{CC+}	Supply voltage(2)		22 V
$V_{CC–}$	Supply voltage		–22 V
V_{ID}	Differential input voltage(3)		±44 V
V_I	Input voltage range (any input)		V_{CC+} V to ($V_{CC–}$ – 0.3) V
I_I	Input current (each input)		±1 mA
I_O	Output current		±80 mA
	Total current into V_{CC+}		80 mA
	Total current out of $V_{CC–}$		80 mA
	Duration of short-circuit current at (or below) 25°C(4)		Unlimited
θ_{JA}	Package thermal impedance(5)(6)	D package	97.1°C/W
		DW package	57.3°C/W
T_A	Operating free-air temperature range		–55°C to 125 °C
T_{stg}	Storage temperature range(7)		–65°C to 150 °C
	Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds		260°C

(1) Stresses beyond those listed under *absolute maximum ratings* may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *recommended operating conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
(2) All voltage values, except differential voltages, are with respect to the midpoint between V_{CC+} and $V_{CC–}$.
(3) Differential voltages are at IN+ with respect to IN–. Excessive current flows, if input, are brought below $V_{CC–}$ – 0.3 V.
(4) The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.
(5) Maximum power dissipation is a function of $T_J(max)$, θ_{JA}, and T_A. The maximum allowable power dissipation at any allowable ambient temperature is $P_D = (T_J(max) – T_A)/\theta_{JA}$. Operating at the absolute maximum T_J of 150°C can affect reliability.
(6) The package thermal impedance is calculated in accordance with JESD 51-7.
(7) Long-term high temperature storage and/or extended use at maximum recommended operating conditions may result in a reduction of overall device life. See http://www.ti.com/ep_quality for additional information on enhanced product packaging.

RECOMMENDED OPERATING CONDITIONS

			MIN	MAX	UNIT
$V_{CC±}$	Supply voltage		±2	±22	V
V_{IC}	Common-mode input voltage	V_{CC} = 5 V	0	2.7	V
		$V_{CC±}$ = ±15 V	–15	12.7	
T_A	Operating free-air temperature		–55	125	°C

Copyright © 2008, Texas Instruments Incorporated

TLE2141 ELECTRICAL CHARACTERISTICS

V_{CC} = 5 V, at specified free-air temperature (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A (1)	TLE2141			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		225	1400	µV
			Full range			2100	
α_{VIO}	Temperature coefficient of input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	Full range		1.7		µV/°C
I_{IO}	Input offset current	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		8	100	nA
			Full range			250	
I_{IB}	Input bias current	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		–0.8	–2	µA
			Full range			–2.3	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	–0.3 to 3.2		V
			Full range	0 to 2.7	–0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = –150 µA	25°C	3.9	4.1		V
		I_{OH} = –1.5 mA		3.8	4		
		I_{OH} = –15 mA		3.2	3.7		
		I_{OH} = –100 µA	Full range	3.75			
		I_{OH} = –1 mA		3.65			
		I_{OH} = –10 mA		3.25			
V_{OL}	Low-level output voltage	I_{OL} = 150 µA	25°C		75	125	mV
		I_{OL} = 1.5 mA			150	225	
		I_{OL} = 15 mA			1.2	1.6	V
		I_{OL} = 100 µA	Full range			200	mV
		I_{OL} = 1 mA				250	
		I_{OL} = 10 mA				1.25	V
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V, R_L = 2 kΩ, V_O = 1 V to –1.5 V	25°C	50	220		V/mV
			Full range	5			
r_i	Input resistance		25°C		70		MΩ
c_i	Input capacitance		25°C		2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}(min), R_S = 50 Ω	25°C	85	118		dB
			Full range	80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		dB
			Full range	85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		3.4	4.4	mA
			Full range			4.6	

(1) Full range is –55°C to 125°C.

Copyright © 2008, Texas Instruments Incorporated

TLE2141 OPERATING CHARACTERISTICS

V_{CC} = 5 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLE2141			UNIT
				MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, R_L = 2 kΩ(1), C_L = 500 pF			45		V/µs
SR–	Negative slew rate	A_{VD} = –1, R_L = 2 kΩ(1), C_L = 500 pF			42		V/µs
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16		µs
			To 0.01%		0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω	f = 10 Hz		15		nV/√Hz
			f = 1 kHz		10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48		µV
		f = 0.1 Hz to 10 Hz			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92		pA/√Hz
		f = 1 kHz			0.5		
THD+N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, R_L = 2 kΩ(1), A_{VD} = 2, f = 10 kHz			0.0052		%
B_1	Unity-gain bandwidth	R_L = 2 kΩ(1), C_L = 100 pF(1)			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ(1), C_L = 100 pF(1), f = 100 kHz			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, R_L = 2 kΩ(1), A_{VD} = 1			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ(1), C_L = 100 pF(1)			57		°

(1) R_L and C_L terminated to 2.5 V.

Copyright © 2008, Texas Instruments Incorporated

TLE2141 ELECTRICAL CHARACTERISTICS

V_{CC} = ±15 V, at specified free-air temperature (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A (1)	TLE2141			UNIT
					MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω		25°C		200	900	µV
				Full range			1700	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω		Full range		1.7		µV/°C
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω		25°C		7	100	nA
				Full range			250	
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω		25°C		–0.7	–1.5	µA
				Full range			–1.8	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	–15 to 13	–15.3 to 13.2		V
				Full range	–15 to 12.7	–15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = –150 µA		25°C	13.8	14.1		V
		I_O = –1.5 mA			13.7	14		
		I_O = –15 mA			13.1	13.7		
		I_O = –100 µA		Full range	13.7			
		I_O = –1 mA			13.6			
		I_O = –10 mA			13.1			
$V_{OM–}$	Maximum negative peak output voltage swing	I_O = 150 µA		25°C	–14.7	–14.9		V
		I_O = 1.5 mA			–14.5	–14.8		
		I_O = 15 mA			–13.4	–13.8		
		I_O = 100 µA		Full range	–14.6			
		I_O = 1 mA			–14.5			
		I_O = 10 mA			–13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V, R_L = 2 kΩ		25°C	100	450		V/mV
				Full range	20			
r_i	Input resistance			25°C		65		MΩ
c_i	Input capacitance			25°C		2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}(min), R_S = 50 Ω		25°C	85	108		dB
				Full range	80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC±}/\Delta V_{IO}$)	$V_{CC±}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		dB
				Full range	85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	–25	–50		mA
			V_{ID} = –1 V		20	31		
I_{CC}	Supply current	V_O = 0, No load, V_{IC} = 2.5 V		25°C		3.5	4.5	mA
				Full range			4.7	

(1) Full range is –55°C to 125°C.

Copyright © 2008, Texas Instruments Incorporated

TLE2141 OPERATING CHARACTERISTICS

V_{CC} = ±15 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLE2141			UNIT
				MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, R_L = 2 kΩ, C_L = 100 pF		27	45		V/µs
SR–	Negative slew rate	A_{VD} = –1, R_L = 2 kΩ, C_L = 100 pF		27	42		V/µs
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34		µs
			To 0.01%		0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω	f = 10 Hz		15		nV/√Hz
			f = 1 kHz		10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48		µV
		f = 0.1 Hz to 10 Hz			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89		pA/√Hz
		f = 1 kHz			0.47		
THD+N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, R_L = 2 kΩ, A_{VD} = 10, f = 10 kHz			0.01		%
B_1	Unity-gain bandwidth	R_L = 2 kΩ, C_L = 100 pF			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, C_L = 100 pF, f = 100 kHz			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1, R_L = 2 kΩ, C_L = 100 pF			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ, C_L = 100 pF			58		°

Copyright © 2008, Texas Instruments Incorporated

TLE2142 ELECTRICAL CHARACTERISTICS

V_{CC} = 5 V, at specified free-air temperature (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A (1)	TLE2142			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		220	1900	μV
			Full range			2600	
α_{VIO}	Temperature coefficient of input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	Full range		1.7		μV/°C
I_{IO}	Input offset current	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		8	100	nA
			Full range			200	
I_{IB}	Input bias current	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		–0.8	–2	μA
			Full range			–2.3	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	–0.3 to 3.2		V
			Full range	0 to 2.7	–0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = –150 μA	25°C	3.9	4.1		V
		I_{OH} = –1.5 mA		3.8	4		
		I_{OH} = –15 mA		3.4	3.7		
		I_{OH} = –100 μA	Full range	3.75			
		I_{OH} = –1 mA		3.65			
		I_{OH} = –10 mA		3.45			
V_{OL}	Low-level output voltage	I_{OL} = 150 μA	25°C		75	125	mV
		I_{OL} = 1.5 mA			150	225	
		I_{OL} = 15 mA			1.2	1.4	V
		I_{OL} = 100 μA	Full range			200	mV
		I_{OL} = 1 mA				250	
		I_{OL} = 10 mA				1.25	V
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V, R_L = 2 kΩ, V_O = 1 V to 1.5 V	25°C	50	220		V/mV
			Full range	5			
r_i	Input resistance		25°C		70		MΩ
c_i	Input capacitance		25°C		2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}(min), R_S = 50 Ω	25°C	85	118		dB
			Full range	80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		dB
			Full range	85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		6.6	8.8	mA
			Full range			9.2	

(1) Full range is –55°C to 125°C.

Copyright © 2008, Texas Instruments Incorporated

TLE2142 OPERATING CHARACTERISTICS

V_{CC} = 5 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLE2142			UNIT
				MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, R_L = 2 kΩ(1), C_L = 500 pF			45		V/µs
SR–	Negative slew rate	A_{VD} = –1, R_L = 2 kΩ(1), C_L = 500 pF			42		V/µs
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16		µs
			To 0.01%		0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω	f = 10 Hz		15		nV/√Hz
			f = 1 kHz		10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48		µV
		f = 0.1 Hz to 10 Hz			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92		pA/√Hz
		f = 1 kHz			0.5		
THD+N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, R_L = 2 kΩ(1), A_{VD} = 2, f = 10 kHz			0.0052		%
B_1	Unity-gain bandwidth	R_L = 2 kΩ(1), C_L = 100 pF			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ(1), C_L = 100 pF, f = 100 kHz			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, R_L = 2 kΩ(1), A_{VD} = 1, C_L = 100 pF			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ(1), C_L = 100 pF			57		°

(1) R_L terminated at 2.5 V.

Copyright © 2008, Texas Instruments Incorporated

TLE2142 ELECTRICAL CHARACTERISTICS

V_{CC} = ±15 V, at specified free-air temperature (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A (1)	TLE2142			UNIT
					MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω		25°C		290	1200	µV
				Full range			2000	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω		Full range		1.7		µV/°C
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω		25°C		7	100	nA
				Full range			250	
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω		25°C		–0.7	–1.5	µA
				Full range			–1.8	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	–15 to 13	–15.3 to 13.2		V
				Full range	–15 to 12.7	–15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = –150 µA		25°C	13.8	14.1		V
		I_O = –1.5 mA			13.7	14		
		I_O = –15 mA			13.3	13.7		
		I_O = –100 µA		Full range	13.7			
		I_O = –1 mA			13.6			
		I_O = –10 mA			13.3			
$V_{OM–}$	Maximum negative peak output voltage swing	I_O = 150 µA		25°C	–14.7	–14.9		V
		I_O = 1.5 mA			–14.5	–14.8		
		I_O = 15 mA			–13.4	–13.8		
		I_O = 100 µA		Full range	–14.6			
		I_O = 1 mA			–14.5			
		I_O = 10 mA			–13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V, R_L = 2 kΩ		25°C	100	450		V/mV
				Full range	20			
r_i	Input resistance			25°C		65		MΩ
c_i	Input capacitance			25°C		2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}(min), R_S = 50 Ω		25°C	85	108		dB
				Full range	80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC±}/\Delta V_{IO}$)	$V_{CC±}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		dB
				Full range	85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	–25	–50		mA
			V_{ID} = –1 V		20	31		
I_{CC}	Supply current	V_O = 0, No load, V_{IC} = 2.5 V		25°C		6.9	9	mA
				Full range			9.4	

(1) Full range is –55°C to 125°C.

Copyright © 2008, Texas Instruments Incorporated

TLE2142 OPERATING CHARACTERISTICS

V_{CC} = ±15 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLE2142			UNIT
				MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, R_L = 2 kΩ, C_L = 100 pF		27	45		V/µs
SR–	Negative slew rate	A_{VD} = –1, R_L = 2 kΩ, C_L = 100 pF		27	42		V/µs
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34		µs
			To 0.01%		0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω	f = 10 Hz		15		nV/√Hz
			f = 1 kHz		10.5		
$V_{n(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48		µV
		f = 0.1 Hz to 10 Hz			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89		pA/√Hz
		f = 1 kHz			0.47		
THD+N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, R_L = 2 kΩ, A_{VD} = 10, f = 10 kHz			0.01		%
B_1	Unity-gain bandwidth	R_L = 2 kΩ, C_L = 100 pF			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, C_L = 100 pF, f = 100 kHz			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1, R_L = 2 kΩ, A_{VD} = 1, C_L = 100 pF			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ, C_L = 100 pF			58		°

Copyright © 2008, Texas Instruments Incorporated

TLE2144 ELECTRICAL CHARACTERISTICS

V_{CC} = 5 V, at specified free-air temperature (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A (1)	TLE2144			UNIT
				MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		0.5	3.8	mV
			Full range			5.2	
α_{VIO}	Temperature coefficient of input offset voltage	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	Full range		1.7		µV/°C
I_{IO}	Input offset current	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		8	100	nA
			Full range			250	
I_{IB}	Input bias current	V_O = 2.5 V, R_S = 50 Ω, V_{IC} = 2.5 V	25°C		–0.8	–2	µA
			Full range			–2.3	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	0 to 3	–0.3 to 3.2		V
			Full range	0 to 2.7	–0.3 to 2.9		
V_{OH}	High-level output voltage	I_{OH} = –150 µA	25°C	3.9	4.1		V
		I_{OH} = –1.5 mA		3.8	4		
		I_{OH} = –15 mA		3.4	3.7		
		I_{OH} = –100 µA	Full range	3.75			
		I_{OH} = –1 mA		3.65			
		I_{OH} = –10 mA		3.45			
V_{OL}	Low-level output voltage	I_{OL} = 150 µA	25°C		75	125	mV
		I_{OL} = 1.5 mA			150	225	
		I_{OL} = 15 mA			1.2	1.6	V
		I_{OL} = 100 µA	Full range			200	mV
		I_{OL} = 1 mA				250	
		I_{OL} = 10 mA				1.45	V
A_{VD}	Large-signal differential voltage amplification	V_{IC} = 2.5 V, R_L = 2 kΩ, V_O = 1 V to –1.5 V	25°C	50	95		V/mV
			Full range	5			
r_i	Input resistance		25°C		70		MΩ
c_i	Input capacitance		25°C		2.5		pF
z_o	Open-loop output impedance	f = 1 MHz	25°C		3.		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}(min), R_S = 50 Ω	25°C	85	118		dB
			Full range	80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}/\Delta V_{IO}$)	$V_{CC\pm}$ = ±2.5 V to ±15 V, R_S = 50 Ω	25°C	90	106		dB
			Full range	85			
I_{CC}	Supply current	V_O = 2.5 V, No load, V_{IC} = 2.5 V	25°C		13.2	17.6	mA
			Full range			18.4	

(1) Full range is –55°C to 125°C.

Copyright © 2008, Texas Instruments Incorporated

TLE2144 OPERATING CHARACTERISTICS

V_{CC} = 5 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLE2144			UNIT
				MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, R_L = 2 kΩ(1), C_L = 500 pF			45		V/µs
SR–	Negative slew rate	A_{VD} = –1, R_L = 2 kΩ(1), C_L = 500 pF			42		V/µs
t_s	Settling time	A_{VD} = –1, 2.5-V step	To 0.1%		0.16		µs
			To 0.01%		0.22		
V_n	Equivalent input noise voltage	R_S = 20 Ω	f = 10 Hz		15		nV/√Hz
			f = 1 kHz		10.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48		µV
		f = 0.1 Hz to 10 Hz			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.92		pA/√Hz
		f = 1 kHz			0.5		
THD+N	Total harmonic distortion plus noise	V_O = 1 V to 3 V, R_L = 2 kΩ(1), A_{VD} = 2, f = 10 kHz			0.0052		%
B_1	Unity-gain bandwidth	R_L = 2 kΩ(1), C_L = 100 pF			5.9		MHz
	Gain-bandwidth product	R_L = 2 kΩ(1), C_L = 100 pF, f = 100 kHz			5.8		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 2 V, R_L = 2 kΩ(1), A_{VD} = 1			660		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ(1), C_L = 100 pF			57		°

(1) R_L terminated at 2.5 V.

Copyright © 2008, Texas Instruments Incorporated

TLE2144 ELECTRICAL CHARACTERISTICS

V_{CC} = ±15 V, at specified free-air temperature (unless otherwise noted)

PARAMETER		TEST CONDITIONS		T_A (1)	TLE2144			UNIT
					MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω		25°C		0.6	2.4	mV
				Full range			4	
α_{VIO}	Temperature coefficient of input offset voltage	V_{IC} = 0, R_S = 50 Ω		25°C		1.7		µV/°C
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω		25°C		7	100	nA
				Full range			250	
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω		25°C		–0.7	–1.5	µA
				Full range			–1.8	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		25°C	–15 to 13	–15.3 to 13.2		V
				Full range	–15 to 12.7	–15.3 to 12.9		
V_{OM+}	Maximum positive peak output voltage swing	I_O = –150 µA		25°C	13.8	14.1		V
		I_O = –1.5 mA			13.7	14		
		I_O = –15 mA			13.1	13.7		
		I_O = –100 µA		Full range	13.7			
		I_O = –1 mA			13.6			
		I_O = –10 mA			13.1			
$V_{OM–}$	Maximum negative peak output voltage swing	I_O = 150 µA		25°C	–14.7	–14.9		V
		I_O = 1.5 mA			–14.5	–14.8		
		I_O = 15 mA			–13.4	–13.8		
		I_O = 100 µA		Full range	–14.6			
		I_O = 1 mA			–14.5			
		I_O = 10 mA			–13.4			
A_{VD}	Large-signal differential voltage amplification	V_O = ±10 V, R_L = 2 kΩ		25°C	100	170		V/mV
				Full range	20			
r_i	Input resistance			25°C		65		MΩ
c_i	Input capacitance			25°C		2.5		pF
z_o	Open-loop output impedance	f = 1 MHz		25°C		30		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}(min), R_S = 50 Ω		25°C	85	108		dB
				Full range	80			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC±}/\Delta V_{IO}$)	$V_{CC±}$ = ±2.5 V to ±15 V, R_S = 50 Ω		25°C	90	106		dB
				Full range	85			
I_{OS}	Short-circuit output current	V_O = 0	V_{ID} = 1 V	25°C	–25	–50		mA
			V_{ID} = –1 V		20	31		
I_{CC}	Supply current	V_O = 0, No load, V_{IC} = 2.5 V		25°C		13.8	18	mA
				Full range			18.8	

(1) Full range is –55°C to 125°C.

Copyright © 2008, Texas Instruments Incorporated

TLE2144 OPERATING CHARACTERISTICS

V_{CC} = ±15 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS		TLE2144			UNIT
				MIN	TYP	MAX	
SR+	Positive slew rate	A_{VD} = –1, R_L = 2 kΩ, C_L = 100 pF		27	45		V/µs
SR–	Negative slew rate	A_{VD} = –1, R_L = 2 kΩ, C_L = 100 pF		27	42		V/µs
t_s	Settling time	A_{VD} = –1, 10-V step	To 0.1%		0.34		µs
			To 0.01%		0.4		
V_n	Equivalent input noise voltage	R_S = 20 Ω	f = 10 Hz		15		nV/√Hz
			f = 1 kHz		10.5		
$V_{n(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 1 Hz			0.48		µV
		f = 0.1 Hz to 10 Hz			0.51		
I_n	Equivalent input noise current	f = 10 Hz			1.89		pA/√Hz
		f = 10 kHz			0.47		
THD+N	Total harmonic distortion plus noise	$V_{O(PP)}$ = 20 V, R_L = 2 kΩ, A_{VD} = 10, f = 10 kHz			0.01		%
B_1	Unity-gain bandwidth	R_L = 2 kΩ, C_L = 100 pF			6		MHz
	Gain-bandwidth product	R_L = 2 kΩ, C_L = 100 pF, f = 100 kHz			5.9		MHz
B_{OM}	Maximum output-swing bandwidth	$V_{O(PP)}$ = 20 V, A_{VD} = 1, R_L = 2 kΩ, C_L = 100 pF			668		kHz
ϕ_m	Phase margin at unity gain	R_L = 2 kΩ, C_L = 100 pF			58		°

Copyright © 2008, Texas Instruments Incorporated

TYPICAL CHARACTERISTICS

Table of Graphs

V_{IO}	Input offset voltage		Distribution	Figure 1, Figure 2, Figure 3
I_{IO}	Input offset current		vs Free-air temperature	Figure 4
I_{IB}	Input bias current		vs Common-mode input voltage	Figure 5
			vs Free-air temperature	Figure 6
V_{OM+}	Maximum positive peak output voltage		vs Supply voltage	Figure 7
			vs Free-air temperature	Figure 8
			vs Output current	Figure 9
			vs Settling time	Figure 11
V_{OM-}	Maximum negative peak output voltage		vs Supply voltage	Figure 7
			vs Free-air temperature	Figure 8
			vs Output current	Figure 10
			vs Settling time	Figure 11
$V_{O(PP)}$	Maximum peak-to-peak output voltage		vs Frequency	Figure 12
V_{OH}	High-level output voltage		vs Output current	Figure 13
V_{OL}	Low-level output voltage		vs Output current	Figure 14
	Phase shift		vs Frequency	Figure 15
A_{VD}	Large-signal differential voltage amplification		vs Frequency	Figure 15
			vs Free-air temperature	Figure 16
z_o	Closed-loop output impedance		vs Frequency	Figure 17
I_{OS}	Short-circuit output current		vs Free-air temperature	Figure 18
CMRR	Common-mode rejection ratio		vs Frequency	Figure 19
			vs Free-air temperature	Figure 20
k_{SVR}	Supply-voltage rejection ratio		vs Frequency	Figure 21
			vs Free-air temperature	Figure 22
I_{CC}	Supply current		vs Supply voltage	Figure 23
			vs Free-air temperature	Figure 24
V_n	Equivalent input noise voltage		vs Frequency	Figure 25
V_n	Input noise voltage		Over a 10-second period	Figure 26
I_n	Noise current		vs Frequency	Figure 27
THD+N	Total harmonic distortion plus noise		vs Frequency	Figure 28
SR	Slew rate		vs Free-air temperature	Figure 29
			vs Load capacitance	Figure 30
	Pulse response	Noninverting large signal	vs Time	Figure 31
		Inverting large signal	vs Time	Figure 32
		Small signal	vs Time	Figure 33
B_1	Unity-gain bandwidth		vs Load capacitance	Figure 34
	Gain margin		vs Load capacitance	Figure 35
ϕ_m	Phase margin		vs Load capacitance	Figure 36

Copyright © 2008, Texas Instruments Incorporated

TLE2141
DISTRIBUTION OF
INPUT OFFSET VOLTAGE




Figure 1.

TLE2142
DISTRIBUTION OF
INPUT OFFSET VOLTAGE




Figure 2.

TLE2144
DISTRIBUTION OF
INPUT OFFSET VOLTAGE




Figure 3.

INPUT OFFSET CURRENT
vs
FREE-AIR TEMPERATURE




Figure 4.

Copyright © 2008, Texas Instruments Incorporated

INPUT BIAS CURRENT vs COMMON-MODE INPUT VOLTAGE




Figure 5.

INPUT BIAS CURRENT vs FREE-AIR TEMPERATURE




Figure 6.

MAXIMUM PEAK OUTPUT VOLTAGE vs SUPPLY VOLTAGE




Figure 7.

MAXIMUM PEAK OUTPUT VOLTAGE vs FREE-AIR TEMPERATURE




Figure 8.

MAXIMUM POSITIVE PEAK OUTPUT VOLTAGE vs OUTPUT CURRENT




Figure 9.

MAXIMUM NEGATIVE PEAK OUTPUT VOLTAGE vs OUTPUT CURRENT




Figure 10.

MAXIMUM PEAK OUTPUT VOLTAGE vs SETTLING TIME




Figure 11.

MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE vs FREQUENCY




Figure 12.

Copyright © 2008, Texas Instruments Incorporated

HIGH-LEVEL OUTPUT VOLTAGE vs OUTPUT CURRENT




Figure 13.

LOW-LEVEL OUTPUT VOLTAGE vs OUTPUT CURRENT




Figure 14.

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION AND PHASE SHIFT vs FREQUENCY




Figure 15.

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION vs FREE-AIR TEMPERATURE




Figure 16.

Copyright © 2008, Texas Instruments Incorporated

CLOSED-LOOP OUTPUT IMPEDANCE vs FREQUENCY




Figure 17.

SHORT-CIRCUIT OUTPUT CURRENT vs FREE-AIR TEMPERATURE




Figure 18.

COMMON-MODE REJECTION RATIO vs FREQUENCY




Figure 19.

COMMON-MODE REJECTION RATIO vs FREE-AIR TEMPERATURE




Figure 20.

Copyright © 2008, Texas Instruments Incorporated

SUPPLY-VOLTAGE REJECTION RATIO
vs
FREQUENCY




Figure 21.

SUPPLY-VOLTAGE REJECTION RATIO
vs
FREE-AIR TEMPERATURE




Figure 22.

SUPPLY CURRENT
vs
SUPPLY VOLTAGE




Figure 23.

SUPPLY CURRENT
vs
FREE-AIR TEMPERATURE




Figure 24.

EQUIVALENT INPUT NOISE VOLTAGE
vs
FREQUENCY




Figure 25.

INPUT NOISE VOLTAGE
OVER A 10-SECOND PERIOD




Figure 26.

NOISE CURRENT
vs
FREQUENCY




Figure 27.

TOTAL HARMONIC DISTORTION
PLUS NOISE
vs
FREQUENCY




Figure 28.

Copyright © 2008, Texas Instruments Incorporated

SLEW RATE vs FREE-AIR TEMPERATURE




Figure 29.

SLEW RATE vs LOAD CAPACITANCE




Figure 30.

NONINVERTING LARGE-SIGNAL PULSE RESPONSE




Figure 31.

INVERTING LARGE-SIGNAL PULSE RESPONSE




Figure 32.

Copyright © 2008, Texas Instruments Incorporated

SMALL-SIGNAL
PULSE RESPONSE




Figure 33.

UNITY-GAIN BANDWIDTH
vs
LOAD CAPACITANCE




Figure 34.

GAIN MARGIN
vs
LOAD CAPACITANCE




Figure 35.

PHASE MARGIN
vs
LOAD CAPACITANCE




Figure 36.

Copyright © 2008, Texas Instruments Incorporated

APPLICATION INFORMATION

Input Offset Voltage Nulling

The TLE2141 offers external null pins that can be used to further reduce the input offset voltage. If this feature is desired, connect the circuit of Figure 37 as shown. If external nulling is not needed, the null pins may be left unconnected.




Figure 37. Input Offset Voltage Null Circuit

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TLE2141MDREP	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	2141EP
TLE2141MDREP.A	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	2141EP
TLE2144MDWREP	Active	Production	SOIC (DW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	TLE2144MEP
TLE2144MDWREP.A	Active	Production	SOIC (DW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	TLE2144MEP
V62/08620-01XE	Active	Production	SOIC (D) | 8	2500 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	2141EP
V62/08620-03YE	Active	Production	SOIC (DW) | 16	2000 | LARGE T&R	Yes	NIPDAU	Level-1-260C-UNLIM	-55 to 125	TLE2144MEP

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF TLE2141-EP, TLE2144-EP :


- Catalog : TLE2141, TLE2144
- Automotive : TLE2141-Q1
- Military : TLE2141M, TLE2144M

NOTE: Qualified Version Definitions:


- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Military - QML certified for Military and Defense Applications

TAPE AND REEL INFORMATION

REEL DIMENSIONS




TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers


QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLE2141MDREP	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2144MDWREP	SOIC	DW	16	2000	330.0	16.4	10.75	10.7	2.7	12.0	16.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TLE2141MDREP	SOIC	D	8	2500	353.0	353.0	32.0
TLE2144MDWREP	SOIC	DW	16	2000	350.0	350.0	43.0

GENERIC PACKAGE VIEW


DW 16

SOIC - 2.65 mm max height


7.5 x 10.3, 1.27 mm pitch

SMALL OUTLINE INTEGRATED CIRCUIT

This image is a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.



4224780/A




PACKAGE OUTLINE

DW0016A


SOIC - 2.65 mm max height

SOIC




NOTES:

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm, per side.
5. Reference JEDEC registration MS-013.



LAND PATTERN EXAMPLE
SCALE:7X




SOLDER MASK DETAILS

4220721/A 07/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.




SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE:7X

4220721/A 07/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.




PACKAGE OUTLINE

D0008A


SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT




NOTES:

1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE
BASED ON .005 INCH [0.125 MM] THICK STENCIL
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale, TI’s General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025