IEC Appliance Inlet C14 with Filter, Circuit Breaker TA35 (recessed)



Screw-on with IP 67



Screw-on A



Screw-on B

C14 70° C

C18 70° C

See below:
Approvals and Compliances

Description
- Panel mount :
  Screw-on or snap-in mounting from front side
- 3 Functions :
  Appliance Inlet protection class I or II , Circuit breaker type TA35 2-pole , Line filter in standard and medical version
- Quick connect terminals 6.3 x 0.8 mm

Unique Selling Proposition
- IP67 protection
- Recessed rocker switch
- Various mounting options
- V-Lock cord retaining

Characteristics
- All single elements are already wired
- Circuit Breaker non-illuminated or illuminated
- Suitable for use in equipment according to IEC/UL 60950
  Suitable for use in medical equipment according to IEC/UL 60601-1

Other versions on request
- Other rocker marking
- Medical version M80
- Capacitance CX1
- Variants in white
- Filter version with high inductance

References
Alternative: version without line filter DG11

Weblinks
pdf data sheet, html data sheet, General Product Information, Distributor-Stock-Check, Accessories, Detailed request for product, Landing Page

Technical Data

Ratings IEC	1 - 10 A @ Ta 40 °C / 250 VAC; 50 Hz
Ratings UL/CSA	1 - 15 A @ Ta 40 °C / 250 VAC; 60 Hz
Leakage Current	standard < 0.5 mA (250 V / 60 Hz) medical < 5 µA (250 V / 60 Hz)
Dielectric Strength	> 1.7 kVDC between L-N > 2.7 kVDC between L/N-PE Test voltage (2 sec)
Allowable Operation Temperature	-25 °C to 60 °C
Climatic Category	25/060/21 acc. to IEC 60068-1
IP-Protection	from front side IP 40 or IP 65 / IP 67 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class I or II acc. to IEC 61140
Terminal	Quick connect terminals 6.3 x 0.8 mm
Panel Thickness S	Screw: max 8 mm Mounting screw torque max 0.5 Nm : S =1.0/1.2/1.5/2.0/2.5/3.0 mm
Material: Housing	Thermoplastic, black, UL 94V-0

appliance inlet/-outlet	C14 C18 acc. to IEC 60320-1 UL 498, CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 10 A, Protection Class I or II
Circuit Breakers	Acc. IEC/EN 60934, UL 1077, CSA 22.2 no. 235 2-pole rocker switch, illuminated or non-illuminated. Optional with undervoltage- or remote trip release Short circuit capacity Icn: 2000 A
Line Filter	Standard and Medical Version, IEC 60939, UL 60939-3, CSA C22.2 no. 8 Technical Details
MTBF	> 100'000 h acc. to MIL-HB-217 F

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products.

Approval Reference Type: DG12

Approval Logo	Certificates	Certification Body	Description
	VDE Approvals	VDE	Certificate Number: 40049092
	UL Approvals	UL	UL File Number: E495089

Product standards

Product standards that are referenced

Organization	Design	Standard	Description
	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes
	Designed according to	IEC 60939	Passive filters for suppressing electromagnetic interference
	Designed according to	IEC 61058-1	Switches for appliances. Part 1. General requirements
	Designed according to	UL 498	Standard for Attachment Plugs and Receptacles
	Designed according to	UL 60939-3	Electromagnetic interference filters
	Designed according to	CSA C22.2 no. 42	General Use Receptacles, Attachment Plugs, and Similar Wiring Devices
	Designed according to	CSA C22.2 no. 8	Electromagnetic interference (EMI) filters

Application standards

Application standards where the product can be used


Organization	Design	Standard	Description
	Designed for applications acc.	IEC/UL 60950	IEC 60950-1 includes the basic requirements for the safety of information technology equipment.
	Designed for applications acc.	IEC 60601-1	Medical electrical equipment - Part 1: General requirements for basic safety and essential performance

Compliances


The product complies with following Guide Lines

Identification	Details	Initiator	Description
	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
	RoHS	SCHURTER AG	EU Directive RoHS 2011/65/EU
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.
		SCHURTER AG	V-Lock system are based on a matching plug-dose combination. The connector is equipped with a notch intended for use with the latching cordset. The cord latching system prevents against accidental removal of the cordset.
	Medical Equipment	SCHURTER AG	Suitable for use in medical equipment according to IEC/UL 60601-1


Dimensions [mm]
Snap-in version




Screw-on A



Screw-on B



Screw-on with IP 67




Technical Data of Filter-Components

Rated Current [A]	Filter-Type	Inductances L [mH]	Capacitance CX [nF]	Capacitance CY [nF]	R [MΩ]
1	Standard Version	2 x 12	220	2.2	1
2	Standard Version	2 x 5.2	220	2.2	1
3	Standard Version	2 x 4	220	2.2	1
4	Standard Version	2 x 2	220	2.2	1
6	Standard Version	2 x 0.8	220	2.2	1
8	Standard Version	2 x 0.6	220	2.2	1
10	Standard Version	2 x 0.4	220	2.2	1
15	Standard Version	2 x 0.1	220	2.2	1
10	Medical Version (M5)	2 x 0.4	220	-	1


Diagrams

Standard Version, medical Version M80




1) Line, 2) Load

Medical version M5, protection class I



1) Line, 2) Load

Medical version M5, protection class II




1) Line
2) Load

Attenuation Loss


- - - - 50Ω differential mode _____ 50Ω common mode

Standard version


1 A




2 A




3 A




4 A




6 A




8 A



10 A




15 A




Medical version (M5)


1 A




2 A




3 A




4 A




6 A




8 A



10 A



15 A




Effect of ambient temperature

Ambient Temperature [°C]	Correction factor
-30	0.76
-20	0.81
0	0.90
+23	1.00
+40	1.03
+50	1.04
+60	1.06


Time-Current-Curves

Tripping Characteristics I_n < 3 A



Reference Temperature +23°

Tripping Characteristics In ≥ 3 ... ≤ 15 A



Reference Temperature +23°

Configuration Code

Type	Configuration Code TA35										
DG12	-	CBDWM100C0-000-C6135	-	X	X	X	-	X	X	X	X	-	0	0

Customer specific type

Color

0	Black
1	White 3)

Panel Mounting 1)

00	Screw version A front mounting
01	Screw version B front mounting
10	Snap-in 1.0 mm
12	Snap-in 1.2 mm
15	Snap-in 1.5 mm
20	Snap-in 2.0 mm
25	Snap-in 2.5 mm
30	Snap-in 3.0 mm
88	Screw version front mounting (sealed towards housing, IP67)

Terminal PE

0	Without (PCII)
1	QC 6.3x0.8 mm

Type of mains filter (inductance)

0	standard inductance
1	higher inductance

Type of mains filter (capacitor)

1	standard	X2=100nF, Y2=2200pF
2	standard	X2=220nF, Y2=2200pF
3	standard	X1=47nF, Y1=2200pF
4	medical M5	X2=100nF
5	medical M5	X2=220nF
6	medical M5	X1=47nF
7	medical M80	X2=100nF, Y2=470pF
8	medical M80	X2=220nF, Y2=470pF
9	medical M80	X1=47nF, Y1=470pF


Type of mains filter (rated current) 2)

1	1A
2	2A
3	3A
4	4A
5	6A
6	8A
7	10A
8	15A (UL), 10A (IEC), 10A (GB)

Configuration Code TA35 2)
See configuration code of TA35 rocker 2pole

1)




Screw version A


Screw version B

2) The rated current of the line-filter must not be exceeded in the end application.

3) Only on request (approvals pending)

ORDER CODE

Number of switched poles		2-pole	
Number of protected poles		1	2
			
Switch	without illumination	**CBT**	**CBD**
Switch	illuminated 240 V	**C12**	**C32**
	illuminated 120 V	**C14**	**C34**

Other versions on request

Table 1 Selection for type TA35

Order example

TA35- | **CBD** | **W** | **F** | **120** | **C0**

C0: No other features

Colours

	Switch front	Rocker non-illuminated	Rocker illuminated
W	black	white	–
B	black	black	–
3	black	–	red transparent
4	black	–	green transparent
6	black	–	orange transparent


Other colours on request

Rocker legend

	Surface	Illustration		Colour of print
F	embossed	–	0	
H	printed	ON	OFF	white
K	printed	ON	OFF	black
L	printed	–	0	white
M	printed	–	0	black

Other legends on request

Position of the rocker legend e.g. I / O



Rated current I_n (A)

I_n	Code	I_n	Code
1,0	**J10**	8,0	**080**
2,0	**J20**	10,0	**100**
4,0	**040**	12,0	**120***
5,0	**050**	15,0	**150***
6,0	**060**		

Other rated currents on request

*) UL / CSA only

Variants

Circuit Breaker				Filter		Connector				
Rated Current [A]	Rocker colour	Illumination	TA35 Code	Rated Current [A]	Filter Type	Protection Class	Color	Mounting	IP-Protection	Order Number
1	black	non-illuminated	CBDBLJ10C0	1	Standard Version	I	**black**	Screw-on A	IP 40	3-108-854
10	white	non-illuminated	CBDWM100C0	10	Standard Version	I	**black**	Screw-on A	IP 40	3-109-572
10	white	non-illuminated	CBDWM100C0	10	Standard Version	I	**black**	Snap-in 1.5	IP 40	3-109-575
10	white	non-illuminated	CBDWM100C0	10	Standard Version	I	**black**	Screw B	IP 40	3-109-698
10	white	non-illuminated	CBDWM100C0	10	Standard Version	I	**black**	Screw	IP 67	3-118-974
15	white	non-illuminated	CBDWM150C0	15	Standard Version	I	**black**	Screw-on A	IP 40	3-109-573
2	white	non-illuminated	CBDWMJ20C0	2	Standard Version	I	**black**	Screw-on A	IP 40	3-109-557
3	white	non-illuminated	CBDWM030C0	3	Standard Version	I	**black**	Screw-on A	IP 40	3-109-558
4	black	non-illuminated	CBDBF040C0	4	Standard Version	I	**black**	Screw-on A	IP 40	3-109-559
6	white	non-illuminated	CBDWM060C0	6	Standard Version	I	**black**	Screw-on A	IP 40	3-109-560
8	white	non-illuminated	CBDWM080C0	8	Standard Version	I	**black**	Screw-on A	IP 40	3-109-561
10	white	non-illuminated	CBDWM100C0	10	Medical Version (M5)	I	**black**	Screw-on A	IP 40	3-108-465
10	white	non-illuminated	CBDWM100C0	10	Medical Version (M5)	I	**black**	Screw B	IP 40	3-118-982

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit 10 Pcs

Mating Outlets/Connectors



Category / Description

Appliance Outlet Overview complete

4787, Mounting: Screw-on mounting, Appliance Outlet: IEC Solder terminals, 10 A, Suitable for appliances with protection class I	4787
4788, Mounting: Snap-in version, Appliance Outlet: IEC Solder terminals or quick connect terminals, 10 A, Suitable for appliances with protection class I	4788
IEC Appliance Outlet F or H, Screw-on Mounting, Front Side, Solder, PCB or Quick-connect Terminal	5091

Appliance Outlet further types to DG12



Connector Overview complete

4782 Mounting: Power Cord, 3 x 1 mm² / 3 x 18 AWG, Cable, Connector: IEC C13	4782
4785 Mounting: Power Cord, 3 x 1 mm² / 3 x 18 AWG, Cable, Connector: IEC C13	4785
4300-06 Mounting: Power Cord, 3 x 1 mm² / 3 x 18 AWG, Cable, Connector: IEC C13	4300-06
4781 Mounting: Power Cord, 3 x 1 mm² / 3 x 18 AWG, Cable, Connector: IEC C15	4781
4784 Mounting: Power Cord, 3 x 1 mm² / 3 x 18 AWG, Cable, Connector: IEC C15	4784
Connector further types to DG12	...

Mating Outlets/Connectors shuttered



Power Cord Overview complete

VAC13KS, Overview, V-Lock cord retaining, diverse Connector IEC C13, diverse, black	VAC13KS

Power Cord further types to DG12

30.01.2019

The specifications, descriptions and illustrations indicated in this document are based on current information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each product selected for their own applications.