

SERIES: VFK400W | DESCRIPTION: DC-DC CONVERTER

FEATURES

- up to 400 W isolated output
- rugged metal enclosure with integrated heat sink
- 4:1 input range (10~36 Vdc, 18~75 Vdc)
- single output from 12~48 Vdc
- 1,500 Vdc isolation
- over current, over temperature, over voltage, and short circuit protection
- remote on/off
- efficiency up to 87%




MODEL

MODEL	input voltage range (Vdc)	output voltage (Vdc)	output current max (A)	output power max (W)	ripple and noise ¹ max (mVp-p)	efficiency max (%)
VFK400W-Q24-S12	10~36	12	33.3	400	200	87.0
VFK400W-Q24-S24	10~36	24	16.7	400	240	86.0
VFK400W-Q24-S48	10~36	48	8.3	398	480	86.0
VFK400W-Q48-S12 ²	20~75	12	33.3	400	200	87.0
VFK400W-Q48-S24	18~75	24	16.7	400	240	86.0
VFK400W-Q48-S48	18~75	48	8.3	398	480	86.5

Note: 1. Ripple and noise are measured at full load, 20 MHz BW with 10μF tantalum capacitor and 1μF ceramic capacitor across the output. The 48 Vdc output models require a 22μF aluminum capacitor and a 1μF ceramic capacitor across the output.
2. An external input capacitor of 470μF is recommended to reduce input ripple voltage.

PART NUMBER KEY



INPUT

parameter	conditions/description		min	typ	max	units
operating input voltage	24 Vdc input		10	24	36	Vdc
	48 Vdc input	12 Vdc output model 24/48 Vdc output models	20 18	48 48	75 75	Vdc Vdc
under voltage shutdown	24 Vdc input	power up power down		9.5 8.5		Vdc Vdc
	48 Vdc input	power up power down		17.8 15.5		Vdc Vdc
CTRL ¹	positive logic	models ON (open circuit)				
		models OFF (0~1.2 Vdc)				
filter	pi filter					

Note: 1. Do not drive high, may damage device.

OUTPUT

parameter	conditions/description		min	typ	max	units
maximum output capacitance	for all models				2,200	µF
line regulation	measured from high line to low line				±1	%
load regulation	measured from full load to zero load				±1	%
voltage accuracy					±1.5	%
adjustability			90		105	%
switching frequency				250		kHz
transient response	25% step load change				500	µs
temperature coefficient				±0.03		%/°C

PROTECTIONS

parameter	conditions/description		min	typ	max	units
short circuit protection	continuous					
over current protection	% nominal output current		110		150	%
over voltage protection			115		140	%
over temperature protection	shutdown			110		°C

SAFETY AND COMPLIANCE

parameter	conditions/description		min	typ	max	units
isolation voltage	for 1 minute: input to output; input to case; output to case		1,500			Vdc
isolation resistance			10			MΩ
RoHS	yes					

ENVIRONMENTAL

parameter	conditions/description		min	typ	max	units
operating temperature	see derating curves		-40		85	°C
storage temperature			-55		105	°C

MECHANICAL



parameter	conditions/description	min	typ	max	units
dimensions	198.90 x 127.00 x 38.93 [7.831 x 5.000 x 1.533 inch]				mm
case material	steel and aluminum extrusion				
weight			1.18		kg

MECHANICAL DRAWING



units: mm[inch]
tolerance: X.X = $\pm 0.5[\pm 0.02]$
 X.XX = $\pm 0.25[\pm 0.010]$

wire range: 22~12 AWG
screw size: #6-32

PIN CONNECTIONS	
PIN	FUNCTION
1, 2	+Vin
3, 4	-Vin
5	on/off
6	case
7, 8	+Vout
9	+S
10	trim
11	-S
12, 13	-Vout



DERATING CURVES



APPLICATION NOTES

1. Output Voltage Trimming

Leave open if not used.

Figure 1
Application Circuit for Trim pin




Table 1
Trim Up Resistor Values (MΩ)¹

Desired Vout (%Vout) Nom. Vout (Vdc)	101	102	103	104	105
	(%)	(%)	(%)	(%)	(%)
12	2.2	1.6	1.2	0.82	0.68
24	4.3	3.3	2.2	1.6	1.5
48	10	6.8	4.8	3.9	3.5

Table 2
Trim Down Resistor Values (KΩ)

Desired Vout (%Vout) Nom. Vout (Vdc)	90	92	94	96	98
	(%)	(%)	(%)	(%)	(%)
12	9	12	22	51	100
24	12	22	51	100	300
48	22	32	49	100	300

Note: 1. VFK400W-Q48-S12 model requires minimum input voltage of 21.6 Vdc in order to trim between 100~105%.

Note: All specifications measured at 25°C, nominal input voltage, and full load unless otherwise noted.

REVISION HISTORY

rev.	description	date
1.0	initial release	03/13/2012
1.01	updated adjustability range	09/20/2012
1.02	corrected weight	12/18/2012
1.03	updated spec	04/01/2013
1.04	added trimming information	01/03/2014
1.05	CTRL line updated	11/13/2020
1.06	derating curves and trim circuit figure updated	09/13/2021
1.07	CE removed from safety marks	02/25/2022
1.08	CE added to safety marks	09/02/2022
1.09	company address updated	11/20/2024
1.10	datasheet updated	05/29/2025

The revision history provided is for informational purposes only and is believed to be accurate.



CUI INC
a bel group

15575 SW Sequoia Pkwy #100
Portland, OR 97224
800.275.4899

Fax 503.612.2383
Belfuse.com
powersupport@belf.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.